

sulfuric acid, conc=93-99.5%

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	: sulfuric acid, conc=93-99.5%
Synonyms	: sulfuric-acid-
Registration number REACH	: 01-2119458838-20-0102 (Nyrstar Belgium NV/SA) 01-2119458838-20-0086 (Nyrstar Budel BV) 01-2119458838-20-0103 (Nyrstar France SAS)
Product type REACH	: Substance/mono-constituent
CAS number	: 7664-93-9
EC index number	: 016-020-00-8
EC number	: 231-639-5
Molecular mass	: 98.08 g/mol
Formula	: H ₂ SO ₄

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

- IU01: Production of sulphuric acid (ES1)
 - IU02: Use of sulphuric acid as an intermediate in manufacture of inorganic and organic chemicals incl. fertilizers (ES2)
 - IU03: Use of sulphuric acid as a processing aid, catalyst, dehydrating agent, pH regulator (ES3)
 - IU04: Use of sulphuric acid for extractions and processing of minerals, ores (ES4)
 - IU05: Use of sulphuric acid in the process of surface treatments, purification and etching (ES5)
 - IU06: Use of sulphuric acid in electrolytic processes (ES6)
 - IU07: Use of sulphuric acid in gas purification, scrubbing, flue gas scrubbing (ES7)
 - IU08: Use of sulphuric acid in production of sulphuric acid contained batteries (ES8)
 - IU09: Use of sulphuric acid in maintenance of sulphuric acid contained batteries (ES9)
 - IU10: Use of sulphuric acid in recycling of sulphuric acid contained batteries (ES10)
 - IU11: Use of sulphuric acid contained batteries (ES11)
 - IU12: Use of sulphuric acid as laboratory chemicals (ES12)
 - IU13: Use of sulphuric acid in industrial cleaning (ES13)
 - IU14: mixing, preparation and repackaging of sulphuric acid (ES14)
- For more detailed information regarding the Identified Uses and the associated Exposure Scenarios: see attached annex

1.2.2 Uses advised against

No uses advised against known

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

Nyrstar Belgium N.V. on behalf of Nyrstar Sales & Marketing A.G.
Zinkstraat 1
B-2490 Balen
☎ +32 14 44 95 00
✉ +32 14 81 05 31
infoSDS@nyrstar.com

Nyrstar Budel B.V. on behalf of Nyrstar Sales & Marketing A.G.
Hoofdstraat 1
6024 AA Budel-Dorplein
☎ +32 14 44 96 80
✉ +32 14 44 95 52
infoSDS@nyrstar.com

Nyrstar France S.A.S. on behalf of Nyrstar Sales & Marketing A.G.
Rue Jean Jacques Rousseau
F-59950 Aubry
☎ +32 14 44 96 80
✉ +33 3 27 88 39 48
infoSDS@nyrstar.com

Manufacturer of the product

Nyrstar Sales & Marketing SA
1 Rue de Jargonant
CH-1207 Geneva
infoSDS@nyrstar.com

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) :
+32 14 58 45 45 (BIG)

sulfuric acid, conc=93-99.5%

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Skin Corr.	category 1A	H314: Causes severe skin burns and eye damage.
Eye Dam.	category 1	H318: Causes serious eye damage.

2.2. Label elements



Signal word Danger

H-statements

H314 Causes severe skin burns and eye damage.

P-statements

P280 Wear protective gloves, protective clothing and eye protection/face protection.
P260 Do not breathe vapours/mist.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse simultaneously with neutralizing agent Diphoterine or equivalent neutralizing agent. Use complete bottle. Rinse under emergency shower for 1 to 2 minutes and continue rinsing under regular shower for 10 minutes with water at 35-36°C
P310 Immediately call a POISON CENTER/doctor.
P305 + P351 IF IN EYES: Rinse cautiously with neutralization agent Diphoterine or equivalent neutralizing agent for several minutes and continue rinsing with water for 10 minutes.
P301 + P330 + P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

2.3. Other hazards

No other hazards known

SECTION 3: Composition/information on ingredients

3.1. Substances

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark
sulfuric acid, conc=93-99.5% 01-2119458838-20	7664-93-9 231-639-5	93%≤C ≤99.5%	Skin Corr. 1A; H314 Eye Dam. 1; H318	(1)(2)(10)	Mono-constituent

(1) For H-statements in full: see heading 16

(2) Substance with a Community workplace exposure limit

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

3.2. Mixtures

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.

After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

After skin contact:

Take off immediately all contaminated clothing and simultaneously rinse with neutralizing agent (BUMB, Diphoterine or equivalent neutralizing agent). Use complete bottle. Continue rinsing under emergency shower for 1 to 2 minutes and continue rinsing under regular shower for 10 minutes with water at 35-36°C. Do not remove clothing if it sticks to the skin. Cover wounds with sterile bandage. Consult a doctor/medical service.

After eye contact:

Rinse cautiously with neutralization agent (BUMB, Diphoterine or equivalent neutralizing agent) for several minutes and continue rinsing with plenty of water during 10 minutes. Take victim to an ophthalmologist.

After ingestion:

Reason for revision: 2.2, 4.1

Publication date: 2001-12-29

Date of revision: 2020-03-26

Revision number: 0103

Product number: 51613

2 / 12

sulfuric acid, conc=93-99.5%

Rinse mouth with water. Immediately after ingestion: give small amount of water to drink. Do not induce vomiting. Do not give activated charcoal. Do not give chemical antidote. Immediately consult a doctor/medical service.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

Dry/sore throat. Coughing. Irritation of the respiratory tract. Irritation of the nasal mucous membranes. ON CONTINUOUS EXPOSURE/CONTACT: Corrosion of the upper respiratory tract. FOLLOWING SYMPTOMS MAY APPEAR LATER: Possible laryngeal spasm/oedema. Risk of pneumonia. Risk of lung oedema. Respiratory difficulties.

After skin contact:

Caustic burns/corrosion of the skin.

After eye contact:

Corrosion of the eye tissue. Permanent eye damage.

After ingestion:

Nausea. Abdominal pain. Blood in stool. Blood in vomit. Burns to the gastric/intestinal mucosa. AFTER INGESTION OF HIGH QUANTITIES: Shock.

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Small fire: Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting CO2 extinguisher.

Major fire: Class B foam (alcohol-resistant); after consulting specialist.

5.1.2 Unsuitable extinguishing media:

Small fire: Water (quick-acting extinguisher, reel); risk of puddle expansion, Quick-acting class B foam extinguisher.

Major fire: Water.

5.2. Special hazards arising from the substance or mixture

On burning: release of toxic and corrosive gases/vapours (sulphur oxides). Violent exothermic reaction with water (moisture): release of corrosive gases/vapours.

5.3. Advice for firefighters

5.3.1 Instructions:

Cool tanks/drums with water spray/remove them into safety. When cooling/extinguishing: no water in the substance. Dilute toxic gases with water spray. Heat exposure: dilute toxic gas/vapour with water spray. Take account of toxic/corrosive precipitation water.

5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Face shield (EN 166). Corrosion-proof suit (EN 14605). Large spills/in enclosed spaces: compressed air apparatus (EN 136 + EN 137). Large spills/in enclosed spaces: gas-tight suit (EN 943). Heat/fire exposure: compressed air apparatus (EN 136 + EN 137).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No naked flames. Keep containers closed. Avoid ingress of water in the containers. Large spills/in confined spaces: consider evacuation.

6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Face shield (EN 166). Corrosion-proof suit (EN 14605). Large spills/in enclosed spaces: compressed air apparatus (EN 136 + EN 137). Large spills/in enclosed spaces: gas-tight suit (EN 943).

Suitable protective clothing

See heading 8.2

6.2. Environmental precautions

Contain released product, pump into suitable containers. Plug the leak, cut off the supply. Dam up the liquid spill. Prevent soil and water pollution. Prevent spreading in sewers.

6.3. Methods and material for containment and cleaning up

Neutralize spill with lime, sodium bicarbonate, soda (sodium carbonate) or soda ash. Neutralized substance: shovel into closing drums. Carefully collect the spill/leftovers. Damaged/cooled tanks must be emptied. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See heading 13.

sulfuric acid, conc=93-99.5%

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Keep away from naked flames/heat. Gas/vapour heavier than air at 20°C. Observe very strict hygiene - avoid contact. Remove contaminated clothing immediately. Do not discharge the waste into the drain. Never add water to this product. Never dilute by pouring water to the acid. Always add the acid to the water. Keep container tightly closed.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Store in a dry area. Ventilation at floor level. Keep locked up. Protect against frost. Store at ambient temperature. Provide for a tub to collect spills. Unauthorized persons are not admitted. Under a shelter/in the open. Aboveground. Keep only in the original container. Store only in a limited quantity. Meet the legal requirements.

7.2.2 Keep away from:

Heat sources, combustible materials, reducing agents, (strong) bases, metals, cellulosic materials, organic materials, oxidizing agents, alcohols, amines, water/moisture.

7.2.3 Suitable packaging material:

Carbon steel, polyethylene, polypropylene, glass, stoneware/porcelain.

7.2.4 Non suitable packaging material:

Monel steel, lead, aluminium, iron, copper, zinc, nickel, bronze.

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

EU

Sulphur dioxide	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	0.5 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1.3 mg/m ³
	Short time value (Indicative occupational exposure limit value)	1 ppm
	Short time value (Indicative occupational exposure limit value)	2.7 mg/m ³
Sulphuric acid (mist)	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	0.05 mg/m ³

Belgium

Acide sulfurique (brume)	Time-weighted average exposure limit 8 h	0.2 mg/m ³
Soufre (dioxyde de)	Time-weighted average exposure limit 8 h	2 ppm
	Time-weighted average exposure limit 8 h	5.3 mg/m ³
	Short time value	5 ppm
	Short time value	13 mg/m ³

The Netherlands

Zwavedioxide	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	0.7 mg/m ³
	Short time value (Public occupational exposure limit value)	0.7 mg/m ³
Zwavelzuur (nevel), gedefinieerd als de thoracale fractie	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	0.012 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	0.05 mg/m ³

France

Acide sulfurique, fraction thoracique	Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire indicative)	0.05 mg/m ³
	Short time value (VL: Valeur non réglementaire indicative)	3 mg/m ³
Soufre (dioxyde de)	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	2 ppm
	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	5 mg/m ³
	Short time value (VL: Valeur non réglementaire indicative)	5 ppm
	Short time value (VL: Valeur non réglementaire indicative)	10 mg/m ³

Germany

Schwefeldioxid	Time-weighted average exposure limit 8 h (TRGS 900)	1 ppm
----------------	---	-------

Reason for revision: 2.2, 4.1

Publication date: 2001-12-29

Date of revision: 2020-03-26

Revision number: 0103

Product number: 51613

4 / 12

sulfuric acid, conc=93-99.5%

Schwefeldioxid	Time-weighted average exposure limit 8 h (TRGS 900)	2.7 mg/m ³
Schwefelsäure	Time-weighted average exposure limit 8 h (TRGS 900)	0.1 mg/m ³

UK

Sulphuric acid (mist)	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	0.05 mg/m ³
-----------------------	---	------------------------

USA (TLV-ACGIH)

Sulfur dioxide	Short time value (TLV - Adopted Value)	0.25 ppm
Sulfuric acid	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	0.2 mg/m ³ (T)

(T): Thoracic fraction

b) National biological limit values

If limit values are applicable and available these will be listed below.

8.1.2 Sampling methods

Product name	Test	Number
NON-VOLATILE ACIDS (Sulfuric Acid)	NIOSH	7908
Sulfur Dioxide (organic and inorganic gases by Extractive FTIR)	NIOSH	3800
Sulfur Dioxide	NIOSH	6004
Sulfur Dioxide	OSHA	1011
Sulfur Dioxide	OSHA	ID 104
Sulfur Dioxide	OSHA	ID 200
Sulfuric Acid	NIOSH	7903
Sulfuric Acid	OSHA	ID 113
Sulfuric Acid	OSHA	ID 165SG

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 Threshold values

DNEL/DMEL - Workers

sulfuric acid, conc=93-99.5%

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term local effects inhalation	0.05 mg/m ³	
	Acute local effects inhalation	0.1 mg/m ³	
	Acute local effects inhalation	2.7 mg/m ³	SO2
	Long-term local effects inhalation	1.3 mg/m ³	SO2

DNEL/DMEL - General population

sulfuric acid, conc=93-99.5%

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term local effects inhalation	0.53 mg/m ³	SO2

PNEC

sulfuric acid, conc=93-99.5%

Compartment	Value	Remark
Fresh water	0.003 mg/l	
Marine water	0.00025 mg/l	
STP	8.8 mg/l	
Fresh water sediment	0.002 mg/kg sediment dw	
Marine water sediment	0.002 mg/kg sediment dw	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Keep away from naked flames/heat. Measure the concentration in the air regularly. Carry operations in the open/under local exhaust/ventilation or with respiratory protection.

8.2.2 Individual protection measures, such as personal protective equipment

Observe very strict hygiene - avoid contact. Do not eat, drink or smoke during work.

a) Respiratory protection:

Full face mask with filter type E, at concentrations in air higher than the exposure limit for sulfur dioxide (SO₂). Dust/aerosol mask with filter type P3 at concentrations in air higher than the exposure limit for sulfuric acid (H₂SO₄).

b) Hand protection:

Protective gloves against chemicals (EN 374).

Materials	Measured breakthrough time	Thickness	Protection index	Remark
butyl rubber	> 120 minutes	0.5 mm	Class 4	
viton	> 480 minutes	0.4 mm	Class 6	
natural rubber				Poor resistance
nitrile rubber				Poor resistance
chloroprene rubber				Poor resistance
leather				Poor resistance

sulfuric acid, conc=93-99.5%

c) Eye protection:

Face shield (EN 166). Protective goggles (EN 166).

d) Skin protection:

Corrosion-proof clothing (EN 14605).

8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Liquid
Viscosity	Oily
Odour	Odourless
Odour threshold	Not applicable
Colour	Colourless to brown
Translucency	Clear
Particle size	Not applicable (liquid)
Explosion limits	Not applicable
Flammability	Non-flammable
Log Kow	Not relevant
Dynamic viscosity	0.0225 Pa.s ; 20 °C ; 95 %
Kinematic viscosity	Not determined
Melting point	10.4 °C - 10.9 °C ; 100 % -1.11 °C - 3.0 °C ; 98 % -13.89 °C - -10 °C ; 96 % 7.56 °C ; 83 %
Boiling point	290 °C ; 100 % 310 °C - 335 °C ; 98 % 330 °C ; 96 %
Evaporation rate	No data available
Relative vapour density	3.4
Vapour pressure	0.06 hPa ; 20 °C ; 90 %
Solubility	Water ; miscible
Relative density	1.8305 ; 20 °C ; 100 % 1.8361 ; 20 °C ; 98 % 1.8355 ; 20 °C ; 96 % 1.8144 ; 20 °C ; 90 %
Decomposition temperature	No data available
Auto-ignition temperature	Not applicable
Flash point	Not applicable
Explosive properties	No chemical group associated with explosive properties
Oxidising properties	No chemical group associated with oxidising properties
pH	No data available

9.2. Other information

Absolute density	1830.5 kg/m ³ ; 20 °C
------------------	----------------------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Acid reaction.

10.2. Chemical stability

Unstable on exposure to moisture.

10.3. Possibility of hazardous reactions

Violent exothermic reaction with water (moisture): release of corrosive gases/vapours. Reacts with many compounds: (increased) risk of fire/explosion. Reacts exothermically with organic material: risk of spontaneous ignition. Reacts violently with combustible materials: (increased) risk of fire/explosion. Reacts violently with (some) bases: heat release resulting in increased fire or explosion risk. Reacts with (strong) reducers: (increased) risk of fire/explosion.

10.4. Conditions to avoid

Precautionary measures

Keep away from naked flames/heat.

10.5. Incompatible materials

Combustible materials, reducing agents, (strong) bases, metals, cellulosic materials, organic materials, oxidizing agents, alcohols, amines, water/moisture.

10.6. Hazardous decomposition products

Reason for revision: 2.2, 4.1

Publication date: 2001-12-29

Date of revision: 2020-03-26

Revision number: 0103

Product number: 51613

6 / 12

sulfuric acid, conc=93-99.5%

Aqueous solution reacts with (some) metals: release of highly flammable gases/vapours (hydrogen). On burning: release of toxic and corrosive gases/vapours (sulphur oxides).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

11.1.1 Test results

- Toxicokinetics: summary

Basic toxicokinetics: The effects of sulphuric acid are essentially the result of the hydrogen ion (local deposition of H⁺, pH change) rather than an effect of the sulphate ion. Sulphuric acid (as such) is not expected to be absorbed or distributed throughout the body as the acid will rapidly dissociate; the hydrogen ion will form water. The sulphate anion will enter the body electrolyte pool, its kinetics will be governed by sulphate homeostatic mechanisms, and is therefore not predicted to play a specific toxicological role. This supposition is supported by experiments which have studied the active component in inorganic acids on various endpoints, using different acids or salts. The results of these studies lead to the conclusion that the observed effects are due to the hydrogen ion, while the anion appeared to have no effect.

In a study of the clearance of radiolabeled sulphuric acid aerosol in different species, the authors observed that the sulphur from sulphuric acid was rapidly cleared (from 2 -9 minutes) from the lungs of animals into the blood following inhalation exposure (Dahl, 1983). Sulphate is a normal constituent of the blood (present at 0.8 -1.2 mg/dl) and is a normal metabolite of sulphur-containing amino acids. The body has efficient sulphate homeostatic mechanisms and excess sulphate is excreted in the urine (capacity-limited proximal tubular absorption); urinary sulphate concentrations of up to 500 umol/dl/kg bw have been reported. The body pool of this anion is large, and it is therefore unlikely that occupational exposure will significantly add to the normal body burden.

Systemic absorption of the hydrogen ion following dermal or inhalation exposure to sulphuric acid is not predicted to be significant, and the low level of hydrogen ions absorbed will be effectively controlled by the homeostatic mechanisms governing pH including the action of the enzyme carbonic anhydrase and NA⁺/H⁺ exchange in the proximal renal tubule. Although acidemia and metabolic acidosis have been noted following cases of ingestion exposure, similar effects are not predicted following occupational inhalation exposure (which will be much lower and effectively limited by respiratory tract irritation) or following dermal exposure (due to low dermal absorption and local dermal irritation).

The deposition of sulphuric particles in the human lung has been studied extensively. Deposition is influenced by subject age, particle size and breathing rate. Sulphuric acid particles are hygroscopic and therefore will absorb moisture present in the airways, thereby increasing particle size and potentially increasing particle retention. Respiratory mucus has a limited buffering capacity and may reduce tissue contact.

The absence of systemic effects in the large number of toxicity studies performed with sulphuric acid is consistent with this assessment of its toxicokinetics.

The following information is taken into account for any hazard / risk assessment: Primary information is limited to a study of the absorption and kinetics of radiolabelled sulphate following the inhalation of sulphuric acid aerosols. Sulphuric acid immediately dissociates to the hydrogen and sulphate ions, with the hydrogen ion being responsible for the local toxicity (irritation and corrosivity) of sulphuric acid.

Dermal absorption: No dermal absorption is predicted under normal conditions of use, based on the physicochemical properties of the substance. However dermal absorption may occur when the integrity of the skin is lost (i. e. in accidental exposures resulting in burns).

The following information is taken into account for any hazard / risk assessment: No studies are proposed for scientific reasons and (given the corrosive nature of the substance), also reasons of animal welfare. No dermal absorption is predicted under normal conditions of use, based on the physicochemical properties of the substance.

Acute toxicity

sulfuric acid, conc=93-99.5%

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	2140 mg/kg		Rat (male / female)	Experimental value	
Dermal						Not relevant, expert judgement	
Inhalation (aerosol)	LC50	Equivalent to OECD 403	375 mg/m ³ air		Rat (male / female)	Experimental value	

Conclusion

Not classified for acute toxicity

Corrosion/irritation

sulfuric acid, conc=93-99.5%

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Highly corrosive					Literature	
Skin	Highly corrosive					Literature	

Conclusion

Causes severe skin burns and eye damage.

Respiratory or skin sensitisation

sulfuric acid, conc=93-99.5%

No (test) data available

Conclusion

Not classified as sensitizing for skin

Not classified as sensitizing for inhalation

Specific target organ toxicity

sulfuric acid, conc=93-99.5%

Reason for revision: 2.2, 4.1

Publication date: 2001-12-29

Date of revision: 2020-03-26

Revision number: 0103

Product number: 51613

7 / 12

sulfuric acid, conc=93-99.5%

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Inhalation (aerosol)	LOAEC	OECD 412	0.3 mg/m ³ air	Respiratory tract		4 weeks (6h / day, 5 days / week)	Rat (female)	Experimental value

Conclusion

Not classified for subchronic toxicity

Mutagenicity (in vitro)

sulfuric acid, conc=93-99.5%

Result	Method	Test substrate	Effect	Value determination	Remark
Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)		Weight of evidence	
Positive	Equivalent to OECD 473	Chinese hamster ovary (CHO)		Weight of evidence	

Mutagenicity (in vivo)

sulfuric acid, conc=93-99.5%

No (test)data available

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

sulfuric acid, conc=93-99.5%

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (aerosol)	NOEC		100 mg/l air		Hamster (male)	No effect		Weight of evidence
Oral	NOAEL	Carcinogenic toxicity study			Mouse (male / female)			Weight of evidence

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

sulfuric acid, conc=93-99.5%

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEC	Equivalent to OECD 414	19.3 mg/m ³ air	6 days (gestation, daily) - 15 days (gestation, daily)	Mouse (female)	No effect		Experimental value

Conclusion

Not classified for reprotoxic or developmental toxicity

Toxicity other effects

sulfuric acid, conc=93-99.5%

No (test)data available

Chronic effects from short and long-term exposure

sulfuric acid, conc=93-99.5%

ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Red skin. Dry skin. Itching. Skin rash/inflammation. Affection/discolouration of the teeth. Inflammation/damage of the eye tissue.

SECTION 12: Ecological information

12.1. Toxicity

sulfuric acid, conc=93-99.5%

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50		16 mg/l - 28 mg/l	96 h	Lepomis macrochirus	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EC50	OECD 202	> 100 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	ErC50	OECD 201	> 100 mg/l	72 h	Desmodesmus subspicatus	Static system	Fresh water	Experimental value; GLP
Long-term toxicity fish	NOEC		0.025 mg/l	65 day(s)	Jordanella floridae	Flow-through system	Fresh water	Experimental value; Nominal concentration

Reason for revision: 2.2, 4.1

Publication date: 2001-12-29

Date of revision: 2020-03-26

Revision number: 0103

Product number: 51613

8 / 12

sulfuric acid, conc=93-99.5%

Toxicity aquatic micro-organisms	NOEC		26 g/l	37 day(s)	Activated sludge	Static system	Fresh water	Weight of evidence; Nominal concentration
----------------------------------	------	--	--------	-----------	------------------	---------------	-------------	---

Conclusion

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

12.2. Persistence and degradability

Water

Biodegradability: not applicable

Hydrolysis in water

12.3. Bioaccumulative potential

sulfuric acid, conc=93-99.5%

Log Kow

Method	Remark	Value	Temperature	Value determination
				Not relevant

Conclusion

Bioaccumulation: not applicable

12.4. Mobility in soil

No (test) data on mobility of the substance available

12.5. Results of PBT and vPvB assessment

The criteria of PBT and vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006 do not apply to inorganic substances.

12.6. Other adverse effects

sulfuric acid, conc=93-99.5%

Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

Groundwater

Groundwater pollutant

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

06 01 01* (wastes from the manufacture, formulation, supply and use (MFSU) of acids: sulphuric acid and sulphurous acid). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Recycle/reuse. Remove for physico-chemical/biological treatment. Remove to an authorized dump (Class I). Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment.

13.1.3 Packaging/Container

European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road (ADR)

14.1. UN number

UN number	1830
-----------	------

14.2. UN proper shipping name

Proper shipping name	Sulphuric acid
----------------------	----------------

14.3. Transport hazard class(es)

Hazard identification number	80
Class	8
Classification code	C1

14.4. Packing group

Packing group	II
Labels	8

Reason for revision: 2.2, 4.1

Publication date: 2001-12-29

Date of revision: 2020-03-26

Revision number: 0103

Product number: 51613

9 / 12

sulfuric acid, conc=93-99.5%

14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

14.6. Special precautions for user

Special provisions	
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Rail (RID)

14.1. UN number

UN number	1830
-----------	------

14.2. UN proper shipping name

Proper shipping name	Sulphuric acid
----------------------	----------------

14.3. Transport hazard class(es)

Hazard identification number	80
Class	8
Classification code	C1

14.4. Packing group

Packing group	II
Labels	8

14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

14.6. Special precautions for user

Special provisions	
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Inland waterways (ADN)

14.1. UN number

UN number	1830
-----------	------

14.2. UN proper shipping name

Proper shipping name	Sulphuric acid
----------------------	----------------

14.3. Transport hazard class(es)

Class	8
Classification code	C1

14.4. Packing group

Packing group	II
Labels	8

14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

14.6. Special precautions for user

Special provisions	
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Sea (IMDG/IMSBC)

14.1. UN number

UN number	1830
-----------	------

14.2. UN proper shipping name

Proper shipping name	sulphuric acid
----------------------	----------------

14.3. Transport hazard class(es)

Class	8
-------	---

14.4. Packing group

Packing group	II
Labels	8

14.5. Environmental hazards

Marine pollutant	-
Environmentally hazardous substance mark	no

14.6. Special precautions for user

Special provisions	
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Annex II of MARPOL 73/78	Not applicable, based on available data
--------------------------	---

Air (ICAO-TI/IATA-DGR)

14.1. UN number

UN number	1830
-----------	------

14.2. UN proper shipping name

Proper shipping name	Sulphuric acid
----------------------	----------------

14.3. Transport hazard class(es)

Class	8
-------	---

14.4. Packing group

sulfuric acid, conc=93-99.5%

Packing group	II
Labels	8
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	
Passenger and cargo transport	
Limited quantities: maximum net quantity per packaging	0.5 L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
	Not applicable (inorganic)

European drinking water standards (Directive 98/83/EC)

sulfuric acid, conc=93-99.5%

Parameter	Parametric value	Note	Reference
Sulphate	250 mg/l		Listed in Annex I, Part C, of Directive 98/83/EC on the quality of water intended for human consumption.

REACH Annex XVII - Restriction

Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
· sulfuric acid, conc=93-99.5%	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage"; b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010. 6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the present Regulation with a view to ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled H304, intended for supply to the general public. 7. Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled H304 to the competent authority in the Member State concerned. Member States shall make those data available to the Commission.'

National legislation Belgium

Additional classification	Acide sulfurique (brume); C; La mention "C" signifie que l'agent en question relève du champ d'application de l'arrêté royal du 2 décembre 1993 concernant la protection des travailleurs contre les risques liés à l'exposition à des agents cancérigènes et mutagènes et reprotoxiques au travail.
---------------------------	--

National legislation The Netherlands

Waterbezwaarlijkheid	B (3); Algemene Beoordelingsmethodiek (ABM)
SZW - Lijst van kankerverwekkende stoffen	zwavelzuurnevels; Listed in SZW-list of carcinogenic substances

National legislation France

No data available

National legislation Germany

Reason for revision: 2.2, 4.1

Publication date: 2001-12-29

Date of revision: 2020-03-26

Revision number: 0103

Product number: S1613

11 / 12

sulfuric acid, conc=93-99.5%

WGK	1; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017
TRGS900 - Risiko der Fruchtschädigung	Schwefeldioxid; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden Schwefelsäure; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

National legislation United Kingdom

No data available

Other relevant data

TLV - Carcinogen	Sulfur dioxide; A4 Sulfuric acid; A2
IARC - classification	3; Sulfur dioxide and some sulfites, bisulfites and metabisulfites 1; Strong-inorganic-acid mists containing sulfuric acid

15.2. Chemical safety assessment

A chemical safety assessment has been performed.

SECTION 16: Other information

Full text of any H-statements referred to under heading 3:

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

(*)	INTERNAL CLASSIFICATION BY BIG
ADI	Acceptable daily intake
AOEL	Acceptable operator exposure level
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC50	Effect Concentration 50 %
ErC50	EC50 in terms of reduction of growth rate
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

Specific concentration limits CLP

sulfuric acid, conc=93-99.5%	C ≥ 15 %	Skin Corr. 1A; H314	CLP Annex VI (ATP 0)
	5 % ≤ C < 15 %	Skin Irrit. 2; H315	CLP Annex VI (ATP 0)
	5 % ≤ C < 15 %	Eye Irrit. 2; H319	CLP Annex VI (ATP 0)

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 2.2, 4.1

Publication date: 2001-12-29

Date of revision: 2020-03-26

Revision number: 0103

Product number: S1613

12 / 12

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Downstream user exposure scenario for sulphuric acid.

1	Exposure Scenario 1: Production of Sulphuric acid
	<p>Production of sulphuric acid</p> <p>Processes Covered:</p> <p>Environmental Releases</p> <p>ERC01: Manufacture of Substances</p> <p>Worker Processes</p> <p>PROC01: Use in closed process, no likelihood of exposure PROC02: Use in closed process, with some potential for exposure PROC03: Use in closed batch process (synthesis or formulation) PROC04: Use in batch and other process (synthesis) where opportunity for exposure exists. PROC08a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities. PROC08b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities. PROC 9: Transfer of formulations or preparations to small containers.</p> <p>Process Category:</p> <p>PC 19: Intermediate</p> <p>Sulphuric acid is most commonly manufactured from sulphur (obtained from refining of crude oil) or from sulphur-containing gas released from high temperature processes such as metal smelting or burning fossil fuels. Sulphuric acid may also be manufactured as a result of sulphur-capture pollution control systems. Several processes may be used to produce sulphuric acid however, the most typical industrial process is the contact process. Sulphur dioxide (SO₂) is produced by combustion of liquid sulphur (S₂ at 140°C). The produced sulphuric acid may then be diluted with water or steam condensate to give a variety of commercial concentrations</p> <p>Due to the hazardous and corrosive nature of sulphuric acid the production systems are highly controlled and employ closed systems during the production processes.</p>
	<p>Contributing Environmental Scenario (CES 1): Environmental exposure arising due to production of sulphuric acid (ERC 1).</p>
	<p>Contributing Worker Scenarios: CES 2: Worker exposure arising due to use in closed processes with no likelihood of exposure (PROC 1), CES 3: worker exposure arising due to use in closed processes with some potential for exposure (PROC 2), CES 4: worker exposure arising due to day to day use in batch or other processes with some potential for exposure (such as sampling, cleaning, maintenance) (PROC 3</p>

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

and PROC 4), CES 5: transfer of substances to and from vessels and containers at non-dedicated facilities (PROC 8a), CES 6: transfer of substances to and from vessels and containers at dedicated facilities (PROC 8b) and CES 7: worker exposure arising due to transfer of formulation to small containers (PROC 9).

1.1 Controlling environmental exposure for ES 1

ES1: Contributing exposure scenario (CES) 1 Environmental exposure arising due to production of sulphuric acid

Section 2.1 describes the environmental releases that may occur during the production of sulphuric acid. These releases may potentially occur due to emission to wastewater or through emission to the atmosphere. Environmental emissions are limited by designated waste treatment process designed to limit environmental exposure to all relevant compartments. Waste gas emissions are scrubbed and may also then be diverted to the wastewater stream. This significantly lessens the possible emission by atmospheric deposition to soil or surface waters.

Liquid wastes are treated (neutralization to neutral pH) prior to emission to remove any sulphuric acid in the waste water and sludge from the waste water treatment plant is sent for incineration or landfill and is not used for agricultural spreading. This precludes any contamination of soil by sludge spreading. Waste water treatment is usually carried out by neutralisation followed by flocculation or decantation.

Production of sulphuric acid is generally continuous with constant production and use. Facilities may generally produce between 100 and 1,500 tonnes per day with up to 1.2million tonnes produced per year at the largest European manufacturing plant. This value has been considered as a worst case assumption for this environmental exposure scenario.

Product characteristics

The produced substance is a liquid with purity greater than 90%. The substance is colourless, odourless inorganic liquid which is miscible with water. Sulphuric acid is not flammable and is non-explosive.

Amounts used

Facilities may generally produce between 100 and 1,500 tonnes per day in a large facility with a working year of 360 days. Up to 1.2million tonnes may be produced per year at the largest European manufacturing plant which is considered to be a worst case assumption.

Frequency and duration of use

Continuous production and release.

Environmental factors influenced by risk management

On site WWTP with the capacity for complete neutralization. Emissions to air may be as much as 33.3 kg/d but are generally much less.

Other operational conditions affecting environmental exposure

Production takes place in a highly specialized indoor facility with emissions to water being fully neutralized before release. Reactors and transfer pipelines are closed systems. Waste gas emissions are scrubbed and may also be diverted to the wastewater stream.

Technical conditions and measures at process level (source) to prevent release

As mentioned above reactors and pipelines are fully sealed. Both production and sampling are carried out in dedicated facilities. Transfer operations are carried out under controlled conditions in sealed systems to reduce potential losses.

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
<p>Sulphuric acid is produced on a large scale, generally on major chemical sites, which will have dedicated effluent treatment facilities, involving both chemical and biological treatment, coping with many chemical substances. As such any emission to wastewater will be almost instantly hydrolysed before even reaching the STP.</p> <p>Neutralisation procedures are in place to ensure that the pH of any downstream biological treatment or final receiving waters is not affected. All waste waters should be treated in this manner. Measured pH values can be used to confirm the efficacy of the neutralization procedure.</p>	
Organizational measures to prevent/limit releases from site	
Workers are fully trained in order to prevent accidental release.	
Conditions and measures related to municipal STP	
Emissions to the municipal STP should not be made. All waste water should be treated in the on-site waste water treatment plant. Precipitated sludge should be sent for specialized waste treatment and should not be spread to soil.	
Conditions and measures related to external treatment of waste for disposal	
Sludge from the on-site WWTP would normally be sent to specialized landfill or for incineration at a dedicated waste facility. Waste from any scrubbers should be directed to waste water. There is no further generation of solid waste.	
Conditions and measures related to external recovery of waste	
There is no envisaged external recovery of waste.	
1.2	Controlling worker exposure for ES 1
<p>ES1: CES 2: Worker exposure arising due to use in closed processes with no likelihood of exposure (PROC 1), CES 3: worker exposure arising due to use in closed processes with some potential for exposure (PROC 2), CES 4: worker exposure arising due to day to day use in batch or other processes with some potential for exposure (such as sampling, cleaning, maintenance) (PROC 3 and PROC 4), CES 5: transfer of substances to and from vessels and containers at non-dedicated facilities (PROC 8a), CES 6: transfer of substances to and from vessels and containers at dedicated facilities (PROC 8b) and CES 7: worker exposure arising due to transfer of formulation to small containers (PROC 9).</p> <p>During the production of sulphuric acid controlled systems are in place to reduce the potential for worker exposure in all cases.</p> <p>Road/rail tanker connecting and disconnecting (loading and unloading) generally takes place in the open air. Loading and unloading of tankers with sulphuric acid is performed in the open air. Workers wear protective clothing (face/eye protection, helmet, anti-acid gloves boots and protective overall). Respiratory equipment (P3 filters) should also be worn when required. A safety shower is required nearby in case of accidental spillage. Gas displacement lines are also used if filling of road tankers takes place under cover.</p>	
Product characteristics	
The produced substance is a liquid with purity greater than 90%. The substance is colourless, odourless inorganic liquid which is miscible with water. Sulphuric acid is not flammable and is non-explosive.	
Amounts used	

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Facilities may generally produce between 100 and 1,500 tonnes per day with up to 1.2million tonnes produced per year at the largest European manufacturing plant considered to be a worst case assumption.
Frequency and duration of use exposure
Workers perform standard shifts of 8 hours per day and have standard working years of 220 days per year. However, some tasks such as sampling and maintenance are expected to be short duration events.
Human factors not influenced by risk management
Respiration volume under conditions of use 10m ³ /d (default value for a worker breathing for an 8h work day in RIP 3.2).
Other given operational conditions affecting worker exposure
Both production and sampling are carried out at dedicated facilities with local exhaust ventilation and vapour recovery systems are in place where required. Transfer operations are carried out in controlled systems with dedicated machinery.
Technical conditions and measures at process level (source) to prevent release
Reactors and pipes are sealed systems. Loss from reactor and pipes is monitored.
Technical conditions to control dispersion from source towards worker
LEV is in place in the production area during transfer and drum filling. Systems are sealed to prevent losses occurring.
Organizational measures to prevent/limit release
Workers are fully trained in order to prevent accidental release and frequent competency assessments are carried out by supervisors.
Conditions and measures related to personal protection, hygiene and health.
Gloves, goggles, chemical resistant overalls and work boots are worn by all operators in the facility to prevent dermal exposure. Respiratory equipment (P3 filter standard) may also be used when required. Air quality is protected by LEV. No consumption of food or liquids is allowed in the production facility.

1.3

Exposure estimation and reference to its source

Environmental Exposure

For the tier 1 risk characterisation PECs derived using the ERC defaults are not assessed below as the PECs are considered unrealistically high and would lead to a failing risk assessment in any case. For the tier 2 risk characterisation the PECs calculated by the EUSES environmental model with refined inputs taking into account the emission RMMs as discussed in section 2.1 above are used to control environmental releases are used for the assessment.

Information for contributing exposure scenario 1:

List of exposure concentrations

Compartment	PEC	Justification
Freshwater (in mg/L)	7×10^{-7}	
Marine water (in mg/L)	1×10^{-7}	
Intermittent releases to water (in mg/L)	NA	Intermittent release not relevant
Freshwater sediment (in mg/kg)	6.7×10^{-7}	
Marine sediment (in mg/kg)	8.2×10^{-8}	

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Agricultural soil (averaged over 30 days (in mg/kg))	4.7×10^{-5}	
Groundwater (in mg/L)	3.5×10^{-4}	
Annual average PEC in air, total (mg/m ³)	0.0091	

The following RCRs were derived taking into account derived PNEC values

Compartments	PEC mg/L	PNEC mg/L	PEC/PNEC	Comments
Tier 2 Freshwater	7×10^{-7}	0.0025	2.8×10^{-4}	Safe use demonstrated
Tier 2 Sediment	6.7×10^{-7}	0.002 (EPM)	3.3×10^{-4}	Safe use demonstrated
Tier 2 Intermittent releases		NA		
Tier 2 Marine	1×10^{-7}	0.002 (EPM)	4×10^{-4}	Safe use demonstrated
Tier 2 Marine sediment	8.2×10^{-8}	0.00025	4.1×10^{-5}	Safe use demonstrated

* EPM = equilibrium partitioning method

Worker exposure

The Advanced REACH tool (ART) was used to estimate worker exposure as it was considered that the ECETOC model cannot estimate in a satisfactory manner the effects of the stringent containment and segregation practices which are in place to deal with sulphuric acid production and to limit exposure.

In the characterisation of the human health risks posed by acute/short term and long-term inhalation exposures to sulphuric acid associated with ES 1, the 90th percentile (e.g. worst case) inhalation exposure concentrations derived using the ART model for relevant PROC codes were compared with the DNEL value for acute local respiratory effects and the DNEL value for long-term local respiratory effects respectively. The results of the risk characterisation are shown in the table below.

The predicted acute/short-term and long-term inhalation exposure concentrations derived using the ART model were not found to exceed the DNEL value for acute local respiratory effects or the DNEL value for long-term local respiratory effects respectively for any of the processes associated with ES 1. On the basis of the assumptions made in the exposure assessment and this risk characterisation, it can be concluded that inhalation exposures to sulphuric acid that may potentially arise during processes associated with ES 1 do not pose an unacceptable health risk to workers.

Information for worker contributing scenarios 2, 3, 4, 5, 6 and 7:

List of inputs used in the ART assessment

	PROC	Parameters/ assumptions
Exposure duration	All	480 min
Product type	All	Liquid (medium viscosity – like oil)
Process temperature	PROC 1,2,3,4	Hot processes (50-150°C)
	PROC 8a,8b, 9	Room temperature (15-25°C)
Vapour pressure	All	6 Pa – Substance is considered to be low volatile,

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

		exposure to mists is estimated
Liquid weight fraction	All	0.98
Primary emission source proximity	PROC 1, 2	Primary emission source is not located in the breathing zone of the worker - the assessment for this activity involves a primary far-field emission source only (workers are in a control room)
	PROC 3,4,8a,8b,9	Primary emission source located in the breathing zone of the workers (i.e. Within 1 metre)
Activity class	All	Transfer of liquid products
Containment	PROC 1,2,3,9	Handling reduces contact between product and adjacent air
	PROC 4	Open process, submerged loading
	PROC 8a,8b	n/a
Localised controls	PROC 1,3,8b	Vapour recovery systems; LEV
	PROC 2,4,9	Vapour recovery
	PROC 8a	None
Segregation	PROC 1,2	Complete segregation of workers in separate control room
Fugative emission source	PROC 1,3,8b,9	Process fully enclosed – not breached for sampling
	PROC 2,4,8a	Not fully enclosed – effective housekeeping practices in place.
Dispersion	PROC 1,2,8a,8b	Outdoors not close to buildings
	PROC 3,4	Outdoors close to buildings
	PROC 9	Indoors, any sized room, only good natural ventilation

List of derived exposure concentrations

Description of activity	PROC	Physical state of material	Short-term Concentrations		Long-term Concentration	
			Estimated Exposure (mg/m ³) 50 th percentile value	Estimated Exposure (mg/m ³) 90 th percentile value	Estimated Exposure (mg/m ³) 50 th percentile value	Estimated Exposure (mg/m ³) 90 th percentile value
Production (High integrity closed system, sampling via closed loop)	1	Liquid	8.2×10^{-10}	9.3×10^{-9}	3.6×10^{-9}	9.4×10^{-9}
Production and sampling (Occasional exposure system)	2	Liquid	8.2×10^{-9}	9.2×10^{-8}	3.6×10^{-8}	9.2×10^{-8}
Production, transfer and sampling	3	Liquid	3.7×10^{-5}	4.2×10^{-4}	1.6×10^{-4}	4.2×10^{-4}
Production, transfer and sampling (Exposure likely)	4	Liquid	1.2×10^{-3}	1.4×10^{-2}	5.4×10^{-3}	1.4×10^{-2}
Loading/transfer	8a	Liquid	2.0×10^{-3}	2.3×10^{-2}	8.8×10^{-2}	2.3×10^{-2}
Loading/transfer	8b	Liquid	1.1×10^{-5}	1.2×10^{-4}	4.8×10^{-5}	4.8×10^{-6}
Loading/transfer (Small containers)	9	Liquid	8.1×10^{-4}	3.2×10^{-3}	3.2×10^{-3}	2.8×10^{-3}

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

List of derived RCRs

Exposure details	CES	PROC Code	ES 1- 90 th exposure concentrations (mg/m3)	Leading toxic end point / Critical effect	DNEL (mg/m3)	Risk characterisation ratio
Acute-local effects	CES 2	PROC 1	9.3×10^{-9}	Respiratory irritation and corrositivity	0.1	9.2×10^{-7}
	CES 3	PROC 2	9.2×10^{-8}	Respiratory irritation and corrositivity	0.1	4.2×10^{-3}
	CES 4	PROC 3	4.2×10^{-4}	Respiratory irritation and corrositivity	0.1	1.4×10^{-1}
		PROC 4	1.4×10^{-2}	Respiratory irritation and corrositivity	0.1	2.3×10^{-1}
	CES 5	PROC 8a	2.3×10^{-2}	Respiratory irritation and corrositivity	0.1	1.2×10^{-3}
	CES 6	PROC 8b	1.2×10^{-4}	Respiratory irritation and corrositivity	0.1	3.2×10^{-2}
	CES 7	PROC 9	3.2×10^{-3}	Respiratory irritation and corrositivity	0.1	9.2×10^{-7}
Long-term – local effects	CES 2	PROC 1	9.4×10^{-9}	Respiratory irritation and corrositivity	0.05	1.8×10^{-6}
	CES 3	PROC 2	9.2×10^{-8}	Respiratory irritation and corrositivity	0.05	8.4×10^{-3}
	CES 4	PROC 3	4.2×10^{-4}	Respiratory irritation and corrositivity	0.05	2.8×10^{-1}
		PROC 4	1.4×10^{-2}	Respiratory irritation and corrositivity	0.05	4.6×10^{-1}
	CES 5	PROC 8a	2.3×10^{-2}	Respiratory irritation and corrositivity	0.05	9.6×10^{-5}
	CES 6	PROC 8b	4.8×10^{-6}	Respiratory irritation and corrositivity	0.05	5.6×10^{-2}
	CES 7	PROC 9	2.8×10^{-3}	Respiratory irritation and corrositivity	0.05	1.8×10^{-6}

Assessment of dermal risk

During the processes that will be carried out for all the exposure scenarios associated with production and use of sulphuric acid a risk may arise if sulphuric acid comes into contact with human skin. This is due to the nature of sulphuric acid and its ability to cause chemical burns. As this effect is considered to be related to the corrosivity of sulphuric acid a threshold DNEL cannot be established for this risk and

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

so measures to control this risk should be assessed in a qualitative manner. Though this risk is most pertinent when workers may come into contact with concentrated sulphuric acid in an industrial setting the operational conditions (OCs) and risk management measures (RMMs) used to control and manage the risk of dermal contact events may be equally applicable across all the exposure scenarios.

In the industrial setting an acute risk of dermal burns from exposure to sulphuric acid in its concentrated form (or its dilute form) exists due to possible splashing of the liquid acid. This risk would be highest at times of transfer to tankers, filling of barrels and filling of small vessels etc. Though these events are considered unlikely due to the high degree of system closure and control the risk is still protected against in order to eliminate any possible routes of exposure.

The first aspect of the OCs that reduces the risk of dermal contact is the specialised nature of the systems involved and the degree of closure associated with them. All pipes and transfers lines are closed and sealed in order to reduce any possible exposure to leaks or splashes. The reactors themselves are similarly closed and sealed in order to reduce any possible emissions. During times of transfer to/from road tankers gas displacement lines and special connecting systems are utilised in order to reduce the levels of gaseous emissions that could deposit to surfaces including human skin. Specialised tanker coupling/uncoupling systems and targeted purging systems may be employed in certain circumstances where large volumes and high concentrations are required. Training and certification plays an important part in ensuring the workers understand the correct procedures for use of these specialized systems so that the measures in place to reduce emission are not circumvented and so proper function can be maintained.

In addition to the measures in place to reduce system emission worker segregation also plays an important part in the reduction of risk in the industrial setting. Workers are generally housed in areas segregated from the main emission sources and time spent on tasks which require close proximity to the emission sources can be minimised effectively. Separate control rooms, screens and outdoor reactor units help to keep workers away from any potential sources of exposure. Emergency measures (and training on procedures and safe work practice) are in place in the industrial setting to ensure that any unforeseen events are safely dealt with in the case that they do arise. These measures would range from procedural policies which are in place to guide workers with respect to proper response in the case of splashes or spills to dedicated equipment (such as emergency showers or spill clean-up kits) which can be used to minimise any effects should unforeseen exposure arise.

In order to further protect the worker personal protective equipment (PPE) should be supplied to any personnel who may be working in areas where potential emission sources (such as transfer pipes) are located. Suitable PPE that should be used to prevent dermal contact for workers would be acid resistant clothing, helmets, gloves, goggles and boots. The PPE should be properly maintained and certified and should be replaced when required. These measures combined will effectively function to ensure three aspects of safe use. These are, firstly, reduction of potential emissions with specialised systems. Secondly reduction of the potential for exposure of workers by means such as segregation and training and thirdly physical protection of the worker with the use of correct PPE. With the combination of these measures it is considered that the risk of chemical burns to workers in large scale industrial production and use plants is adequately managed.

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

As mentioned above when the concentration of the acid decreases so does the potential for chemical burns to human skin. However the same measures are still in place to ensure that professionals and workers are protected from risk.

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environmental releases:

In order to work within the boundaries of the ES the following conditions should be met:

- Emission to air after scrubbing less than 33.3 kg per day
- No emission to the municipal STP
- The industrial WWTP sludge should not be spread to soil
- Wastewater should be fully neutralized
- Measured emissions should be confirmed to be less than the relevant PNECs in section 3

Worker exposure:

In order to work within the boundaries of the ES the following conditions should be met:

- Reactors and pipelines should be sealed systems
- LEV should be in place in the production facility and in transfer areas
- Workers should wear RPE, protective gloves, goggles, overalls and boots at all times in the production and transfer area
- Any measured exposure should be confirmed to be less than the relevant DNELs in section 3 above

1.5 Additional good practice advice beyond the REACH CSA.

- Do not eat, drink or smoke when working with sulphuric acid.
- Always wash hands and exposed skin thoroughly after using sulphuric acid or any surfaces/machinery that may have come into contact with sulphuric acid.
- Workers should be suitably trained in all safety procedures
- Procedural and safety compliance should be routinely assessed by management
- Machinery should be regularly maintained and checked for proper function
- Efficacy of all emission RMMs and waste treatment procedures should be routinely assessed and confirmed to be functioning correctly

2 Exposure Scenario 2: Use of Sulphuric Acid as an Intermediate in manufacture of inorganic and organic chemicals, including fertilizers.

Use of Sulphuric Acid as an Intermediate in manufacture of inorganic and organic chemicals, including fertilizers.

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Processes Covered:

Environmental Releases

ERC6A: Industrial use resulting in manufacture of another substance (use of intermediates)

Worker Processes

PROC01: Use in closed process, no likelihood of exposure

PROC02: Use in closed process, with some potential for exposure

PROC03: Use in closed batch process (synthesis or formulation)

PROC04: Use in batch and other process (synthesis) where opportunity for exposure arises.

PROC08a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC08b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC09: Transfer of formulations or preparations to small containers

Produce Category

PC19: Intermediate

The use of sulphuric acid as an intermediate in the production of inorganic and organic chemicals including but not limited to the production of fertilizers includes the production of oils used for lipolysis, sulphates, nitrogen fertilizers, granulation of complex fertilizers, phosphoric acid (wet process), titanium dioxide (sulphate route), hydrofluoric acid, fine chemicals and speciality chemicals. Sulphuric acid is also used as an intermediate for reactive use in water treatment, use as a granulating agent and use as a tanning agent whereas sulphuric acid is consumed in a chemical synthesis to form sulphate.

Due to the hazardous and corrosive nature of sulphuric acid when used as an intermediate, the process is conducted under highly controlled conditions.

Contributing Environmental Scenario: CES1 Environmental exposure arising due to the use of Sulphuric Acid as an Intermediate in manufacture of inorganic and organic chemicals, including fertilizers (ERC 6A).

Contributing Worker Scenarios: CES 2: Worker exposure arising due to use in closed processes with no likelihood of exposure (PROC 1), CES 3: worker exposure arising due to use in closed processes with some potential for exposure (PROC 2), CES 4: worker exposure arising due to day to day use in batch or other processes with some potential for exposure (PROC 3 and PROC 4), CES 5: worker exposure arising due transfer of substances to large vessels at non-dedicated and dedicated facilities (PROC 8a and PROC 8b) and CES 6: worker exposure arising due to transfer of formulation to small containers (PROC 9).

2.1 Controlling environmental exposure for ES 2

ES1: Contributing exposure scenario (CES) 1 Environmental exposure arising due to use of Sulphuric Acid as an Intermediate in manufacture of inorganic and organic chemicals, including fertilizers.

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Section 2.1 describes the environmental releases that may occur during the use of sulphuric acid as an intermediate. These releases may potentially occur due to emission to wastewater or through emission to the atmosphere. Environmental emissions are limited by designated waste treatment process designed to limit environmental exposure to all relevant compartments. Waste gas emissions are scrubbed and may also then be diverted to the wastewater stream. This significantly lessens the possible emission by atmospheric deposition to soil or surface waters.

Liquid wastes are treated (neutralization to neutral pH) prior to emission to remove any sulphuric acid in the waste water. Sludge from the waste water treatment plant is sent for incineration or landfill and is not used for agricultural spreading. This precludes any contamination of soil by sludge spreading. Waste water treatment is usually carried out by neutralisation followed by flocculation or decantation.

Use of sulphuric acid as an intermediate is generally continuous with constant production and use. Facilities generally use between 100 and 500 tonnes per day in a large facility, with 300,000 tonnes per year used as a worst case assumption.

Product characteristics

The produced substance is a liquid with purity greater than 90%. The substance is colourless, odourless inorganic liquid which is miscible with water. Sulphuric acid is not flammable and is non-explosive.

Amounts used

Facilities generally use between 100 and 500 tonnes per day in a large facility with a working year of 360 days. Up to 1.2million tonnes may be produced per year at the largest European manufacturing plant which is considered to be a worst case assumption.

Frequency and duration of use

Continuous production and release.

Environmental factors influenced by risk management

On site WWTP with the capacity for complete neutralization. Emissions to air may be as much as 94.9 kg/d but are generally much less. Exhaust gases may be treated by scrubbers.

Other operational conditions affecting environmental exposure

Intermediate use of sulphuric acid takes place in a highly specialized indoor facility with emissions to water being fully neutralized before release. Reactors and transfer pipelines are closed systems.

Technical conditions and measures at process level (source) to prevent release

As mentioned above reactors and pipelines are fully sealed. Both production and sampling are carried out in dedicated facilities. Transfer operations are carried out under controlled conditions in sealed systems to reduce potential losses.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Sulphuric acid used as an intermediate on a large scale generally occurs on major chemical sites which will have dedicated effluent treatment facilities, involving both chemical and biological treatment, coping with many chemical substances. As such any emission to wastewater will be almost instantly hydrolysed before even reaching the STP.

Neutralisation procedures are in place to ensure that the pH of any downstream biological treatment or final receiving waters is not affected. All waste waters should be treated in this manner. Measured pH values can be used to confirm the efficacy of the neutralization procedure.

Organizational measures to prevent/limit releases from site

Workers are fully trained in order to prevent accidental release. pH alarms are in place to monitor the

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

pH and ensure successful neutralization has taken place.	
Conditions and measures related to municipal STP	
Emissions to the municipal STP should not be made. All waste water should be treated in the on-site waste water treatment plant. Precipitated sludge should be sent for specialized waste treatment and should not be spread to soil.	
Conditions and measures related to external treatment of waste for disposal	
Sludge from the on-site WWTP would normally be sent to specialized landfill or for incineration at a dedicated waste facility. Waste from any scrubbers should be directed to waste water. There is no further generation of solid waste.	
Conditions and measures related to external recovery of waste	
There is no envisaged external recovery of waste.	
2.2	Controlling worker exposure for ES 2
<p>ES2: CES 2: Worker exposure arising due to use in closed processes with no likelihood of exposure (PROC 1), CES 3: worker exposure arising due to use in closed processes with some potential for exposure (PROC 2), CES 4: worker exposure arising due to day to day use in batch or other processes with some potential for exposure (PROC 3 and PROC 4), CES 5: worker exposure arising due transfer of substances to large vessels at non-dedicated and dedicated facilities (PROC 8a and PROC 8b) and CES 6: worker exposure arising due to transfer of formulation to small containers (PROC 9).</p>	
<p>During the use of sulphuric acid as an intermediate, controlled systems are in place to reduce the potential for worker exposure in all cases.</p> <p>Road/rail tanker connecting and disconnecting (loading and unloading) generally takes place in the open air. Loading and unloading of tankers with sulphuric acid is performed in the open air. Workers wear protective clothing (face/eye protection, helmet, anti-acid gloves boots and protective overall). Respiratory protection is used when required. A safety shower is required nearby in case of accidental spillage. Gas displacement lines are also used if filling of road tankers takes place under cover.</p>	
Product characteristics	
The produced substance is a liquid with purity greater than 90%. The substance is colourless, odourless inorganic liquid which is miscible with water. Sulphuric acid is not flammable and is non-explosive.	
Amounts used	
Facilities generally use between 100 and 500 tonnes per day in a large facility with a working year of 360 days. Up to 1.2million tonnes may be produced per year at the largest European manufacturing plant which is considered to be a worst case assumption.	
Frequency and duration of use exposure	
Workers perform standard shifts of 8 hours per day and have standard working years of 220 days per year. However, some tasks, such as sampling and maintenance will only be of a short duration.	
Human factors not influenced by risk management	
Respiration volumes under conditions of use 10m ³ /d (default value for a worker breathing for a 8h work day in RIP 3.2).	
Other given operational conditions affecting worker exposure	
Both production and sampling are carried out at dedicated facilities with local exhaust ventilation and vapour recovery systems in place where required. Transfer operations are carried out in controlled systems with dedicated machinery. The handling of sulphuric acid involves special equipment and	

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

controlled systems with little or no potential for exposure.
Technical conditions and measures at process level (source) to prevent release
Reactors and pipes are sealed systems. Loss from reactor and pipes is monitored.
Technical conditions to control dispersion from source towards worker
Any gas displaced from containers is conducted via pipeline to be processed (removed and scrubbed and /or filtered) in the areas where sulphuric acid is used as an intermediate. During handling when transferring drum filling, special equipment and controlled systems with little or no potential for exposure are used to prevent losses occurring.
Organizational measures to prevent/limit release
Workers involved in the sampling and transfer of materials to road tankers are fully trained in order to prevent accidental release and frequent competency assessments are carried out by supervisors.
Conditions and measures related to personal protection, hygiene and health.
Gloves, goggles, chemical resistant overalls and work boots are worn by all operators in the facility to prevent dermal exposure. Appropriate respiratory equipment is also worn when required.

2.3 Exposure estimation and reference to its source

Environmental Exposure

For the tier 1 risk characterisation PECs derived using the ERC defaults are not assessed below as the PECs are considered unrealistically high and would lead to a failing risk assessment in any case. For the tier 2 risk characterisation the PECs calculated by the EUSES environmental model with refined inputs taking into account the emission RMMs as discussed in section 2.1 above are used to control environmental releases are used for the assessment.

Information for contributing exposure scenario 1:

List of exposure concentrations

Compartment	PEC	Justification
Freshwater (in mg/L)	8.8×10^{-4}	
Marine water (in mg/L)	1.2×10^{-4}	
Intermittent releases to water (in mg/L)	NA	Intermittent release not relevant
Freshwater sediment (in mg/kg)	7.13×10^{-4}	
Marine sediment (in mg/kg)	1.03×10^{-4}	
Agricultural soil (averaged over 30 days (in mg/kg)	0.0149	
Groundwater (in mg/L)	0.11	
Annual average PEC in air, total (mg/m ³)	0.0261	

The following RCRs were derived taking into account derived PNEC values

Compartments	PEC mg/L	PNEC mg/L	PEC/PNEC	Comments
Tier 2 Freshwater	8.8×10^{-4}	0.0025	0.352	Safe use demonstrated
Tier 2 Sediment	7.3×10^{-4}	0.002 (EPM)	0.365	Safe use

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

				demonstrated
Tier 2 Intermittent releases		NA		
Tier 2 Marine	1.2×10^{-4}	0.00025	0.48	Safe use demonstrated
Tier 2 Marine sediment	1.03×10^{-4}	0.002 (EPM)	0.051	Safe use demonstrated

* EPM = equilibrium partitioning method

Worker exposure

The Advanced REACH tool (ART) was used to estimate worker exposure as it was considered that the ECETOC model cannot estimate in a satisfactory manner the effects of the stringent containment and segregation practices which are in place to deal with sulphuric acid production and to limit exposure.

In the characterisation of the human health risks posed by acute/short term and long-term inhalation exposures to sulphuric acid (or formed sulphuric acid) associated with ES 2, the 90th percentile (e.g. worst case) inhalation exposure concentrations derived using the ART model for relevant PROC codes were compared with the DNEL value for acute local respiratory effects and the DNEL value for long-term local respiratory effects respectively. The results of the risk characterisation are shown in the table below.

The predicted acute/short-term and long-term inhalation exposure concentrations derived using the ART model were not found to exceed the DNEL value for acute local respiratory effects or the DNEL value for long-term local respiratory effects respectively for any of the processes associated with ES 2. On the basis of the assumptions made in the exposure assessment and this risk characterisation, it can be concluded that inhalation exposures to sulphuric acid that may potentially arise during processes associated with ES 2 do not pose an unacceptable health risk to workers.

Information for worker contributing scenarios 2, 3, 4, 5 and 6:

List of inputs used in the ART assessment

	PROC	Parameters/ assumptions
Exposure duration	All	480 min
Product type	All	Liquid (medium viscosity – like oil)
Process temperature	PROC 1,2,3,4	Hot processes (50-150°C)
	PROC 8a,8b, 9	Room temperature (15-25°C)
Vapour pressure	All	6 Pa – Substance is considered to be low volatile, exposure to mists is estimated
Liquid weight fraction	All	0.98
Primary emission source proximity	PROC 1,2	Primary emission source is not located in the breathing zone of the worker - the assessment for this activity involves a primary far-field emission source only (workers are in a control room)
	PROC 3,4,8a,8b,9	Primary emission source located in the breathing zone of the workers (i.e. Within 1 metre)
Activity class	All	Transfer of liquid products
Containment	PROC 1,2, 3,9	Handling reduces contact between product and adjacent air.
	PROC 4	Open process, submerged loading
	PROC 8a,8b	n/a

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Localised controls	PROC1,3,8b	Vapour recovery systems; LEV
	PROC 2,4,9	Vapour recovery
	PROC 8a	None
Segregation	PROC 1,2	Complete segregation of workers in separate control room
Fugative emission source	PROC 1,3,8b,9	Process fully enclosed – not breached for sampling
	PROC 2,4,8a	Not fully enclosed – effective housekeeping practices in place.
Dispersion	PROC 1,2,8a,8b	Outdoors not close to buildings
	PROC 3,4	Outdoors near to buildings
	PROC 9	Indoors, any sized room, only good natural ventilation

List of derived exposure concentrations

Description of activity	PROC	Physical state of material	Estimated Exposure (mg/m3)	Short-term Concentrations	Estimated Exposure (mg/m3)	Long-term Concentration
			50 th percentile value	90 th percentile value	50 th percentile value	90 th percentile value
Use in closed process, no likelihood of exposure	1	Liquid	8.2×10^{-10}	9.3×10^{-9}	3.6×10^{-9}	9.4×10^{-9}
Use in closed, continuous process with occasional controlled exposure (including sampling and maintenance)	2	Liquid	8.2×10^{-9}	9.2×10^{-8}	3.6×10^{-8}	9.2×10^{-8}
Use in closed batch process (synthesis or formulation)	3	Liquid	3.7×10^{-5}	4.2×10^{-4}	1.6×10^{-4}	4.2×10^{-4}
Use in batch and other process (synthesis) where opportunity for exposure arises	4	Liquid	1.2×10^{-3}	1.4×10^{-2}	5.4×10^{-3}	1.4×10^{-2}
Loading/transfer	8a	Liquid	2.0×10^{-3}	2.3×10^{-2}	8.8×10^{-2}	2.3×10^{-2}
Loading/transfer	8b	Liquid	1.1×10^{-5}	1.2×10^{-4}	4.8×10^{-5}	4.8×10^{-6}
Loading/transfer (Small containers)	9	Liquid	8.1×10^{-4}	3.2×10^{-3}	3.2×10^{-3}	2.8×10^{-3}

List of derived RCRs

Exposure details	CES	PROC Code	ES 2- 90 th exposure concentrations (mg/m3)	Leading toxic end point / Critical effect	DNEL (mg/m3)	Risk characterisation ratio
Acute-local effects	CES 2	PROC 1	9.3×10^{-9}	Respiratory irritation and corrositivity	0.1	9.2×10^{-7}
	CES 3	PROC 2	9.2×10^{-8}	Respiratory irritation and corrositivity	0.1	4.2×10^{-3}
	CES 4	PROC 3	4.2×10^{-4}	Respiratory irritation and corrositivity	0.1	1.4×10^{-1}
		PROC 4	1.4×10^{-2}	Respiratory irritation and corrositivity	0.1	2.3×10^{-1}

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

	CES 5	PROC 8a	2.3×10^{-2}	Respiratory irritation and corrositivity	0.1	1.2×10^{-3}
		PROC 8b	1.2×10^{-4}	Respiratory irritation and corrositivity	0.1	3.2×10^{-2}
	CES 6	PROC 9	3.2×10^{-3}	Respiratory irritation and corrositivity	0.1	9.2×10^{-7}
Long-term – local effects	CES 2	PROC 1	9.4×10^{-9}	Respiratory irritation and corrositivity	0.05	1.8×10^{-6}
	CES 3	PROC 2	9.2×10^{-8}	Respiratory irritation and corrositivity	0.05	8.4×10^{-3}
	CES 4	PROC 3	4.2×10^{-4}	Respiratory irritation and corrositivity	0.05	2.8×10^{-1}
		PROC 4	1.4×10^{-2}	Respiratory irritation and corrositivity	0.05	4.6×10^{-1}
	CES 5	PROC 8a	2.3×10^{-2}	Respiratory irritation and corrositivity	0.05	9.6×10^{-5}
		PROC 8b	4.8×10^{-6}	Respiratory irritation and corrositivity	0.05	5.6×10^{-2}
	CES6	PROC 9	2.8×10^{-3}	Respiratory irritation and corrositivity	0.05	1.8×10^{-6}

Assessment of dermal risk

During the processes that will be carried out for all the exposure scenarios associated with production and use of sulphuric acid a potential risk may arise if sulphuric acid comes into contact with human skin. This is due to the nature of sulphuric acid and its ability to cause chemical burns. As this effect is considered to be related to the corrosivity of sulphuric acid a threshold DNEL cannot be established for this risk and so measures to control this risk should be assessed in a qualitative manner. Though this risk is most pertinent when workers may come into contact with concentrated sulphuric acid in an industrial setting the operational conditions (OCs) and risk management measures (RMMs) used to control and manage the risk of dermal contact events may be equally applicable across all the exposure scenarios.

In the industrial setting an acute risk of dermal burns from exposure to sulphuric acid in its concentrated form (or its dilute form) exists due to possible splashing of the liquid acid. This risk would be highest at times of transfer to tankers, filling of barrels and filling of small vessels etc. Though these events are considered unlikely due to the high degree of system closure and control the risk is still protected against in order to eliminate any possible routes of exposure.

The risk of dermal contact is reduced due to the OC's in place. The specialised nature of the systems and the degree of closure associated with them ensure the potential for dermal contact is minimised. All pipes and transfers lines are closed and sealed in order to reduce possible exposure to leaks or splashes, as are the reactors to reduce possible emissions. During times of transfer to/from road tankers gas

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

displacement lines and special connecting systems are in place to reduce the levels of gaseous emissions that could deposit to surfaces including human skin. Specialised tanker coupling/uncoupling systems and targeted purging systems may be used in certain circumstances where large volumes and high concentrations are required. Training and certification ensures the workers understand the correct procedures for use of these specialized systems so that the measures in place to reduce emissions are conducted so proper function can be maintained.

In addition to the measures in place to reduce system emissions, workers are completely separated from the site of operation. Workers are generally housed in areas segregated from the main emission sources and time spent on tasks which require close proximity to the emission sources can be minimised effectively. Separate control rooms, screens and outdoor reactor units help to keep workers away from any potential sources of exposure. Emergency measures (and training on procedures and safe work practice) are in place in the industrial setting to ensure that any unforeseen events are safely dealt with in the case that they do arise. These measures range from procedural policies which are in place to guide workers in the proper response in the case of splashes or spills to dedicated equipment (such as emergency showers or spill clean-up kits) which can be used to minimise any effects should unforeseen exposure arise.

Personal protective equipment (PPE) should be supplied to any personnel who may be working in areas where potential emission sources (such as transfer pipes) are located. Suitable PPE that should be used to prevent dermal contact for workers would be acid resistant clothing, helmets, gloves, goggles and boots. The PPE should be properly maintained and certified and should be replaced when required. These measures combined will effectively function to ensure three aspects of safe use. These are, firstly, reduction of potential emissions with specialised systems. Secondly reduction of the potential for exposure of workers by means such as segregation and training and thirdly physical protection of the worker with the use of correct PPE. With the combination of these measures it is considered that the risk of chemical burns to workers is adequately managed.

As mentioned above when the concentration of the sulphuric acid decreases so does the potential for chemical burns to human skin. However the same measures are still in place to ensure that workers, professionals and consumers are protected from risk.

2.4

Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environmental releases:

In order to work within the boundaries of the ES the following conditions should be met:

- Emission to air after scrubbing less than 94.9 kg per day
- No emission to the municipal STP
- The industrial WWTP sludge should not be spread to soil
- Wastewater should be fully neutralized
- Exhaust gases from the intermediate use are treated with scrubbers.
- Measured emissions should be confirmed to be less than the relevant PNECs in section 3

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Worker exposure:

In order to work within the boundaries of the ES the following conditions should be met:

- Reactors and pipelines should be sealed systems
- LEV should be in place in the production facility and in transfer areas
- Workers should wear protective gloves, goggles, overalls and boots at all times in the production and transfer area
- Appropriate respiratory equipment should also be worn if required.
- Any measured exposure should be confirmed to be less than the relevant DNELs in section 3 above
- Submerged loading can be used to reduce the amount of aerosol formation.

2.5

Additional good practice advice beyond the REACH CSA.

- Do not eat, drink or smoke when working with sulphuric acid.
- Always wash hands and exposed skin thoroughly after using sulphuric acid or any surfaces/machinery that may have come into contact with sulphuric acid.
- Workers should be suitably trained in all safety procedures
- All PPE should be properly maintained and stored in an appropriate way so as not to damage its integrity. Workers should be correctly trained in its use.
- Procedural and safety compliance should be routinely assessed by management
- Machinery should be regularly maintained and checked for proper function
- Efficacy of all emission RMMs and waste treatment procedures should be routinely assessed and confirmed to be functioning correctly

3 Exposure Scenario 3: Use of Sulphuric Acid as a Processing aid, catalyst, dehydrating agent and pH regulator.

Use of Sulphuric Acid as a Processing aid, catalyst, dehydrating agent and pH regulator.

Processes Covered:

Environmental Releases

ERC6B: Industrial use of reactive processing aids.

Worker Processes

PROC01: Use in closed process, no likelihood of exposure

PROC02: Use in closed process, with some potential for exposure

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

PROC03: Use in closed batch process (synthesis or formulation)
 PROC04: Use in batch and other process (synthesis) where opportunity for exposure arises.
 PROC08a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities
 PROC08b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities
 PROC09: Transfer of formulations or preparations to small containers
 PROC13: Treatment of articles by dipping and pouring.

Produce Category

PC20: Products such as pH-regulators, flocculants, precipitants, neutralization agents.

Sulphuric acid is used in the industrial manufacture of organic chemicals and fine chemicals. These processes include using sulphuric acid in large volumes as a processing aid, catalyst or dehydration agent in the chemical process of manufacture of adhesives, explosives, acids, organic salts, dyes and pigments, biofuels, pharmaceuticals and the alkylation of aliphatics. Sulphuric acid may also be used to regulate pH in water streams and as a process aid in the leather and textiles industry.

Due to the hazardous and corrosive nature of sulphuric acid when used as a processing aid, the process is conducted under highly controlled conditions.

Contributing Environmental Scenario: CES1 Environmental exposure arising due to the use of Sulphuric Acid as a Processing aid, catalyst, dehydrating agent and pH regulator. (ERC 6B).

Contributing Worker Scenarios: CES 2: Worker exposure arising due to use in closed processes with no likelihood of exposure (PROC 1), CES 3: worker exposure arising due to use in closed processes with some potential for exposure (PROC 2), CES 4: worker exposure arising due to day to day use in batch or other processes with some potential for exposure (PROC 3 and PROC 4), CES 5: worker exposure arising due transfer of substances to large vessels at non-dedicated and dedicated facilities (PROC 8a and PROC 8b), CES 6: worker exposure arising due to transfer of formulation to small containers (PROC 9) and CES 7: worker exposure arising due to treatment of articles by dipping and pouring.

3.1 Controlling environmental exposure for ES 3

ES3: Contributing exposure scenario (CES) 1 Environmental exposure arising due to use of Sulphuric Acid as a processing aid, catalyst, dehydrating agent and pH regulator.

Section 2.1 describes the environmental releases that may occur during the use of sulphuric acid as a processing aid, catalyst, dehydrating agent or pH regulator. These releases may potentially occur due to emission to wastewater or through emission to the atmosphere. Environmental emissions are limited by designated waste treatment process designed to limit environmental exposure to all relevant compartments. Waste gas emissions are scrubbed and may also then be diverted to the wastewater stream. This significantly lessens the possible emission by atmospheric deposition to soil or surface waters.

Liquid wastes are treated (neutralization to neutral pH) prior to emission to remove any sulphuric acid in

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

the waste water. Sludge from the waste water treatment plant is sent for incineration or landfill and is not used for agricultural spreading. This precludes any contamination of soil by sludge spreading. Waste water treatment is usually carried out by neutralisation followed by flocculation or decantation.

Use of sulphuric acid as a processing aid, catalyst, dehydrating agent or pH regulator is generally continuous with constant production and use. Facilities generally use between 100 and 500 tonnes per day in a large facility, with 100,000 tonnes per year used as a worst case assumption.

Product characteristics

The produced substance is a liquid with purity greater than 90%. The substance is colourless, odourless inorganic liquid which is miscible with water. Sulphuric acid is not flammable and is non-explosive.

Amounts used

Facilities generally use between 100 and 500 tonnes per day in a large facility with a working year of 360 days. Up to 100,000 tonnes may be produced per year at the largest European manufacturing plant which is considered to be a worst case assumption.

Frequency and duration of use

Continuous production and release.

Environmental factors influenced by risk management

On site WWTP with the capacity for complete neutralization. Emissions to air may be as much as 333 kg/d but are generally much less. Exhaust gases may be treated by scrubbers.

Other operational conditions affecting environmental exposure

The use of sulphuric acid as a processing aid, catalyst, dehydrating agent or pH regulator takes place in a highly specialized, high integrity indoor facility with emissions to water being fully neutralized before release. Reactors and transfer pipelines are closed systems.

Technical conditions and measures at process level (source) to prevent release

As mentioned above reactors and pipelines are fully sealed. Both production and sampling are carried out in dedicated facilities. Transfer operations are carried out under controlled conditions in sealed systems to reduce potential losses.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Sulphuric acid used as a processing aid, catalyst, dehydrating agent or pH regulator on a large scale generally occurs on major chemical sites which will have dedicated effluent treatment facilities, involving both chemical and biological treatment, coping with many chemical substances. As such any emission to wastewater will be almost instantly hydrolysed before even reaching the STP.

Neutralisation procedures are in place to ensure that the pH of any downstream biological treatment or final receiving waters is not affected. All waste waters should be treated in this manner. Measured pH values can be used to confirm the efficacy of the neutralization procedure.

Organizational measures to prevent/limit releases from site

Workers are fully trained in order to prevent accidental release. pH alarms are in place to monitor the pH and ensure successful neutralization has taken place.

Conditions and measures related to municipal STP

Emissions to the municipal STP should not be made. All waste water should be treated in the on-site waste water treatment plant. Precipitated sludge should be sent for specialized waste treatment and should not be spread to soil.

Conditions and measures related to external treatment of waste for disposal

Sludge from the on-site WWTP would normally be sent to specialized landfill or for incineration at a dedicated waste facility. Waste from any scrubbers should be directed to waste water. There is no

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

further generation of solid waste.	
Conditions and measures related to external recovery of waste	
There is no envisaged external recovery of waste.	
3.2	Controlling worker exposure for ES 3
<p>ES3: CES 2: Worker exposure arising due to use in closed processes with no likelihood of exposure (PROC 1), CES 3: worker exposure arising due to use in closed processes with some potential for exposure (PROC 2), CES 4: worker exposure arising due to day to day use in batch or other processes with some potential for exposure (PROC 3 and PROC 4), CES 5: worker exposure arising due transfer of substances to large vessels at non-dedicated and dedicated facilities (PROC 8a and PROC 8b), CES 6: worker exposure arising due to transfer of formulation to small containers (PROC 9) and CES 7: worker exposure arising due to treatment of articles by dipping and pouring.</p>	
<p>During the use of sulphuric acid as a processing aid, catalyst, dehydrating agent or pH regulator, controlled systems are in place to reduce the potential for worker exposure in all cases.</p> <p>Road/rail tanker connecting and disconnecting (loading and unloading) generally takes place in the open air. Loading and unloading of tankers with sulphuric acid is performed in the open air. Workers wear protective clothing (face/eye protection, helmet, anti-acid gloves boots and protective overall). Respiratory protection is used when required. A safety shower is required nearby in case of accidental spillage. Gas displacement lines are also used if filling of road tankers takes place under cover.</p>	
Product characteristics	
The produced substance is a liquid with purity greater than 90%. The substance is colourless, odourless inorganic liquid which is miscible with water. Sulphuric acid is not flammable and is non-explosive.	
Amounts used	
Facilities generally use between 100 and 500 tonnes per day in a large facility with a working year of 360 days. Up to 100,000 tonnes may be produced per year at the largest European manufacturing plant which is considered to be a worst case assumption.	
Frequency and duration of use exposure	
Workers perform standard shifts of 8 hours per day and have standard working years of 220 days per year. However, some tasks, such as sampling and maintenance will only be of a short duration.	
Human factors not influenced by risk management	
Respiration volumes under conditions of use 10m ³ /d (default value for a worker breathing for a 8h work day in RIP 3.2).	
Other given operational conditions affecting worker exposure	
Both production and sampling are carried out at dedicated facilities with local exhaust ventilation and vapour recovery systems in place where required. Transfer operations are carried out in controlled systems with dedicated machinery. The handling of sulphuric acid involves special equipment and controlled systems with little or no potential for exposure.	
Technical conditions and measures at process level (source) to prevent release	
Reactors and pipes are sealed systems. Loss from reactor and pipes is monitored.	
Technical conditions to control dispersion from source towards worker	
Any gas displaced from containers is conducted via pipeline to be processed (removed and scrubbed and /or filtered) in the areas where sulphuric acid is used as a processing aid, catalyst, dehydrating agent or pH regulator. During handling when transferring drum filling, special equipment and controlled systems	

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

with little or no potential for exposure are used to prevent losses occurring.

Organizational measures to prevent/limit release

Workers involved in the sampling and transfer of materials to road tankers are fully trained in order to prevent accidental release and frequent competency assessments are carried out by supervisors.

Conditions and measures related to personal protection, hygiene and health.

Gloves, goggles, chemical resistant overalls and work boots are worn by all operators in the facility to prevent dermal exposure.

3.3

Exposure estimation and reference to its source

Environmental Exposure

For the tier 1 risk characterisation PECs derived using the ERC defaults are not assessed below as the PECs are considered unrealistically high and would lead to a failing risk assessment in any case. For the tier 2 risk characterisation the PECs calculated by the EUSES environmental model with refined inputs taking into account the emission RMMs as discussed in section 2.1 above are used to control environmental releases are used for the assessment.

Information for contributing exposure scenario 1:

List of exposure concentrations

Compartment	PEC	Justification
Freshwater (in mg/L)	5.91×10^{-6}	
Marine water (in mg/L)	8.56×10^{-7}	
Intermittent releases to water (in mg/L)	NA	Intermittent release not relevant
Freshwater sediment (in mg/kg)	4.8×10^{-6}	
Marine sediment (in mg/kg)	6.9×10^{-7}	
Agricultural soil (averaged over 30 days (in mg/kg)	3.9×10^{-4}	
Groundwater (in mg/L)	2.9×10^{-3}	
Annual average PEC in air, total (mg/m ³)	0.0091	

The following RCRs were derived taking into account derived PNEC values

Compartments	PEC mg/L	PNEC mg/L	PEC/PNEC	Comments
Tier 2 Freshwater	5.9×10^{-6}	0.0025	2.3×10^{-3}	Safe use demonstrated
Tier 2 Sediment	4.75×10^{-6}	0.002 (EPM)	2.35×10^{-3}	Safe use demonstrated
Tier 2 Intermittent releases		NA		
Tier 2 Marine	8.56×10^{-7}	0.00025	3.4×10^{-3}	Safe use demonstrated

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Tier 2 Marine sediment	6.9×10^{-7}	0.002 (EPM)	3.4×10^{-4}	Safe use demonstrated
------------------------	----------------------	-------------	----------------------	-----------------------

* EPM = equilibrium partitioning method

Worker exposure

The Advanced REACH tool (ART) was used to estimate worker exposure as it was considered that the ECETOC model cannot estimate in a satisfactory manner the effects of the stringent containment and segregation practices which are in place to deal with sulphuric acid production and to limit exposure.

In the characterisation of the human health risks posed by acute/short term and long-term inhalation exposures to sulphuric acid (or formed sulphuric acid) associated with ES 3, the 90th percentile (e.g. worst case) inhalation exposure concentrations derived using the ART model for relevant PROC codes were compared with the DNEL value for acute local respiratory effects and the DNEL value for long-term local respiratory effects respectively. The results of the risk characterisation are shown in the table below.

The predicted acute/short-term and long-term inhalation exposure concentrations derived using the ART model were not found to exceed the DNEL value for acute local respiratory effects or the DNEL value for long-term local respiratory effects respectively for any of the processes associated with ES 3. On the basis of the assumptions made in the exposure assessment and this risk characterisation, it can be concluded that inhalation exposures to sulphuric acid that may potentially arise during processes associated with ES 3 do not pose an unacceptable health risk to workers.

Information for worker contributing scenarios 2, 3, 4, 5, 6 and 7:

List of inputs used in the ART assessment

	PROC	Parameters/ assumptions
Exposure duration	All	480 min
Product type	All	Liquid (medium viscosity – like oil)
Process temperature	PROC 1,2,3,4	Hot processes (50-150°C)
	PROC 8a,8b, 9,13	Room temperature (15-25°C)
Vapour pressure	All	6 Pa – Substance is considered to be low volatile, exposure to mists is estimated
Liquid weight fraction	All	0.98
Primary emission source proximity	PROC 1,2	Primary emission source is not located in the breathing zone of the worker - the assessment for this activity involves a primary far-field emission source only (workers are in a control room)
	PROC 3,4,8a,8b,9,13	Primary emission source located in the breathing zone of the workers (i.e. Within 1 metre)
Activity class	PROC 1,2,3,4,8a,8b,9	Transfer of liquid products
	PROC 13	Activities with open liquid surface or reservoirs
Containment	PROC 1,2, 3,9	Handling reduces contact between product and adjacent air
	PROC 4	Open process, submerged loading
	PROC 8a,8b,13	n/a
Localised controls	PROC 1,2,3,8b	Vapour recovery systems; LEV
	PROC 2,4,9	Vapour recovery
	PROC 8a,13	None
Segregation	PROC 1,2	Complete segregation of workers in separate control room

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Fugative emission source	PROC 1,3,8b,9	Process fully enclosed – not breached for sampling
	PROC 2,4,8a,13	Not fully enclosed – effective housekeeping practices in place.
Dispersion	PROC 1,2,8a,8b	Outdoors not close to buildings
	PROC 3,4	Outdoors near to buildings
	PROC 9,13	Indoors, any sized room, only good natural ventilation

List of derived exposure concentrations

Description of activity	PROC	Physical state of material	Estimated Exposure Concentrations (mg/m3)		Estimated Exposure Concentration (mg/m3)	
			50 th percentile value	90 th percentile value	50 th percentile value	90 th percentile value
Use in closed process, no likelihood of exposure	1	Liquid	8.20×10^{-10}	9.30×10^{-09}	3.60×10^{-09}	9.40×10^{-09}
Use in closed, continuous process with occasional controlled exposure (including sampling and maintenance)	2	Liquid	8.20×10^{-09}	9.20×10^{-08}	3.60×10^{-08}	9.20×10^{-08}
Use in closed batch process (synthesis or formulation)	3	Liquid	3.70×10^{-05}	4.20×10^{-04}	1.60×10^{-04}	4.20×10^{-04}
Use in batch and other process (synthesis) where opportunity for exposure arises	4	Liquid	1.2×10^{-3}	0.014	0.0054	0.014
Loading/transfer: Loading and unloading a tanker (non-dedicated site)	8a	Liquid	2.0×10^{-3}	0.023	0.0088	0.023
Loading/transfer: Loading and unloading a tanker (dedicated site)	8b	Liquid	1.10×10^{-05}	1.20×10^{-04}	4.80×10^{-05}	4.80×10^{-06}
Loading/transfer (filling small containers with sulphuric acid)	9	Liquid	8.1×10^{-4}	0.0032	0.0011	0.0028
Treatment of articles by dipping and pouring (immersion operations)	13	Liquids	4.5×10^{-3}	0.018	0.0062	0.016

List of derived RCRs

Exposure details	CES	PROC Code	ES 3- 90 th exposure concentrations (mg/m3)	Leading toxic end point / Critical effect	DNEL (mg/m3)	Risk characterisation ratio
Acute-local effects	CES 2	PROC 1	9.3×10^{-9}	Respiratory irritation and corrositivity	0.1	9.3×10^{-8}
	CES 3	PROC 2	9.2×10^{-8}	Respiratory irritation and corrositivity	0.1	9.2×10^{-7}

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

	CES 4	PROC 3	4.2×10^{-4}	Respiratory irritation and corrositivity	0.1	4.2×10^{-3}
		PROC 4	1.4×10^{-2}	Respiratory irritation and corrositivity	0.1	1.4×10^{-1}
	CES 5	PROC 8a	2.3×10^{-2}	Respiratory irritation and corrositivity	0.1	2.3×10^{-1}
		PROC 8b	1.2×10^{-4}	Respiratory irritation and corrositivity	0.1	1.2×10^{-3}
	CES 6	PROC 9	3.2×10^{-3}	Respiratory irritation and corrositivity	0.1	3.2×10^{-2}
	CES 7	PROC 13	1.8×10^{-2}	Respiratory irritation and corrositivity	0.1	1.8×10^{-1}
Long-term – local effects	CES 2	PROC 1	3.6×10^{-9}	Respiratory irritation and corrositivity	0.05	1.9×10^{-7}
	CES 3	PROC 2	3.6×10^{-8}	Respiratory irritation and corrositivity	0.05	1.8×10^{-6}
	CES 4	PROC 3	1.6×10^{-4}	Respiratory irritation and corrositivity	0.05	8.4×10^{-3}
		PROC 4	5.4×10^{-3}	Respiratory irritation and corrositivity	0.05	2.8×10^{-1}
	CES 5	PROC 8a	8.8×10^{-3}	Respiratory irritation and corrositivity	0.05	4.6×10^{-1}
		PROC 8b	4.8×10^{-5}	Respiratory irritation and corrositivity	0.05	9.6×10^{-5}
	CES6	PROC 9	1.1×10^{-3}	Respiratory irritation and corrositivity	0.05	5.6×10^{-2}
	CES 7	PROC 13	6.2×10^{-3}	Respiratory irritation and corrositivity	0.05	3.2×10^{-1}

Assessment of dermal risk

During the processes that will be carried out for all the exposure scenarios associated with production and use of sulphuric acid a potential risk may arise if sulphuric acid comes into contact with human skin. This is due to the nature of sulphuric acid and its ability to cause chemical burns. As this effect is considered to be related to the corrosivity of sulphuric acid a threshold DNEL cannot be established for this risk and so measures to control this risk should be assessed in a qualitative manner. Though this risk is most pertinent when workers may come into contact with concentrated sulphuric acid in an industrial setting the operational conditions (OCs) and risk management measures (RMMs) used to control and manage the risk of dermal contact events may be equally applicable across all the exposure scenarios.

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

In the industrial setting an acute risk of dermal burns from exposure to sulphuric acid in its concentrated form (or its dilute form) exists due to possible splashing of the liquid acid. This risk would be highest at times of transfer to tankers, filling of barrels and filling of small vessels etc. Though these events are considered unlikely due to the high degree of system closure and control the risk is still protected against in order to eliminate any possible routes of exposure.

The risk of dermal contact is reduced due to the OC's in place. The specialised nature of the systems and the degree of closure associated with them ensure the potential for dermal contact is minimised. All pipes and transfers lines are closed and sealed in order to reduce possible exposure to leaks or splashes, as are the reactors to reduce possible emissions. During times of transfer to/from road tankers gas displacement lines and special connecting systems are in place to reduce the levels of gaseous emissions that could deposit to surfaces including human skin. Specialised tanker coupling/uncoupling systems and targeted purging systems may be used in certain circumstances where large volumes and high concentrations are required. Training and certification ensures the workers understand the correct procedures for use of these specialized systems so that the measures in place to reduce emissions are conducted so proper function can be maintained.

In addition to the measures in place to reduce system emissions, workers are completely separated from the site of operation. Workers are generally housed in areas segregated from the main emission sources and time spent on tasks which require close proximity to the emission sources can be minimised effectively. Separate control rooms, screens and outdoor reactor units help to keep workers away from any potential sources of exposure. Emergency measures (and training on procedures and safe work practice) are in place in the industrial setting to ensure that any unforeseen events are safely dealt with in the case that they do arise. These measures range from procedural policies which are in place to guide workers in the proper response in the case of splashes or spills to dedicated equipment (such as emergency showers or spill clean-up kits) which can be used to minimise any effects should unforeseen exposure arise.

Personal protective equipment (PPE) should be supplied to any personnel who may be working in areas where potential emission sources (such as transfer pipes) are located. Suitable PPE that should be used to prevent dermal contact for workers would be acid resistant clothing, helmets, gloves, goggles and boots. The PPE should be properly maintained and certified and should be replaced when required. These measures combined will effectively function to ensure three aspects of safe use. These are, firstly, reduction of potential emissions with specialised systems. Secondly reduction of the potential for exposure of workers by means such as segregation and training and thirdly physical protection of the worker with the use of correct PPE. With the combination of these measures it is considered that the risk of chemical burns to workers is adequately managed.

As mentioned above when the concentration of the sulphuric acid decreases so does the potential for chemical burns to human skin. However the same measures are still in place to ensure that workers, professionals and consumers are protected from risk.

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

3.4	Guidance to DU to evaluate whether he works inside the boundaries set by the ES
-----	--

Environmental releases:

In order to work within the boundaries of the ES the following conditions should be met:

- Emission to air after scrubbing less than 333 kg per day
- No emission to the municipal STP
- The industrial WWTP sludge should not be spread to soil
- Wastewater should be fully neutralized
- Exhaust gases from the intermediate use are treated with scrubbers.
- Measured emissions should be confirmed to be less than the relevant PNECs in section 3

Worker exposure:

In order to work within the boundaries of the ES the following conditions should be met:

- Reactors and pipelines should be sealed systems
- Workers should wear protective gloves, goggles, overalls and boots at all times in the production and transfer area
- Appropriate respiratory equipment should also be worn if required.
- Any measured exposure should be confirmed to be less than the relevant DNELs in section 3 above.

3.5	Additional good practice advice beyond the REACH CSA.
-----	--

- Do not eat, drink or smoke when working with sulphuric acid.
- Always wash hands and exposed skin thoroughly after using sulphuric acid or any surfaces/machinery that may have come into contact with sulphuric acid.
- Workers should be suitably trained in all safety procedures
- All PPE should be properly maintained and stored in an appropriate way so as not to damage its integrity. Workers should be correctly trained in its use.
- Procedural and safety compliance should be routinely assessed by management
- Machinery should be regularly maintained and checked for proper function
- Efficacy of all emission RMMs and waste treatment procedures should be routinely assessed and confirmed to be functioning correctly

4	Exposure Scenario 4: Use of Sulphuric Acid for extractions and processing of minerals and ores
---	---

Use of Sulphuric Acid for extractions and processing of minerals and ores.

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Processes Covered:

Environmental Releases

ERC04: Industrial use of processing aids in processes and products, not becoming part of articles
ERC06B: Industrial use of reactive processing aids.

Worker Processes

PROC02: Use in closed process, with some potential for exposure
PROC03: Use in closed batch process (synthesis or formulation)
PROC04: Use in batch and other process (synthesis) where opportunity for exposure arises.

Produce Category

PC20: Products such as pH-regulators, flocculants, precipitants, neutralization agents.
PC40: Extraction agents

Sulphuric acid is used in industrial extraction of and processing of minerals and ores. This use includes leaching, dissolution and enrichment of ores including zinc, copper, nickel and uranium. Metal removal from sand and clay and titanium limonite leaching are also encompassed under this use. Sulphuric acid is utilised in this exposure scenario as a method of mineral and ore leaching and extraction. Ores and minerals are usually leached with sulphuric acid using specialised leaching systems which employs sulphuric acid to dissolve the ores or minerals from their substrate. This process may be performed in ore/mineral piles in the open. The sulphuric acid can then be stripped of its ore or minerals and can then be re-circulated and re-used. Though the acid is intended to react with the substrates a portion of the acid involved may remain un-reacted.

Due to the hazardous and corrosive nature of sulphuric acid when used as a processing aid, the process is conducted under highly controlled conditions.

Contributing Environmental Scenario: CES1 Environmental exposure arising due to the use of Sulphuric Acid for extractions and in the processing of minerals and ores. (ERC 4 and ERC 6B).

Contributing Worker Scenarios: CES 2: worker exposure arising due to use in closed processes with some potential for exposure (PROC 2) and CES 3: worker exposure arising due to day to day use in batch or other processes with some potential for exposure (PROC 3 and PROC 4).

4.1 Controlling environmental exposure for ES 4

ES4: Contributing exposure scenario (CES) 1 Environmental exposure arising due to use of Sulphuric Acid for extractions and in the processing of minerals and ores.

Section 2.1 describes the environmental releases that may occur during the use of sulphuric acid for extractions and in the processing of minerals and ores. These releases may potentially occur due to emission to wastewater or through emission to the atmosphere. Environmental emissions are limited by

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

designated waste treatment process designed to limit environmental exposure to all relevant compartments. Waste gas emissions are scrubbed and may also then be diverted to the wastewater stream. This significantly lessens the possible emission by atmospheric deposition to soil or surface waters.

Liquid wastes are treated (neutralization to neutral pH) prior to emission to remove any sulphuric acid in the waste water. Sludge from the waste water treatment plant is sent for incineration or landfill and is not used for agricultural spreading. This precludes any contamination of soil by sludge spreading. Waste water treatment is usually carried out by neutralisation followed by flocculation or decantation.

Use of sulphuric acid in the processing of minerals and ores is generally continuous with constant production and use. Facilities may use up to 480 tonnes per year, considered to be a worst case assumption.

Product characteristics

The produced substance is a liquid with purity greater than 90%. The substance is colourless, odourless inorganic liquid which is miscible with water. Sulphuric acid is not flammable and is non-explosive.

Amounts used

Facilities may use up to 480 tonnes per year, considered to be a worst case assumption.

Frequency and duration of use

Continuous production and release.

Environmental factors influenced by risk management

On site WWTP with the capacity for complete neutralization. Emissions to air may be as much as 1.2 kg/d but are generally much less. Exhaust gases may be treated by scrubbers.

Other operational conditions affecting environmental exposure

The use of sulphuric acid for extractions and in the processing of minerals and ores takes place in a highly specialized, high integrity indoor facility with emissions to water being fully neutralized before release. Reactors and transfer pipelines are closed systems.

Technical conditions and measures at process level (source) to prevent release

As mentioned above reactors and pipelines are fully sealed. Both production and sampling are carried out in dedicated facilities.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Sulphuric acid used for extractions and in the processing of minerals and ores on a large scale generally occurs on major chemical sites which will have dedicated effluent treatment facilities, involving both chemical and biological treatment, coping with many chemical substances. As such any emission to wastewater will be almost instantly hydrolysed before even reaching the STP.

Neutralisation procedures are in place to ensure that the pH of any downstream biological treatment or final receiving waters is not affected. All waste waters should be treated in this manner. Measured pH values can be used to confirm the efficacy of the neutralization procedure.

Organizational measures to prevent/limit releases from site

Workers are fully trained in order to prevent accidental release. pH alarms are in place to monitor the pH and ensure successful neutralization has taken place.

Conditions and measures related to municipal STP

Emissions to the municipal STP should not be made. All waste water should be treated in the on-site waste water treatment plant. Precipitated sludge should be sent for specialized waste treatment and should not be spread to soil.

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Conditions and measures related to external treatment of waste for disposal	
Sludge from the on-site WWTP is collected and processed for residual metal recovery, incinerated or sent for recovery. Waste from any scrubbers should be directed to waste water. There is no further generation of solid waste.	
Conditions and measures related to external recovery of waste	
There is no envisaged external recovery of waste.	
4.2	Controlling worker exposure for ES 4
ES4: CES 2: worker exposure arising due to use in closed processes with some potential for exposure (PROC 2) and CES 3: worker exposure arising due to day to day use in batch or other processes with some potential for exposure (PROC 3 and PROC 4).	
During the use of sulphuric acid in the processing of minerals and ores, controlled systems are in place to reduce the potential for worker exposure in all cases.	
Loading and unloading of tankers with sulphuric acid is performed in the open air. Workers wear protective clothing (face/eye protection, helmet, anti-acid gloves boots and protective overall). Respiratory protection is used when required. A safety shower is required nearby in case of accidental spillage. Gas displacement lines are also used if filling of road tankers takes place under cover.	
Product characteristics	
The produced substance is a liquid with purity greater than 90%. The substance is colourless, odourless inorganic liquid which is miscible with water. Sulphuric acid is not flammable and is non-explosive.	
Amounts used	
Facilities may use up to 480 tonnes per year, considered to be a worst case assumption.	
Frequency and duration of use exposure	
Workers perform standard shifts of 8 hours per day and have standard working years of 220 days per year. However, some tasks, such as sampling and maintenance are expected to be of a short duration.	
Human factors not influenced by risk management	
Respiration volumes under conditions of use 10m ³ /d (default value for a worker breathing for an 8h work day in RIP 3.2).	
Other given operational conditions affecting worker exposure	
Both production and sampling are carried out at dedicated facilities with vapour recovery systems in place where required. Transfer operations are carried out in controlled systems with dedicated machinery. The handling of sulphuric acid involves special equipment and controlled systems with little or no potential for exposure.	
Technical conditions and measures at process level (source) to prevent release	
Reactors and pipes are sealed systems. Loss from reactor and pipes is monitored.	
Technical conditions to control dispersion from source towards worker	
Any gas displaced from containers is conducted via pipeline to be processed (removed and scrubbed and /or filtered) in the areas where sulphuric acid is used in the processing of minerals and ores. During handling when transferring drum filling, special equipment and controlled systems with little or no potential for exposure are used to prevent losses occurring.	
Organizational measures to prevent/limit release	
Workers involved in the sampling and workers involved in extraction work are generally separated from the leaching and extraction heaps and systems with no direct contact to the acid. Workers involved in	

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

sampling and transfer of materials (new or waste acids to be recycled) to road tankers are trained in the procedures and protective equipment is intended to cope with the worst case scenario, in order to minimise exposure and risks.

Conditions and measures related to personal protection, hygiene and health.

Gloves, goggles, chemical resistant overalls and work boots are worn by all operators in the facility to prevent dermal exposure.

4.3

Exposure estimation and reference to its source

Environmental Exposure

For the tier 1 risk characterisation PECs derived using the ERC defaults are not assessed below as the PECs are considered unrealistically high and would lead to a failing risk assessment in any case. For the tier 2 risk characterisation the PECs calculated by the EUSES environmental model with refined inputs taking into account the emission RMMs as discussed in section 2.1 above are used to control environmental releases are used for the assessment.

Information for contributing exposure scenario 1:

List of exposure concentrations

Compartment	PEC	Justification
Freshwater (in mg/L)	5.91×10^{-6}	
Marine water (in mg/L)	8.56×10^{-7}	
Intermittent releases to water (in mg/L)	NA	Intermittent release not relevant
Freshwater sediment (in mg/kg)	4.8×10^{-6}	
Marine sediment (in mg/kg)	6.9×10^{-7}	
Agricultural soil (averaged over 30 days (in mg/kg)	3.9×10^{-4}	
Groundwater (in mg/L)	2.9×10^{-3}	
Annual average PEC in air, total (mg/m ³)	0.0091	

The following RCRs were derived taking into account derived PNEC values

Compartments	PEC mg/L	PNEC mg/L	PEC/PNEC	Comments
ERC 6B Tier 2 Freshwater	2.6×10^{-8}	0.0025	1.1×10^{-4}	Safe use demonstrated in tier 2
ERC 6B Tier 2 Sediment	2×10^{-8}	0.002 (EPM)	1×10^{-5}	Safe use demonstrated in tier 2
ERC 6B Tier 2 Marine sediment	3×10^{-9}	0.002 (EPM)	1×10^{-6}	Safe use demonstrated in tier 2
ERC 6B Tier 2	3.8×10^{-9}	0.00025	1.5×10^{-5}	Safe use

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Marine				demonstrated in tier 2
ERC 4Tier 2 Freshwater	2.5×10^{-5}	0.0025	0.01	Safe use demonstrated in tier 2
ERC 4Tier 2 Sediment	2×10^{-5}	0.002 (EPM)	0.01	Safe use demonstrated in tier 2
ERC 4Tier 2 Marine sediment	2.9×10^{-6}	0.002 (EPM)	0.0145	Safe use demonstrated in tier 2
ERC 4Tier 2 Marine	3.6×10^{-6}	0.00025	0.0144	Safe use demonstrated in tier 2

* EPM = equilibrium partitioning method

Worker exposure

The Advanced REACH tool (ART) was used to estimate worker exposure as it was considered that the ECETOC model cannot estimate in a satisfactory manner the effects of the stringent containment and segregation practices which are in place to deal with sulphuric acid production and to limit exposure.

In the characterisation of the human health risks posed by acute/short term and long-term inhalation exposures to sulphuric acid (or formed sulphuric acid) associated with ES 4, the 90th percentile (e.g. worst case) inhalation exposure concentrations derived using the ART model for relevant PROC codes were compared with the DNEL value for acute local respiratory effects and the DNEL value for long-term local respiratory effects respectively. The results of the risk characterisation are shown in the table below.

The predicted acute/short-term and long-term inhalation exposure concentrations derived using the ART model were not found to exceed the DNEL value for acute local respiratory effects or the DNEL value for long-term local respiratory effects respectively for any of the processes associated with ES 4. On the basis of the assumptions made in the exposure assessment and this risk characterisation, it can be concluded that inhalation exposures to sulphuric acid that may potentially arise during processes associated with ES 4 do not pose an unacceptable health risk to workers.

Information for worker contributing scenarios 2 and 3:

List of inputs used in the ART assessment

	PROC	Parameters/ assumptions
Exposure duration	All	480 mins
Product type	All	Liquid (medium viscosity – like oil)
Process temperature	All	Hot processes (50-150oC)
Vapour pressure	All	6 Pa – Substance is considered to be low volatile, exposure to mists is estimated
Liquid weight fraction	All	0.98
Primary emission source proximity	PROC 2	Primary emission source is not located in the breathing zone of the worker - the assessment for this

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

		activity involves a primary far-field emission source only (workers are in a control room)
	PROC 3,4	Primary emission source located in the breathing zone of the workers (i.e. Within 1 metre)
Activity class	All	Transfer of liquid products
Containment	PROC 2,3	Handling reduces contact between product and adjacent air
	PROC 4	Open process, submerged loading
Localised controls	PROC 2	Vapour recovery systems; LEV
	PROC 2,4	Vapour recovery
Segregation	PROC 2	Complete segregation of workers in separate control room
Fugitive emission source	PROC 3	Process fully enclosed – not breached for sampling
	PROC 2,4	Not fully enclosed – effective housekeeping practices in place.
Dispersion	PROC 2	Outdoors not close to buildings
	PROC 3,4	Outdoors near to buildings

List of derived exposure concentrations

Description of activity	PROC	Physical state of material	Short-term Concentrations		Long-term Concentration	
			Estimated Exposure (mg/m ³) 50 th percentile value	90 th percentile value	Estimated Exposure (mg/m ³) 50 th percentile value	90 th percentile value
Use in closed, continuous process with occasional controlled exposure (including sampling and maintenance)	2	Liquid	8.20×10^{-09}	9.20×10^{-08}	3.60×10^{-08}	9.20×10^{-08}
Use in closed batch process (synthesis or formulation)	3	Liquid	3.70×10^{-05}	4.20×10^{-04}	1.60×10^{-04}	4.20×10^{-04}
Use in batch and other process (synthesis) where opportunity for exposure arises	4	Liquid	0.0012	0.014	0.0054	0.014

List of derived RCRs

Exposure details	CES	PROC Code	ES 4- 90 th exposure concentrations (mg/m ³)	Leading toxic end point / Critical effect	DNEL (mg/m ³)	Risk characterisation ratio
Acute-local effects	CES 2	PROC 2	9.2×10^{-8}	Respiratory irritation and corrositivity	0.1	9.2×10^{-7}
	CES 3	PROC 3	4.2×10^{-4}	Respiratory irritation and corrositivity	0.1	4.2×10^{-3}

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

		PROC 4	1.4×10^{-2}	Respiratory irritation and corrositivity	0.1	1.4×10^{-1}
Long-term – local effects	CES 2	PROC 2	9.2×10^{-8}	Respiratory irritation and corrositivity	0.05	1.8×10^{-6}
	CES 3	PROC 3	4.2×10^{-4}	Respiratory irritation and corrositivity	0.05	8.4×10^{-3}
		PROC 4	1.4×10^{-2}	Respiratory irritation and corrositivity	0.05	2.8×10^{-1}

Assessment of dermal risk

During the processes that will be carried out for all the exposure scenarios associated with production and use of sulphuric acid a potential risk may arise if sulphuric acid comes into contact with human skin. This is due to the nature of sulphuric acid and its ability to cause chemical burns. As this effect is considered to be related to the corrosivity of sulphuric acid a threshold DNEL cannot be established for this risk and so measures to control this risk should be assessed in a qualitative manner. Though this risk is most pertinent when workers may come into contact with concentrated sulphuric acid in an industrial setting the operational conditions (OCs) and risk management measures (RMMs) used to control and manage the risk of dermal contact events may be equally applicable across all the exposure scenarios.

In the industrial setting an acute risk of dermal burns from exposure to sulphuric acid in its concentrated form (or its dilute form) exists due to possible splashing of the liquid acid. This risk would be highest at times of transfer to tankers, filling of barrels and filling of small vessels etc. Though these events are considered unlikely due to the high degree of system closure and control the risk is still protected against in order to eliminate any possible routes of exposure.

The risk of dermal contact is reduced due to the OC's in place. The specialised nature of the systems and the degree of closure associated with them ensure the potential for dermal contact is minimised. All pipes and transfers lines are closed and sealed in order to reduce possible exposure to leaks or splashes, as are the reactors to reduce possible emissions. During times of transfer to/from road tankers gas displacement lines and special connecting systems are in place to reduce the levels of gaseous emissions that could deposit to surfaces including human skin. Specialised tanker coupling/uncoupling systems and targeted purging systems may be used in certain circumstances where large volumes and high concentrations are required. Training and certification ensures the workers understand the correct procedures for use of these specialized systems so that the measures in place to reduce emissions are conducted so proper function can be maintained.

In addition to the measures in place to reduce system emissions, workers are completely separated from the site of operation. Workers are generally housed in areas segregated from the main emission sources and time spent on tasks which require close proximity to the emission sources can be minimised effectively. Separate control rooms, screens and outdoor reactor units help to keep workers away from any potential sources of exposure. Emergency measures (and training on procedures and safe work

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

practice) are in place in the industrial setting to ensure that any unforeseen events are safely dealt with in the case that they do arise. These measures range from procedural policies which are in place to guide workers in the proper response in the case of splashes or spills to dedicated equipment (such as emergency showers or spill clean-up kits) which can be used to minimise any effects should unforeseen exposure arise.

Personal protective equipment (PPE) should be supplied to any personnel who may be working in areas where potential emission sources (such as transfer pipes) are located. Suitable PPE that should be used to prevent dermal contact for workers would be acid resistant clothing, helmets, gloves, goggles and boots. The PPE should be properly maintained and certified and should be replaced when required. These measures combined will effectively function to ensure three aspects of safe use. These are, firstly, reduction of potential emissions with specialised systems. Secondly reduction of the potential for exposure of workers by means such as segregation and training and thirdly physical protection of the worker with the use of correct PPE. With the combination of these measures it is considered that the risk of chemical burns to workers is adequately managed.

As mentioned above when the concentration of the sulphuric acid decreases so does the potential for chemical burns to human skin. However the same measures are still in place to ensure that workers, professionals and consumers are protected from risk.

4.4

Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environmental releases:

In order to work within the boundaries of the ES the following conditions should be met:

- Emission to air after scrubbing less than 1,140 kg per day
- No emission to the municipal STP
- The industrial WWTP sludge should not be spread to soil
- Wastewater should be fully neutralized
- Exhaust gases from the intermediate use are treated with scrubbers.
- Measured emissions should be confirmed to be less than the relevant PNECs in section 3

Worker exposure:

In order to work within the boundaries of the ES the following conditions should be met:

- Reactors and pipelines should be sealed systems
- Workers should wear protective gloves, goggles, overalls and boots at all times in the production and transfer area
- Workers should be segregated from the area of use.
- Any measured exposure should be confirmed to be less than the relevant DNELs in section 3 above.

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

4.5	Additional good practice advice beyond the REACH CSA.
-----	--

- Do not eat, drink or smoke when working with sulphuric acid.
- Always wash hands and exposed skin thoroughly after using sulphuric acid or any surfaces/machinery that may have come into contact with sulphuric acid.
- Workers should be suitably trained in all safety procedures and in the safe handling of sulphuric acid to prevent risk of exposure.
- All PPE should be properly maintained and stored in an appropriate way so as not to damage its integrity. Workers should be correctly trained in its use.
- Procedural and safety compliance should be routinely assessed by management
- Machinery should be regularly maintained and checked for proper function
- Efficacy of all emission RMMs and waste treatment procedures should be routinely assessed and confirmed to be functioning correctly

5	Exposure Scenario 5: Use of Sulphuric Acid in surface treatments, purification and etching.
---	--

Use of Sulphuric Acid in surface treatments, purification and etching.

Processes Covered:

Environmental Releases

ERC06B: Industrial use of reactive processing aids.

Worker Processes

PROC01: Use in closed process, no likelihood of exposure
 PROC02: Use in closed, continuous process with occasional controlled exposure (including sampling and maintenance)
 PROC03: Use in closed batch process (synthesis or formulation)
 PROC04: Use in batch and other process (synthesis) where opportunity for exposure arises
 PROC08a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities
 PROC08b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities
 PROC09: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
 PROC13: Treatment of articles by dipping and pouring

Produce Category

PC14: Metal surface treatment products, including galvanic and electroplating products
 PC15: Non-metal-surface treatment products

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Sulphuric acid is used in surface treatment, purification and etching to pickle metallic surface prior to electrolysis in order to remove impurities, stains, rust or other inorganic contaminants. Used pickling fluid is generally neutralised and does not have any consumer application. The processes which use sulphuric acid as metallurgical surface treatments are highly specialised and are controlled to limit emissions and environmental exposure.

Because of the conditions involved in the metal treatment processes (and the nature of sulphuric acid and the produced gases) specially trained workers and systems are employed.

Contributing Environmental Scenario: CES1 Environmental exposure arising due to the use of sulphuric acid in surface treatment, purification and etching. (ERC 6B).

Contributing Worker Scenarios: CES 2: Worker exposure arising due to use in closed processes with no likelihood of exposure (PROC 1), CES 3: worker exposure arising due to use in closed processes with some potential for exposure (PROC 2), CES 4: worker exposure arising due to day to day use in batch or other processes with some potential for exposure (PROC 3 and PROC 4), CES 5: worker exposure arising due transfer of substances to large vessels at non-dedicated and dedicated facilities (PROC 8a and PROC 8b), CES 6: worker exposure arising due to transfer of formulation to small containers (PROC 9) and CES 7: worker exposure arising due to treatment of articles by dipping and pouring.

5.1 Controlling environmental exposure for ES 5

ES5: Contributing exposure scenario (CES) 1 Environmental exposure arising due to use of sulphuric acid in surface treatment, purification and etching.

Section 2.1 describes the environmental releases that may occur during the use of sulphuric acid in surface treatment, purification and etching. These releases may potentially occur due to emission to wastewater or through emission to the atmosphere. Environmental emissions are limited by designated waste treatment process designed to limit environmental exposure to all relevant compartments. Waste gas emissions are scrubbed and may also then be diverted to the wastewater stream. This significantly lessens the possible emission by atmospheric deposition to soil or surface waters.

Liquid wastes are treated (neutralization to neutral pH) prior to emission to remove any sulphuric acid in the waste water. Sludge from the waste water treatment plant is sent for incineration or landfill and is not used for agricultural spreading. This precludes any contamination of soil by sludge spreading. Waste water treatment is usually carried out by neutralisation followed by flocculation or decantation.

Use of sulphuric acid in surface treatment, purification and etching is generally continuous with constant production and use. Facilities generally use between 50 and 200 tonnes per year, with utilization of 10,000 tonnes per year at one site considered to be a worst case assumption.

Product characteristics

The produced substance is a liquid with purity greater than 90%. The substance is colourless, odourless inorganic liquid which is miscible with water. Sulphuric acid is not flammable and is non-explosive.

Amounts used

Facilities generally use between 50 and 200 tonnes per year in a working year of 365 days, with utilization of 10,000 tonnes per year at one site considered to be a worst case assumption.

Frequency and duration of use

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Continuous production and release.	
Environmental factors influenced by risk management	
On site WWTP with the capacity for complete neutralization. Emissions to air may be as much as 27.4 kg/d but are generally much less. Exhaust gases may be treated by scrubbers.	
Other operational conditions affecting environmental exposure	
The use of sulphuric acid in surface treatment, purification and etching takes place in a highly specialized, high integrity, contained indoor facility with emissions to water being fully neutralized before release. Reactors and transfer pipelines are closed systems.	
Technical conditions and measures at process level (source) to prevent release	
As mentioned above reactors and pipelines are fully sealed. Both production and sampling are carried out in dedicated facilities.	
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
<p>Sulphuric acid used in surface treatment, purification and etching on a large scale generally occurs on major chemical sites which will have dedicated effluent treatment facilities, involving both chemical and biological treatment, coping with many chemical substances. As such any emission to wastewater will be almost instantly hydrolysed before even reaching the STP.</p> <p>Neutralisation procedures are in place to ensure that the pH of any downstream biological treatment or final receiving waters is not affected. All waste waters should be treated in this manner. Measured pH values can be used to confirm the efficacy of the neutralization procedure.</p>	
Organizational measures to prevent/limit releases from site	
Workers are fully trained in order to prevent accidental release.	
Conditions and measures related to municipal STP	
Waste waters are generally treated on site by chemical and/or biological methods before release to the municipal STP or to the environment.	
Conditions and measures related to external treatment of waste for disposal	
All sludge from onsite WWTP is collected and incinerated or sent to landfill. Waste from any scrubbers should be directed to waste water stream for further treatment. There is no further generation of solid waste.	
Conditions and measures related to external recovery of waste	
There is no envisaged external recovery of waste.	

5.2	Controlling worker exposure for ES 5
<p>ES5: CES 2: Worker exposure arising due to use in closed processes with no likelihood of exposure (PROC 1), CES 3: worker exposure arising due to use in closed processes with some potential for exposure (PROC 2), CES 4: worker exposure arising due to day to day use in batch or other processes with some potential for exposure (PROC 3 and PROC 4), CES 5: worker exposure arising due transfer of substances to large vessels at non-dedicated and dedicated facilities (PROC 8a and PROC 8b), CES 6: worker exposure arising due to transfer of formulation to small containers (PROC 9) and CES 7: worker exposure arising due to treatment of articles by dipping and pouring.</p> <p>During the use of sulphuric acid in surface treatment, purification and etching, controlled systems are in place to reduce the potential for worker exposure in all cases.</p>	

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

<p>Loading and unloading of tankers with sulphuric acid for use as a surface treatment and etching agent is usually performed in the open air. Workers wear protective clothing (face/eye protection, helmet, anti-acid gloves boots and protective overall). A safety shower is required nearby in case of accidental spillage. Gas displacement lines are also used if filling of road tankers takes place under cover.</p>	
Product characteristics	
<p>The produced substance is a liquid with purity greater than 90%. The substance is colourless, odourless inorganic liquid which is miscible with water. Sulphuric acid is not flammable and is non-explosive.</p>	
Amounts used	
<p>Facilities generally use between 50 and 200 tonnes per year in a working year of 365 days, with utilization of 10,000 tonnes per year at one site considered to be a worst case assumption.</p>	
Frequency and duration of use exposure	
<p>Workers perform standard shifts of 8 hours per day and have standard working years of 220 days per year. However, some tasks, such as sampling and maintenance and dipping and pouring are expected to be of a short duration.</p>	
Human factors not influenced by risk management	
<p>Respiration volumes under conditions of use 10m³/d (default value for a worker breathing for an 8h work day in RIP 3.2).</p>	
Other given operational conditions affecting worker exposure	
<p>Both production and sampling are carried out at dedicated facilities with vapour recovery systems in place where required. Transfer operations are carried out in controlled systems with dedicated machinery. The handling of sulphuric acid involves special equipment and controlled systems with little or no potential for exposure.</p>	
Technical conditions and measures at process level (source) to prevent release	
<p>Reactors and pipes are sealed systems. Loss from reactor and pipes is monitored.</p>	
Technical conditions to control dispersion from source towards worker	
<p>Any gas displaced from containers is conducted via pipeline to be processed (removed and scrubbed and /or filtered) in the areas where sulphuric acid is used in surface treatment, purification and etching. During handling when transferring drum filling, special equipment and controlled systems with little or no potential for exposure are used to prevent losses occurring.</p>	
Organizational measures to prevent/limit release	
<p>Workers involved in sampling and transfer of materials to road tankers are trained in the procedures and protective equipment is intended to cope with the worst case scenario, in order to minimise exposure and risks.</p>	
Conditions and measures related to personal protection, hygiene and health.	
<p>Gloves, goggles, chemical resistant overalls and work boots are worn by all operators in the facility to prevent dermal exposure.</p>	
5.3	Exposure estimation and reference to its source

Environmental Exposure

For the tier 1 risk characterisation PECs derived using the ERC defaults are not assessed below as the PECs are considered unrealistically high and would lead to a failing risk assessment in any case. For the tier 2 risk characterisation the PECs calculated by the EUSES environmental model with refined inputs taking into account the emission RMMs as discussed in section 2.1 above are used to control

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

environmental releases are used for the assessment.

Information for contributing exposure scenario 1:

List of exposure concentrations

Compartment	PEC	Justification
Freshwater (in mg/L)	5.91×10^{-7}	
Marine water (in mg/L)	8.56×10^{-8}	
Intermittent releases to water (in mg/L)	NA	Intermittent release not relevant
Freshwater sediment (in mg/kg)	2×10^{-8}	
Marine sediment (in mg/kg)	3×10^{-9}	
Agricultural soil (averaged over 30 days (in mg/kg)	3.94×10^{-5}	
Groundwater (in mg/L)	2.91×10^{-4}	
Annual average PEC in air, total (mg/m ³)	7.62×10^{-3}	

The following RCRs were derived taking into account derived PNEC values

Compartments	PEC mg/L	PNEC mg/L	PEC/PNEC	Comments
Tier 2 Freshwater	5.9×10^{-7}	0.0025	2.3×10^{-4}	Safe use demonstrated in tier 2
Tier 2 Sediment	4.75×10^{-7}	0.002 (EPM)	2.35×10^{-4}	Safe use demonstrated in tier 2
Tier 2 Marine sediment	3×10^{-9}	0.002 (EPM)	1×10^{-6}	Safe use demonstrated in tier 2
Tier 2 Marine	8.56×10^{-8}	0.00025	3.4×10^{-5}	Safe use demonstrated in tier 2

* EPM = equilibrium partitioning method

Worker exposure

The Advanced REACH tool (ART) was used to estimate worker exposure as it was considered that the ECETOC model cannot estimate in a satisfactory manner the effects of the stringent containment and segregation practices which are in place to deal with sulphuric acid production and to limit exposure.

In the characterisation of the human health risks posed by acute/short term and long-term inhalation exposures to sulphuric acid (or formed sulphuric acid) associated with ES 5, the 90th percentile (e.g. worst case) inhalation exposure concentrations derived using the ART model for relevant PROC codes were compared with the DNEL value for acute local respiratory effects and the DNEL value for long-term local respiratory effects respectively. The results of the risk characterisation are shown in the table below.

The predicted acute/short-term and long-term inhalation exposure concentrations derived using the ART

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

model were not found to exceed the DNEL value for acute local respiratory effects or the DNEL value for long-term local respiratory effects respectively for any of the processes associated with ES 5. On the basis of the assumptions made in the exposure assessment and this risk characterisation, it can be concluded that inhalation exposures to sulphuric acid that may potentially arise during processes associated with ES 5 do not pose an unacceptable health risk to workers.

Information for worker contributing scenarios 2, 3, 4, 5, 6 and 7:

List of inputs used in the ART assessment

	PROC	Parameters/ assumptions
Exposure duration	All	480 mins
Product type	All	Liquid (medium viscosity – like oil)
Process temperature	PROC 1,2,3,4	Hot processes (50-150oC)
	PROC 8a,8b, 9,13	Room temperature (15-25oC)
Vapour pressure	All	6 Pa – Substance is considered to be low volatile, exposure to mists is estimated
Liquid weight fraction	All	0.98
Primary emission source proximity	PROC 1,2	Primary emission source is not located in the breathing zone of the worker - the assessment for this activity involves a primary far-field emission source only (workers are in a control room)
	PROC 3,4,8a,8b,9,13	Primary emission source located in the breathing zone of the workers (i.e. Within 1 metre)
Activity class	PROC 1,2,3,4,8a,8b,9	Transfer of liquid products
	PROC 13	Activities with open liquid surface or reservoirs
Containment	PROC 1,2,3,9	Handling reduces contact between product and adjacent air
	PROC 4	Open process, submerged loading
	PROC 8a,8b,13	n/a
Localised controls	PROC 1,2,3,8b,	Vapour recovery systems; LEV
	PROC 2,4,9	Vapour recovery
	PROC 8a,13	None
Segregation	PROC 1,2	Complete segregation of workers in separate control room
Fugative emission source	PROC 1,3,8b,9	Process fully enclosed – not breached for sampling
	PROC 2,4,8a,13	Not fully enclosed – effective housekeeping practices in place.
Dispersion	PROC 1,2, 8a, 8b	Outdoors not close to buildings
	PROC 3,4	Outdoors near to buildings
	PROC 9,13	Indoors, any sized room, only good natural ventilation

List of derived exposure concentrations

Description of activity	PROC	Physical state of material	Estimated Exposure (mg/m3)	Short-term Concentrations	Estimated Exposure (mg/m3)	Long-term Concentration

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

			50 th percentile value	90 th percentile value	50 th percentile value	90 th percentile value
Use in closed process, no likelihood of exposure	1	Liquid	8.20×10^{-10}	9.30×10^{-09}	3.60×10^{-09}	9.40×10^{-09}
Use in closed, continuous process with occasional controlled exposure (including sampling and maintenance)	2	Liquid	8.20×10^{-09}	9.20×10^{-08}	3.60×10^{-08}	9.20×10^{-08}
Use in closed batch process (synthesis or formulation)	3	Liquid	3.70×10^{-05}	4.20×10^{-04}	1.60×10^{-04}	4.20×10^{-04}
Use in batch and other process (synthesis) where opportunity for exposure arises	4	Liquid	0.0012	0.014	0.0054	0.014
Loading/transfer: Loading and unloading a tanker (non-dedicated site)	8a	Liquid	0.002	0.023	0.0088	0.023
Loading/transfer: Loading and unloading a tanker (dedicated site)	8b	Liquid	1.10×10^{-05}	1.20×10^{-04}	4.80×10^{-05}	4.80×10^{-06}
Loading/transfer (filling small containers with sulphuric acid)	9	Liquid	0.00081	0.0032	0.0011	0.0028
Treatment of articles by dipping and pouring (immersion operations)	13	Liquids	0.0045	0.018	0.0062	0.016

List of derived RCRs

Exposure details	CES	PROC Code	ES 5- 90 th exposure concentrations (mg/m3)	Leading toxic end point / Critical effect	DNEL (mg/m3)	Risk characterisation ratio
Acute-local effects	CES 2	PROC 1	9.3×10^{-9}	Respiratory irritation and corrositivity	0.1	9.3×10^{-8}
	CES 3	PROC 2	9.2×10^{-8}	Respiratory irritation and corrositivity	0.1	9.2×10^{-7}
	CES 4	PROC 3	4.2×10^{-4}	Respiratory irritation and corrositivity	0.1	4.2×10^{-3}
		PROC 4	1.4×10^{-2}	Respiratory irritation and corrositivity	0.1	1.4×10^{-1}
	CES 5	PROC 8a	2.3×10^{-2}	Respiratory irritation and corrositivity	0.1	2.3×10^{-1}
		PROC 8b	1.2×10^{-4}	Respiratory irritation and corrositivity	0.1	1.2×10^{-3}

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Long-term – local effects	CES 6	PROC 9	3.2×10^{-3}	Respiratory irritation and corrositivity	0.1	3.2×10^{-2}
	CES 7	PROC 13	1.8×10^{-2}	Respiratory irritation and corrositivity	0.1	1.8×10^{-1}
	CES 2	PROC 1	9.4×10^{-9}	Respiratory irritation and corrositivity	0.05	8.4×10^{-3}
	CES 3	PROC 2	9.2×10^{-8}	Respiratory irritation and corrositivity	0.05	2.8×10^{-1}
	CES 4	PROC 3	4.2×10^{-4}	Respiratory irritation and corrositivity	0.05	4.6×10^{-1}
		PROC 4	1.4×10^{-2}	Respiratory irritation and corrositivity	0.05	9.6×10^{-5}
	CES 5	PROC 8a	2.3×10^{-2}	Respiratory irritation and corrositivity	0.05	5.6×10^{-2}
		PROC 8b	4.8×10^{-6}	Respiratory irritation and corrositivity	0.05	3.2×10^{-1}
	CES 6	PROC 9	2.8×10^{-3}	Respiratory irritation and corrositivity	0.05	8.4×10^{-3}
	CES 7	PROC 13	1.6×10^{-2}	Respiratory irritation and corrositivity	0.05	2.8×10^{-1}

Assessment of dermal risk

During the processes that will be carried out for all the exposure scenarios associated with production and use of sulphuric acid a potential risk may arise if sulphuric acid comes into contact with human skin. This is due to the nature of sulphuric acid and its ability to cause chemical burns. As this effect is considered to be related to the corrosivity of sulphuric acid a threshold DNEL cannot be established for this risk and so measures to control this risk should be assessed in a qualitative manner. Though this risk is most pertinent when workers may come into contact with concentrated sulphuric acid in an industrial setting the operational conditions (OCs) and risk management measures (RMMs) used to control and manage the risk of dermal contact events may be equally applicable across all the exposure scenarios.

In the industrial setting an acute risk of dermal burns from exposure to sulphuric acid in its concentrated form (or its dilute form) exists due to possible splashing of the liquid acid. This risk would be highest at times of transfer to tankers, filling of barrels and filling of small vessels etc. Though these events are considered unlikely due to the high degree of system closure and control the risk is still protected against in order to eliminate any possible routes of exposure.

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

The risk of dermal contact is reduced due to the OC's in place. The specialised nature of the systems and the degree of closure associated with them ensure the potential for dermal contact is minimised. All pipes and transfers lines are closed and sealed in order to reduce possible exposure to leaks or splashes, as are the reactors to reduce possible emissions. During times of transfer to/from road tankers gas displacement lines and special connecting systems are in place to reduce the levels of gaseous emissions that could deposit to surfaces including human skin. Specialised tanker coupling/uncoupling systems and targeted purging systems may be used in certain circumstances where large volumes and high concentrations are required. Training and certification ensures the workers understand the correct procedures for use of these specialized systems so that the measures in place to reduce emissions are conducted so proper function can be maintained.

In addition to the measures in place to reduce system emissions, workers are completely separated from the site of operation. Workers are generally housed in areas segregated from the main emission sources and time spent on tasks which require close proximity to the emission sources can be minimised effectively. Separate control rooms, screens and outdoor reactor units help to keep workers away from any potential sources of exposure. Emergency measures (and training on procedures and safe work practice) are in place in the industrial setting to ensure that any unforeseen events are safely dealt with in the case that they do arise. These measures range from procedural policies which are in place to guide workers in the proper response in the case of splashes or spills to dedicated equipment (such as emergency showers or spill clean-up kits) which can be used to minimise any effects should unforeseen exposure arise.

Personal protective equipment (PPE) should be supplied to any personnel who may be working in areas where potential emission sources (such as transfer pipes) are located. Suitable PPE that should be used to prevent dermal contact for workers would be acid resistant clothing, helmets, gloves, goggles and boots. The PPE should be properly maintained and certified and should be replaced when required. These measures combined will effectively function to ensure three aspects of safe use. These are, firstly, reduction of potential emissions with specialised systems. Secondly reduction of the potential for exposure of workers by means such as segregation and training and thirdly physical protection of the worker with the use of correct PPE. With the combination of these measures it is considered that the risk of chemical burns to workers is adequately managed.

As mentioned above when the concentration of the sulphuric acid decreases so does the potential for chemical burns to human skin. However the same measures are still in place to ensure that workers, professionals and consumers are protected from risk.

5.4

Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environmental releases:

In order to work within the boundaries of the ES the following conditions should be met:

- Emission to air after scrubbing less than 27.4 kg per day
- No emission to the municipal STP

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

- The industrial WWTP sludge should not be spread to soil
- Wastewater should be fully neutralized
- Exhaust gases from the intermediate use are treated with scrubbers.
- Measured emissions should be confirmed to be less than the relevant PNECs in section 3

Worker exposure:

In order to work within the boundaries of the ES the following conditions should be met:

- Reactors and pipelines should be sealed systems
- Workers should wear protective gloves, goggles, overalls and boots at all times in the production and transfer area
- Workers should be segregated from the area of use.
- Any measured exposure should be confirmed to be less than the relevant DNELs in section 3 above.

5.5

Additional good practice advice beyond the REACH CSA.

- Do not eat, drink or smoke when working with sulphuric acid.
- Always wash hands and exposed skin thoroughly after using sulphuric acid or any surfaces/machinery that may have come into contact with sulphuric acid.
- Workers should be suitably trained in all safety procedures and in the safe handling of sulphuric acid to prevent risk of exposure.
- All PPE should be properly maintained and stored in an appropriate way so as not to damage its integrity. Workers should be correctly trained in its use.
- Procedural and safety compliance should be routinely assessed by management
- Machinery should be regularly maintained and checked for proper function
- Efficacy of all emission RMMs and waste treatment procedures should be routinely assessed and confirmed to be functioning correctly

6

Exposure Scenario 6: Use of Sulphuric Acid in electrolytic processes.

Use of Sulphuric Acid in electrolytic processes.

Processes Covered:

Environmental Releases

ERC05: Industrial use resulting in inclusion into or onto a matrix

ERC6b: Industrial use of reactive processing aids

Worker Processes

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

PROC01: Use in closed process, no likelihood of exposure

PROC02: Use in closed, continuous process with occasional controlled exposure (including sampling and maintenance)

PROC08b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC09: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC13: Treatment of articles by dipping and pouring

Produce Category

PC14: Metal surface treatment products, including galvanic and electroplating products

PC20: Products such as ph-regulators, flocculants, precipitants, neutralization agents

The use of sulphuric acid in electrolytic processes includes metal refining, electroplating of zinc and electrogalvanizing of iron and steel. The processes which use sulphuric acid as electrolytic agents are highly specialised and are controlled to limit emissions and environmental exposure. The electrolytic processes take place in a specially constructed vessel which contains a bath of sulphuric acid solution. Two electrical poles are located either side of the acid bath and these pass current through the electrolyte to achieve electrolysis. As the sulphuric acid acts primarily as an electrolyte the acid may be re-used several times before it is considered spent and sent to the waste system.

Because of the nature of the process during electrolysis (including the corrosive nature of the acid and the electrical currents) specially trained workers and systems are employed.

Contributing Environmental Scenario: CES1 Environmental exposure arising due to the use of sulphuric acid in electrolytic processes. (ERC 5 and ERC 6B).

Contributing Worker Scenarios: CES 2: Worker exposure arising due to use in closed processes with no likelihood of exposure (PROC 1), CES 3: worker exposure arising due to use in closed processes with some potential for exposure (PROC 2), CES 4: worker exposure arising due transfer of substances to large vessels at dedicated facilities (PROC 8b), CES 5: worker exposure arising due to transfer of formulation to small containers (PROC 9) and CES 6: worker exposure arising due to treatment of articles by dipping and pouring (PROC 13).

6.1

Controlling environmental exposure for ES 6

ES6: Contributing exposure scenario (CES) 1 Environmental exposure arising due to use of sulphuric acid in electrolytic processes.

Section 2.1 describes the environmental releases that may occur during the use of sulphuric acid in electrolytic processes. These releases may potentially occur due to emission to wastewater or through emission to the atmosphere. Environmental emissions are limited by designated waste treatment process designed to limit environmental exposure to all relevant compartments. Waste gas emissions are scrubbed and may also then be diverted to the wastewater stream. This significantly lessens the possible emission by atmospheric deposition to soil or surface waters.

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

<p>Liquid wastes are treated (neutralization to neutral pH) prior to emission to remove any sulphuric acid in the waste water. Sludge from the waste water treatment plant is sent for incineration or landfill and is not used for agricultural spreading. This precludes any contamination of soil by sludge spreading. Waste water treatment is usually carried out by neutralisation followed by flocculation or decantation.</p> <p>Use of sulphuric acid in surface treatment, purification and etching is generally continuous with constant production and use. Facilities generally use between 50 and 200 tonnes per day, with utilization of 2,306 tonnes per year at one site considered to be a worst case assumption.</p>
Product characteristics
The produced substance is a liquid with purity greater than 90%. The substance is colourless, odourless inorganic liquid which is miscible with water. Sulphuric acid is not flammable and is non-explosive.
Amounts used
Facilities generally use between 50 and 200 tonnes per day in a working year of 365 days, with utilization of 2,306 tonnes per year at one site considered to be a worst case assumption.
Frequency and duration of use
Continuous production and release.
Environmental factors influenced by risk management
On site WWTP with the capacity for complete neutralization. Emissions to air may be as much as 3,160 kg/d but are generally much less. Exhaust gases may be treated by scrubbers.
Other operational conditions affecting environmental exposure
The use of sulphuric acid in electrolysis processes takes place in a highly specialized, high integrity, contained indoor facilities with emissions to water being fully neutralized before release. Reactors and transfer pipelines are closed systems.
Technical conditions and measures at process level (source) to prevent release
As mentioned above reactors and pipelines are fully sealed. Both production and sampling are carried out in dedicated facilities.
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil
<p>Sulphuric acid used in electrolysis processes on a large scale generally occurs on major chemical sites which will have dedicated effluent treatment facilities, involving both chemical and biological treatment, coping with many chemical substances. As such any emission to wastewater will be almost instantly hydrolysed before even reaching the STP.</p> <p>Neutralisation procedures are in place to ensure that the pH of any downstream biological treatment or final receiving waters is not affected. All waste waters should be treated in this manner.</p>
Organizational measures to prevent/limit releases from site
Workers are fully trained in order to prevent accidental release.
Conditions and measures related to municipal STP
Waste waters are generally treated on site by chemical and/or biological methods before release to the municipal STP or to the environment.
Conditions and measures related to external treatment of waste for disposal
All sludge from onsite WWTP is collected and processed for metal recovery, incinerated or sent to landfill. Waste from any scrubbers should be directed to waste water stream for further treatment. There is no further generation of solid waste.
Conditions and measures related to external recovery of waste
There is no envisaged external recovery of waste.

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

6.2	Controlling worker exposure for ES 6
<p>ES 6: CES 2: Worker exposure arising due to use in closed processes with no likelihood of exposure (PROC 1), CES 3: worker exposure arising due to use in closed processes with some potential for exposure (PROC 2), CES 4: worker exposure arising due transfer of substances to large vessels at dedicated facilities (PROC 8b), CES 5: worker exposure arising due to transfer of formulation to small containers (PROC 9) and CES 6: worker exposure arising due to treatment of articles by dipping and pouring (PROC 13).</p>	
<p>During the use of sulphuric acid in electrolysis processes, controlled systems are in place to reduce the potential for worker exposure in all cases.</p>	
<p>Loading and unloading of tankers with sulphuric acid for use as a surface treatment and etching agent is usually performed in the open air. Workers wear protective clothing (face/eye protection, helmet, anti-acid gloves boots and protective overall). A safety shower is required nearby in case of accidental spillage. Gas displacement lines are also used if filling of road tankers takes place under cover.</p>	
Product characteristics	
<p>The produced substance is a liquid with purity greater than 90%. The substance is colourless, odourless inorganic liquid which is miscible with water. Sulphuric acid is not flammable and is non-explosive.</p>	
Amounts used	
<p>Facilities generally use between 50 and 200 tonnes per year in a working year of 365 days, with utilization of 2,306 tonnes per year at one site considered to be a worst case assumption.</p>	
Frequency and duration of use exposure	
<p>Workers perform standard shifts of 8 hours per day and have standard working years of 220 days per year. However, some tasks, such as sampling and maintenance and dipping and pouring are expected to be of a short duration.</p>	
Human factors not influenced by risk management	
<p>Respiration volumes under conditions of use 10m³/d (default value for a worker breathing for an 8h work day in RIP 3.2).</p>	
Other given operational conditions affecting worker exposure	
<p>Both production and sampling are carried out at dedicated facilities with LEV and vapour recovery systems in place where required. Transfer operations are carried out in controlled systems with dedicated machinery. The handling of sulphuric acid involves special equipment and controlled systems with little or no potential for exposure.</p>	
Technical conditions and measures at process level (source) to prevent release	
<p>Reactors and pipes are sealed systems. Loss from reactor and pipes is monitored.</p>	
Technical conditions to control dispersion from source towards worker	
<p>Any gas displaced from containers is conducted via pipeline to be processed (removed and scrubbed and /or filtered) in the areas where sulphuric acid is used in electrolytic processes. During handling when transferring drum filling, special equipment and controlled systems with little or no potential for exposure are used to prevent losses occurring.</p>	
Organizational measures to prevent/limit release	
<p>Workers involved in sampling and transfer of materials to road tankers are trained in the procedures and protective equipment is intended to cope with the worst case scenario, in order to minimise exposure and risks.</p>	
Conditions and measures related to personal protection, hygiene and health.	

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Gloves, goggles, chemical resistant overalls and work boots are worn by all operators in the facility to prevent dermal exposure.

6.3

Exposure estimation and reference to its source

Environmental Exposure

For the tier 1 risk characterisation PECs derived using the ERC defaults are not assessed below as the PECs are considered unrealistically high and would lead to a failing risk assessment in any case. For the tier 2 risk characterisation the PECs calculated by the EUSES environmental model with refined inputs taking into account the emission RMMs as discussed in section 2.1 above are used to control environmental releases are used for the assessment.

Information for contributing exposure scenario 1:

List of exposure concentrations

Compartment	PEC	Justification
ERC 6B Freshwater (in mg/L)	1.36×10^{-7}	
ERC 6B Marine water (in mg/L)	1.97×10^{-8}	
ERC 6B Intermittent releases to water (in mg/L)	NA	Intermittent release not relevant
ERC 6B Freshwater sediment (in mg/kg)	1.17×10^{-7}	
ERC 6B Marine sediment (in mg/kg)	1.59×10^{-8}	
ERC 6B Agricultural soil (averaged over 30 days (in mg/kg)	9.08×10^{-6}	
ERC 6B Groundwater (in mg/L)	6.72×10^{-5}	
ERC 6B Annual average PEC in air, total (mg/m ³)	1.76×10^{-3}	
ERC 5 Freshwater (in mg/L)	6.81×10^{-5}	
ERC 5 Marine water (in mg/L)	9.87×10^{-6}	
ERC 5 Intermittent releases to water (in mg/L)	NA	Intermittent release not relevant
ERC 5 Freshwater sediment (in mg/kg)	5.48×10^{-5}	
ERC 5 Marine sediment (in mg/kg)	7.94×10^{-6}	
ERC 5 Agricultural soil (averaged over 30 days (in mg/kg)	4.54×10^{-3}	
ERC 5 Groundwater (in mg/L)	0.0336	
ERC 5 Annual average PEC in air, total (mg/m ³)	0.878	

The following RCRs were derived taking into account derived PNEC values

Compartments	PEC mg/L	PNEC mg/L	PEC/PNEC	Comments
ERC 6B Tier 2 Freshwater	1.36×10^{-7}	0.0025	5.2×10^{-5}	Safe use demonstrated in tier 2

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

ERC 6B Tier 2 Sediment	1.17×10^{-7}	0.002 (EPM)	5.5×10^{-5}	Safe use demonstrated in tier 2
ERC 6B Tier 2 Marine sediment	1.59×10^{-8}	0.002 (EPM)	7.9×10^{-6}	Safe use demonstrated in tier 2
ERC 6B Tier 2 Marine	1.97×10^{-8}	0.00025	3.8×10^{-4}	Safe use demonstrated in tier 2
ERC 5Tier 2 Freshwater	6.81×10^{-5}	0.0025	0.039	Safe use demonstrated in tier 2
ERC 5Tier 2 Sediment	4.48×10^{-5}	0.002 (EPM)	0.022	Safe use demonstrated in tier 2
ERC 5Tier 2 Marine sediment	7.94×10^{-6}	0.002 (EPM)	3.9×10^{-3}	Safe use demonstrated in tier 2
ERC 5Tier 2 Marine	9.87×10^{-6}	0.00025	0.039	Safe use demonstrated in tier 2

* EPM = equilibrium partitioning method

Worker exposure

The Advanced REACH tool (ART) was used to estimate worker exposure as it was considered that the ECETOC model cannot estimate in a satisfactory manner the effects of the stringent containment and segregation practices which are in place to deal with sulphuric acid production and to limit exposure.

In the characterisation of the human health risks posed by acute/short term and long-term inhalation exposures to sulphuric acid (or formed sulphuric acid) associated with ES 6, the 90th percentile (e.g. worst case) inhalation exposure concentrations derived using the ART model for relevant PROC codes were compared with the DNEL value for acute local respiratory effects and the DNEL value for long-term local respiratory effects respectively. The results of the risk characterisation are shown in the table below.

The predicted acute/short-term and long-term inhalation exposure concentrations derived using the ART model were not found to exceed the DNEL value for acute local respiratory effects or the DNEL value for long-term local respiratory effects respectively for any of the processes associated with ES 6. On the basis of the assumptions made in the exposure assessment and this risk characterisation, it can be concluded that inhalation exposures to sulphuric acid that may potentially arise during processes associated with ES 6 do not pose an unacceptable health risk to workers.

Information for worker contributing scenarios 2, 3, 4, 5 and 6:

List of inputs used in the ART assessment

	PROC	Parameters/ assumptions
Exposure duration	All	480 mins
Product type	All	Liquid (medium viscosity – like oil)

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Process temperature	PROC 1,2	Hot processes (50-150oC)
	PROC 8b, 9,13	Room temperature (15-25oC)
Vapour pressure	All	6 Pa – Substance is considered to be low volatile, exposure to mists is estimated
Liquid weight fraction	All	0.98
Primary emission source proximity	PROC 1,2	Primary emission source is not located in the breathing zone of the worker - the assessment for this activity involves a primary far-field emission source only (workers are in a control room)
	PROC,8b,9,13	Primary emission source located in the breathing zone of the workers (i.e. Within 1 metre)
Activity class	PROC 1,2,8b,9	Transfer of liquid products
	PROC 13	Activities with open liquid surface or reservoirs
Containment	PROC 1,2,9	Handling reduces contact between product and adjacent air
	PROC 8b,13	n/a
Localised controls	PROC 1,8b,	Vapour recovery systems; LEV
	PROC 2,9	Vapour recovery
	PROC 13	LE
Segregation	PROC 1,2	Complete segregation of workers in separate control room
Fugitive emission source	PROC 1,8b,9	Process fully enclosed – not breached for sampling
	PROC 2,13	Not fully enclosed – effective housekeeping practices in place.
Dispersion	PROC 1,2, 8a, 8b	Outdoors not close to buildings
	PROC 9,13	Indoors, any sized room, only good natural ventilation (however LEV will be employed when needed).

List of derived exposure concentrations

Description of activity	PROC	Physical state of material	Estimated Exposure (mg/m3)	Short-term Concentrations		Estimated Exposure (mg/m3)	Long-term Concentration
				50 th percentile value	90 th percentile value	50 th percentile value	90 th percentile value
Use in closed process, no likelihood of exposure	1	Liquid	8.20×10^{-10}		9.30×10^{-09}	3.60×10^{-09}	9.40×10^{-09}
Use in closed, continuous process with occasional controlled exposure (including sampling and maintenance)	2	Liquid	8.20×10^{-09}		9.20×10^{-08}	3.60×10^{-08}	9.20×10^{-08}
Loading/transfer: Loading and unloading a tanker (dedicated site)	8b	Liquid	1.10×10^{-05}		1.20×10^{-04}	4.80×10^{-05}	4.80×10^{-06}
Loading/transfer (filling small containers with	9	Liquid	0.00081		0.0032	0.0011	0.0028

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

sulphuric acid)						
Treatment of articles by dipping and pouring (immersion operations)	13	Liquids	0.14	0.54	0.19	0.47

List of derived RCRs

Exposure details	CES	PROC Code	ES 6- 90 th exposure concentrations (mg/m ³)	Leading toxic end point / Critical effect	DNEL (mg/m ³)	Risk characterisation ratio
Acute-local effects	CES 2	PROC 1	9.3×10^{-9}	Respiratory irritation and corrositivity	0.1	9.3×10^{-8}
	CES 3	PROC 2	9.2×10^{-8}	Respiratory irritation and corrositivity	0.1	9.2×10^{-7}
	CES 4	PROC 8b	1.2×10^{-4}	Respiratory irritation and corrositivity	0.1	1.2×10^{-3}
	CES 5	PROC 9	3.2×10^{-3}	Respiratory irritation and corrositivity	0.1	3.2×10^{-2}
	CES 6	PROC 13	5.4×10^{-1} (3×10^{-2})*	Respiratory irritation and corrositivity	0.1	5.4×10^{-0} (3×10^{-1})*
Long-term – local effects	CES 2	PROC 1	9.4×10^{-9}	Respiratory irritation and corrositivity	0.05	1.9×10^{-7}
	CES 3	PROC 2	9.2×10^{-8}	Respiratory irritation and corrositivity	0.05	1.8×10^{-6}
	CES 4	PROC 8b	4.8×10^{-6}	Respiratory irritation and corrositivity	0.05	9.6×10^{-5}
	CES 5	PROC 9	2.8×10^{-3}	Respiratory irritation and corrositivity	0.05	5.6×10^{-2}
	CES 6	PROC 13	4.7×10^{-1} (2×10^{-2})*	Respiratory irritation and corrositivity	0.05	9.4×10^{-0} (4×10^{-1})*

* Assumes Respiratory Protective Equipment (95% reduction) is worn

Assessment of dermal risk

During the processes that will be carried out for all the exposure scenarios associated with production and use of sulphuric acid a potential risk may arise if sulphuric acid comes into contact with human skin. This is due to the nature of sulphuric acid and its ability to cause chemical burns. As this effect is considered to be related to the corrosivity of sulphuric acid a threshold DNEL cannot be established for this risk and so measures to control this risk should be assessed in a qualitative manner. Though this risk is most pertinent when workers may come into contact with concentrated sulphuric acid in an industrial setting the operational conditions (OCs) and risk management measures (RMMs) used to control and manage the risk of dermal contact events may be equally applicable across all the exposure scenarios.

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

In the industrial setting an acute risk of dermal burns from exposure to sulphuric acid in its concentrated form (or its dilute form) exists due to possible splashing of the liquid acid. This risk would be highest at times of transfer to tankers, filling of barrels and filling of small vessels etc. Though these events are considered unlikely due to the high degree of system closure and control the risk is still protected against in order to eliminate any possible routes of exposure.

The risk of dermal contact is reduced due to the OC's in place. The specialised nature of the systems and the degree of closure associated with them ensure the potential for dermal contact is minimised. All pipes and transfers lines are closed and sealed in order to reduce possible exposure to leaks or splashes, as are the reactors to reduce possible emissions. During times of transfer to/from road tankers gas displacement lines and special connecting systems are in place to reduce the levels of gaseous emissions that could deposit to surfaces including human skin. Specialised tanker coupling/uncoupling systems and targeted purging systems may be used in certain circumstances where large volumes and high concentrations are required. Training and certification ensures the workers understand the correct procedures for use of these specialized systems so that the measures in place to reduce emissions are conducted so proper function can be maintained.

In addition to the measures in place to reduce system emissions, workers are completely separated from the site of operation. Workers are generally housed in areas segregated from the main emission sources and time spent on tasks which require close proximity to the emission sources can be minimised effectively. Separate control rooms, screens and outdoor reactor units help to keep workers away from any potential sources of exposure. Emergency measures (and training on procedures and safe work practice) are in place in the industrial setting to ensure that any unforeseen events are safely dealt with in the case that they do arise. These measures range from procedural policies which are in place to guide workers in the proper response in the case of splashes or spills to dedicated equipment (such as emergency showers or spill clean-up kits) which can be used to minimise any effects should unforeseen exposure arise.

Personal protective equipment (PPE) should be supplied to any personnel who may be working in areas where potential emission sources (such as transfer pipes) are located. Suitable PPE that should be used to prevent dermal contact for workers would be acid resistant clothing, helmets, gloves, goggles and boots. The PPE should be properly maintained and certified and should be replaced when required. These measures combined will effectively function to ensure three aspects of safe use. These are, firstly, reduction of potential emissions with specialised systems. Secondly reduction of the potential for exposure of workers by means such as segregation and training and thirdly physical protection of the worker with the use of correct PPE. With the combination of these measures it is considered that the risk of chemical burns to workers is adequately managed.

As mentioned above when the concentration of the sulphuric acid decreases so does the potential for chemical burns to human skin. However the same measures are still in place to ensure that workers, professionals and consumers are protected from risk.

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

6.4

Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environmental releases:

In order to work within the boundaries of the ES the following conditions should be met:

- Emission to air after scrubbing less than 3,160 kg per day
- No emission to the municipal STP
- The industrial WWTP sludge should not be spread to soil
- Wastewater should be fully neutralized
- Exhaust gases from the intermediate use are treated with scrubbers.
- Sufficient LEV and vapour recovery systems are in place to reduce exposure when open electrolyte baths are in place..
- Measured emissions should be confirmed to be less than the relevant PNECs in section 3

Worker exposure:

In order to work within the boundaries of the ES the following conditions should be met:

- Reactors and pipelines should be sealed systems
- Workers should wear protective gloves, goggles, overalls and boots at all times in the production and transfer area
- Workers should be segregated from the area of use.
- Any measured exposure should be confirmed to be less than the relevant DNELs in section 3 above.

6.5

Additional good practice advice beyond the REACH CSA.

- Do not eat, drink or smoke when working with sulphuric acid.
- Always wash hands and exposed skin thoroughly after using sulphuric acid or any surfaces/machinery that may have come into contact with sulphuric acid.
- Workers should be suitably trained in all safety procedures and in the safe handling of sulphuric acid to prevent risk of exposure.
- All PPE should be properly maintained and stored in an appropriate way so as not to damage its integrity. Workers should be correctly trained in its use.
- Procedural and safety compliance should be routinely assessed by management
- Machinery should be regularly maintained and checked for proper function
- Efficacy of all emission RMMs and waste treatment procedures should be routinely assessed and confirmed to be functioning correctly

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

7	Exposure Scenario 7: Use of Sulphuric Acid in gas purification, scrubbing, flue gas scrubbing etching.
	<p>Use of Sulphuric Acid in gas purification, scrubbing, flue gas scrubbing etching.</p> <p>Processes Covered:</p> <p>Environmental Releases</p> <p>ERC07: Industrial use of substances in closed systems</p> <p>Worker Processes</p> <p>PROC01: Use in closed process, no likelihood of exposure PROC02: Use in closed, continuous process with occasional controlled exposure (including sampling and maintenance) PROC08b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities</p> <p>Produce Category</p> <p>PC20: Products such as ph-regulators, flocculants, precipitants, neutralization agents</p> <p>Sulphuric acid as may be used as an agent for gas purification. This includes gas scrubbing and flue gas scrubbing. The main applications of this would be in purification of gas from coke ovens and in the purification and drying of industrial gases generated from the manufacture of other substances.</p> <p>Due to the corrosive nature of sulphuric acid, specially trained workers and systems are employed.</p>
	<p>Contributing Environmental Scenario: CES1 Environmental exposure arising due to the use of sulphuric acid in gas purification, scrubbing, flue gas scrubbing etching. (ERC 7).</p>
	<p>Contributing Worker Scenarios: CES 2: Worker exposure arising due to use in closed processes with no likelihood of exposure (PROC 1), CES 3: worker exposure arising due to use in closed processes with some potential for exposure (PROC 2), and CES 4: worker exposure arising due transfer of substances to large vessels at dedicated facilities (PROC 8b).</p>
7.1	Controlling environmental exposure for ES 7
	<p>ES7: Contributing exposure scenario (CES) 1 Environmental exposure arising due to use of sulphuric acid in gas purification, scrubbing, flue gas scrubbing etching.</p>
	<p>Section 2.1 describes the environmental releases that may occur during the use of sulphuric acid in gas purification, scrubbing, flue gas scrubbing etching. These releases may potentially occur due to emission to wastewater or through emission to the atmosphere. Environmental emissions are limited by designated waste treatment process designed to limit environmental exposure to all relevant</p>

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

compartments. Waste gas emissions are scrubbed and may also then be diverted to the wastewater stream. This significantly lessens the possible emission by atmospheric deposition to soil or surface waters.

Liquid wastes are treated (neutralization to neutral pH) prior to emission to remove any sulphuric acid in the waste water. Sludge from the waste water treatment plant is sent for incineration or landfill and is not used for agricultural spreading. This precludes any contamination of soil by sludge spreading. Waste water treatment is usually carried out by neutralisation followed by flocculation or decantation.

In addition to these risk management measures, direct emission of de-contaminated sulphuric acid to surface water exists where around 560 tonnes of sulphuric acid per year is emitted to a large brackish river with a large acid buffering capacity and a very high flow rate.

Use of sulphuric acid in gas purification, scrubbing, flue gas scrubbing etching is generally continuous with constant production and use. Facilities generally use up to 30,000 tonnes per year which is considered to be a worst case assumption for a single site in Europe, with reports of 1.5tonnes emitted per day in some sites.

Product characteristics

The produced substance is a liquid with purity greater than 90%. The substance is colourless, odourless inorganic liquid which is miscible with water. Sulphuric acid is not flammable and is non-explosive.

Amounts used

Facilities generally use up to 30,000 tonnes per year which is considered to be a worst case assumption for a single site in Europe, with reports of 1.5tonnes emitted per day in some sites.

Frequency and duration of use

Continuous production and release.

Environmental factors influenced by risk management

On site WWTP with the capacity for complete neutralization. Emissions to air may be as much as 5,000 kg/d but are generally much less. Exhaust gases may be treated by scrubbers and filtered.

Other operational conditions affecting environmental exposure

The use of sulphuric acid in facilities in the process of gas purification, scrubbing and flue gas scrubbing takes place in a highly specialized, high integrity, contained indoor facilities with emissions to water being fully neutralized before release. Reactors and transfer pipelines are closed systems, with insulation if required.

Technical conditions and measures at process level (source) to prevent release

As mentioned above reactors and pipelines are fully sealed and insulated if necessary. Both production and sampling are carried out in dedicated facilities.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Sulphuric acid used in the process of gas purification, scrubbing and flue gas scrubbing on a large scale generally occurs on major chemical sites which will have dedicated effluent treatment facilities, involving both chemical and biological treatment, coping with many chemical substances. As such any emission to wastewater will be almost instantly hydrolysed before even reaching the STP.

Neutralisation procedures are in place to ensure that the pH of any downstream biological treatment or final receiving waters is not affected. Spent acid solutions are neutralized to circumneutral pH prior to discharge. All waste waters should be treated in this manner.

In some cases, emissions are made to a large brackish river with a considerable buffering capacity and a very high flow rate.

Organizational measures to prevent/limit releases from site

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Workers are fully trained in order to prevent accidental release.	
Conditions and measures related to municipal STP	
Waste waters are generally treated on site by chemical and/or biological methods before release to the municipal STP or to the environment.	
Conditions and measures related to external treatment of waste for disposal	
All sludge from the onsite WWTP is collected and incinerated or sent to landfill for disposal. Waste from any scrubbers should be directed to waste water stream for further treatment. There is no further generation of solid waste.	
Conditions and measures related to external recovery of waste	
There is no envisaged external recovery of waste.	
7.2	Controlling worker exposure for ES 7
<p>ES 7: CES 2: Worker exposure arising due to use in closed processes with no likelihood of exposure (PROC 1), CES 3: worker exposure arising due to use in closed processes with some potential for exposure (PROC 2) and CES 4: worker exposure arising due transfer of substances to large vessels at dedicated facilities (PROC 8b).</p> <p>During the use of sulphuric acid in the process of gas purification, scrubbing and flue gas scrubbing, controlled systems are in place to reduce the potential for worker exposure in all cases.</p> <p>Loading and unloading of tankers with sulphuric acid to be used as a gas purifier is usually performed in semi-closed conditions. Workers wear protective clothing (face/eye protection, helmet, anti-acid gloves boots and protective overall). A safety shower is required nearby in case of accidental spillage. Gas displacement lines are also used if filling of road tankers takes place under cover.</p>	
Product characteristics	
The produced substance is a liquid with purity greater than 90%. The substance is colourless, odourless inorganic liquid which is miscible with water. Sulphuric acid is not flammable and is non-explosive.	
Amounts used	
Facilities generally use up to 30,000 tonnes per year, considered to be 365 days, which is considered to be a worst case assumption for a single site in Europe, with reports of 1.5tonnes emitted per day in some sites.	
Frequency and duration of use exposure	
Workers perform standard shifts of 8 hours per day and have standard working years of 220 days per year. However, some tasks, such as sampling and maintenance are expected to be short duration tasks.	
Human factors not influenced by risk management	
Respiration volumes under conditions of use 10m ³ /d (default value for a worker breathing for an 8h work day in RIP 3.2).	
Other given operational conditions affecting worker exposure	
Both production and sampling are carried out at dedicated facilities with vapour recovery systems in place where required. Transfer operations are carried out in controlled systems with dedicated machinery. The handling of sulphuric acid involves special equipment and controlled systems with little or no potential for exposure.	
Technical conditions and measures at process level (source) to prevent release	
Reactors and pipes are sealed systems. Loss from reactor and pipes is monitored.	
Technical conditions to control dispersion from source towards worker	
Any gas displaced from containers is conducted via pipeline to be processed (removed and scrubbed and	

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

/or filtered) in the areas where sulphuric acid is used in electrolytic processes. During handling when transferring drum filling, special equipment and controlled systems with little or no potential for exposure are used to prevent losses occurring.

Organizational measures to prevent/limit release

Workers involved in sampling and transfer of materials to road tankers are trained in the procedures and protective equipment is intended to cope with the worst case scenario, in order to minimise exposure and risks. Workers are generally separated from the purification or scrubbing systems with no direct contact to the installations housing the material.

Conditions and measures related to personal protection, hygiene and health.

Gloves, goggles, chemical resistant overalls and work boots are worn by all operators in the facility to prevent dermal exposure.

7.3 Exposure estimation and reference to its source

Environmental Exposure

For the tier 1 risk characterisation PECs derived using the ERC defaults are not assessed below as the PECs are considered unrealistically high and would lead to a failing risk assessment in any case. For the tier 2 risk characterisation the PECs calculated by the EUSES environmental model with refined inputs taking into account the emission RMMs as discussed in section 2.1 above are used to control environmental releases are used for the assessment.

Information for contributing exposure scenario 1:

List of exposure concentrations

Compartment	PEC	Justification
Freshwater (in mg/L)	8.86×10^{-5}	
Marine water (in mg/L)	1.28×10^{-5}	
Intermittent releases to water (in mg/L)	NA	Intermittent release not relevant
Freshwater sediment (in mg/kg)	7.13×10^{-5}	
Marine sediment (in mg/kg)	1.03×10^{-5}	
Agricultural soil (averaged over 30 days (in mg/kg)	5.91×10^{-3}	
Groundwater (in mg/L)	0.0437	
Annual average PEC in air, total (mg/m ³)	1.14	

The following RCRs were derived taking into account derived PNEC values

Compartments	PEC mg/L	PNEC mg/L	PEC/PNEC	Comments
Tier 2 Freshwater	8.86×10^{-5}	0.0025	0.0352	Safe use demonstrated in tier 2
Tier 2 Sediment	7.13×10^{-5}	0.002 (EPM)	0.0355	Safe use demonstrated in tier 2

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Tier 2 Marine sediment	1.03×10^{-5}	0.002 (EPM)	0.005	Safe use demonstrated in tier 2
Tier 2 Marine	1.28×10^{-5}	0.00025	0.048	Safe use demonstrated in tier 2

* EPM = equilibrium partitioning method

Worker exposure

The Advanced REACH tool (ART) was used to estimate worker exposure as it was considered that the ECETOC model cannot estimate in a satisfactory manner the effects of the stringent containment and segregation practices which are in place to deal with sulphuric acid production and to limit exposure.

In the characterisation of the human health risks posed by acute/short term and long-term inhalation exposures to sulphuric acid (or formed sulphuric acid) associated with ES 7, the 90th percentile (e.g. worst case) inhalation exposure concentrations derived using the ART model for relevant PROC codes were compared with the DNEL value for acute local respiratory effects and the DNEL value for long-term local respiratory effects respectively. The results of the risk characterisation are shown in the table below.

The predicted acute/short-term and long-term inhalation exposure concentrations derived using the ART model were not found to exceed the DNEL value for acute local respiratory effects or the DNEL value for long-term local respiratory effects respectively for any of the processes associated with ES 7. On the basis of the assumptions made in the exposure assessment and this risk characterisation, it can be concluded that inhalation exposures to sulphuric acid that may potentially arise during processes associated with ES 7 do not pose an unacceptable health risk to workers.

Information for worker contributing scenarios 2, 3 and 4:

List of inputs used in the ART assessment

	PROC	Parameters/ assumptions
Exposure duration	All	480 mins
Product type	All	Liquid (medium viscosity – like oil)
Process temperature	All	Hot processes (50-150oC)
Vapour pressure	All	6 Pa – Substance is considered to be low-volatile, exposure to mists is estimated
Liquid weight fraction	All	0.98
Primary emission source proximity	PROC 1,2	Primary emission source is not located in the breathing zone of the worker - the assessment for this activity involves a primary far-field emission source only (workers are in a control room)
	PROC 8b	Primary emission source located in the breathing zone of the workers (i.e. Within 1 metre)
Activity class	All	Transfer of liquid products
Containment	PROC 1,2,	Handling reduces contact between product and adjacent air
	PROC 8b	n/a
Localised controls	PROC 1,8b,	Vapour recovery systems; LEV

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

	PROC 2	Vapour recovery
Segregation	PROC 1,2	Complete segregation of workers in separate control room
Fugitive emission source	PROC 1,8b	Process fully enclosed – not breached for sampling
	PROC 2	Not fully enclosed – effective housekeeping practices in place.
Dispersion	PROC 1,2,8b	Outdoors not close to buildings

List of derived exposure concentrations

Description of activity	PROC	Physical state of material	Short-term Concentrations		Long-term Concentration	
			Estimated Exposure (mg/m ³) 50 th percentile value	90 th percentile value	Estimated Exposure (mg/m ³) 50 th percentile value	90 th percentile value
Use in closed process, no likelihood of exposure	1	Liquid	8.20×10^{-10}	9.30×10^{-09}	3.60×10^{-09}	9.40×10^{-09}
Use in closed, continuous process with occasional controlled exposure (including sampling and maintenance)	2	Liquid	8.20×10^{-09}	9.20×10^{-08}	3.60×10^{-08}	9.20×10^{-08}
Loading/transfer of sulphuric acid to/from large vessels/containers at dedicated site	8b	Liquid	1.10×10^{-05}	1.20×10^{-04}	4.80×10^{-05}	4.80×10^{-06}

List of derived RCRs

Exposure details	CES	PROC Code	ES 7- 90 th exposure concentrations (mg/m ³)	Leading toxic end point / Critical effect	DNEL (mg/m ³)	Risk characterisation ratio
Acute-local effects	CES 2	PROC 1	9.3×10^{-9}	Respiratory irritation and corrositivity	0.1	9.3×10^{-8}
	CES 3	PROC 2	9.2×10^{-8}	Respiratory irritation and corrositivity	0.1	9.2×10^{-7}
	CES 4	PROC 8b	1.2×10^{-4}	Respiratory irritation and corrositivity	0.1	1.2×10^{-3}
Long-term – local effects	CES 2	PROC 1	9.4×10^{-9}	Respiratory irritation and corrositivity	0.05	1.88×10^{-7}
	CES 3	PROC 2	9.2×10^{-8}	Respiratory irritation and corrositivity	0.05	1.84×10^{-6}
	CES 4	PROC 8b	4.8×10^{-6}	Respiratory irritation and corrositivity	0.05	9.6×10^{-5}

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Assessment of dermal risk

During the processes that will be carried out for all the exposure scenarios associated with production and use of sulphuric acid a potential risk may arise if sulphuric acid comes into contact with human skin. This is due to the nature of sulphuric acid and its ability to cause chemical burns. As this effect is considered to be related to the corrosivity of sulphuric acid a threshold DNEL cannot be established for this risk and so measures to control this risk should be assessed in a qualitative manner. Though this risk is most pertinent when workers may come into contact with concentrated sulphuric acid in an industrial setting the operational conditions (OCs) and risk management measures (RMMs) used to control and manage the risk of dermal contact events may be equally applicable across all the exposure scenarios.

In the industrial setting an acute risk of dermal burns from exposure to sulphuric acid in its concentrated form (or its dilute form) exists due to possible splashing of the liquid acid. This risk would be highest at times of transfer to tankers, filling of barrels and filling of small vessels etc. Though these events are considered unlikely due to the high degree of system closure and control the risk is still protected against in order to eliminate any possible routes of exposure.

The risk of dermal contact is reduced due to the OC's in place. The specialised nature of the systems and the degree of closure associated with them ensure the potential for dermal contact is minimised. All pipes and transfers lines are closed and sealed in order to reduce possible exposure to leaks or splashes, as are the reactors to reduce possible emissions. During times of transfer to/from road tankers gas displacement lines and special connecting systems are in place to reduce the levels of gaseous emissions that could deposit to surfaces including human skin. Specialised tanker coupling/uncoupling systems and targeted purging systems may be used in certain circumstances where large volumes and high concentrations are required. Training and certification ensures the workers understand the correct procedures for use of these specialized systems so that the measures in place to reduce emissions are conducted so proper function can be maintained.

In addition to the measures in place to reduce system emissions, workers are completely separated from the site of operation. Workers are generally housed in areas segregated from the main emission sources and time spent on tasks which require close proximity to the emission sources can be minimised effectively. Separate control rooms, screens and outdoor reactor units help to keep workers away from any potential sources of exposure. Emergency measures (and training on procedures and safe work practice) are in place in the industrial setting to ensure that any unforeseen events are safely dealt with in the case that they do arise. These measures range from procedural policies which are in place to guide workers in the proper response in the case of splashes or spills to dedicated equipment (such as emergency showers or spill clean-up kits) which can be used to minimise any effects should unforeseen exposure arise.

Personal protective equipment (PPE) should be supplied to any personnel who may be working in areas where potential emission sources (such as transfer pipes) are located. Suitable PPE that should be used to prevent dermal contact for workers would be acid resistant clothing, helmets, gloves, goggles and boots. The PPE should be properly maintained and certified and should be replaced when required. These measures combined will effectively function to ensure three aspects of safe use. These are, firstly, reduction of potential emissions with specialised systems. Secondly reduction of the potential for

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

exposure of workers by means such as segregation and training and thirdly physical protection of the worker with the use of correct PPE. With the combination of these measures it is considered that the risk of chemical burns to workers is adequately managed.

As mentioned above when the concentration of the sulphuric acid decreases so does the potential for chemical burns to human skin. However the same measures are still in place to ensure that workers, professionals and consumers are protected from risk.

7.4

Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environmental releases:

In order to work within the boundaries of the ES the following conditions should be met:

- Emission to air after scrubbing less than 5,000 kg per day
- No emission to the municipal STP
- The industrial WWTP sludge should not be spread to soil
- Wastewater should be fully neutralized
- Exhaust gases from use are treated with scrubbers.
- Sufficient vapour recovery systems are in place to reduce exposure.
- In some instances, emissions are released to large brackish lakes with a very high acid buffering capacity and high flow rate.
- Measured emissions should be confirmed to be less than the relevant PNECs in section 3.

Worker exposure:

In order to work within the boundaries of the ES the following conditions should be met:

- Reactors and pipelines should be sealed systems
- Workers should wear protective gloves, goggles, overalls and boots at all times in the production and transfer area
- Workers should be segregated from the area of use.
- Any measured exposure should be confirmed to be less than the relevant DNELs in section 3 above.

7.5

Additional good practice advice beyond the REACH CSA.

- Do not eat, drink or smoke when working with sulphuric acid.
- Always wash hands and exposed skin thoroughly after using sulphuric acid or any surfaces/machinery that may have come into contact with sulphuric acid.
- Workers should be suitably trained in all safety procedures and in the safe handling of sulphuric acid to prevent risk of exposure.
- All PPE should be properly maintained and stored in an appropriate way so as not to damage its integrity. Workers should be correctly trained in its use.
- Procedural and safety compliance should be routinely assessed by management

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

- Machinery should be regularly maintained and checked for proper function
- Efficacy of all emission RMMs and waste treatment procedures should be routinely assessed and confirmed to be functioning correctly

8 Exposure Scenario 8: Use of Sulphuric Acid in production of lead acid batteries containing sulphuric acid.

Use of Sulphuric Acid in production of lead acid batteries containing sulphuric acid.

Processes Covered:

Environmental Releases

ERC02: Formulation of preparations

ERC05: Industrial use resulting in inclusion into or onto a matrix

Worker Processes

PROC02: Use in closed, continuous process with occasional controlled exposure (including sampling and maintenance)

PROC03: Use in closed batch process (synthesis or formulation)

PROC04: Use in batch and other process (synthesis) where opportunity for exposure arises

PROC09: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

Produce Category

PC0: Other [UNC code E10100 (Electrolytes)]

Sulphuric acid is used in the production of the liquid electrolyte for batteries. The electrolyte solution generally contains sulphuric acid at a concentration of 25% to 40%. The electrolyte solution is added to the batteries and then sealed within them.

Because of the processes involved in battery manufacturing (and the nature of sulphuric acid and the produced gases), specially trained workers and systems are employed.

Contributing Environmental Scenario: CES1 Environmental exposure arising due to the use of sulphuric acid in the production of lead acid batteries containing sulphuric acid. (ERC 02 and ERC 05).

Contributing Worker Scenarios: CES 2: worker exposure arising due to use in closed processes with some potential for exposure (PROC 2), CES 3: worker exposure arising due to use in batch processes with some potential for exposure (PROC 3 and PROC 4), and CES 4: worker exposure arising due transfer of formulations or preparations to small containers (PROC 9).

8.1 Controlling environmental exposure for ES 8

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

ES8: Contributing exposure scenario (CES) 1 Environmental exposure arising due to use of sulphuric acid in production of lead acid batteries containing sulphuric acid.

Section 2.1 describes the environmental releases that may occur during the use of sulphuric acid in production of lead acid batteries containing sulphuric acid. These releases may potentially occur due to emission to wastewater or through emission to the atmosphere. Environmental emissions are limited by designated waste treatment process designed to limit environmental exposure to all relevant compartments. Waste gas emissions are scrubbed and may also then be diverted to the wastewater stream. This significantly lessens the possible emission by atmospheric deposition to soil or surface waters.

Liquid wastes are treated (neutralization to neutral pH) prior to emission to remove any sulphuric acid in the waste water. Sludge from the waste water treatment plant is sent for incineration or landfill and is not used for agricultural spreading. This precludes any contamination of soil by sludge spreading. Waste water treatment is usually carried out by neutralisation followed by flocculation or decantation.

Use of sulphuric acid in the production of lead acid batteries containing sulphuric acid is generally continuous with constant production and use. Facilities generally use up to 2,500 tonnes per year which is considered to be a worst case assumption for a single site in Europe, operating 365 days per year.

Product characteristics

The produced substance is a liquid with purity greater than 90%. The substance is colourless, odourless inorganic liquid which is miscible with water. Sulphuric acid is not flammable and is non-explosive.

Amounts used

Facilities generally use up to 2,500 tonnes per year which is considered to be a worst case assumption for a single site in Europe, operating 365 days per year.

Frequency and duration of use

Continuous production and release.

Environmental factors influenced by risk management

On site WWTP with the capacity for complete neutralization. Emissions to air may be as much as 12,500 kg/d but are generally much less. Exhaust gases may be treated by scrubbers and filtered.

Other operational conditions affecting environmental exposure

The use of sulphuric acid in the production of lead acid batteries containing sulphuric acid takes place in a highly specialized, high integrity, contained indoor facilities with emissions to water being fully neutralized before release. Reactors and transfer pipelines are closed systems, with insulation if required.

Technical conditions and measures at process level (source) to prevent release

As mentioned above reactors and pipelines are fully sealed and insulated if necessary. Both production and sampling are carried out in dedicated, contained facilities.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Sulphuric acid used in the production of lead acid batteries containing sulphuric acid on a large scale generally occurs on major chemical sites which will have dedicated effluent treatment facilities, involving both chemical and biological treatment, coping with many chemical substances. As such any emission to wastewater will be almost instantly hydrolysed before even reaching the STP.

Neutralisation procedures are in place to ensure that the pH of any downstream biological treatment or final receiving waters is not affected. All waste waters should be treated in this manner.

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Organizational measures to prevent/limit releases from site	
Workers are fully trained in order to prevent accidental release.	
Conditions and measures related to municipal STP	
Waste waters are generally treated on site by chemical and/or biological methods before release to the municipal STP or to the environment.	
Conditions and measures related to external treatment of waste for disposal	
All sludge from the onsite WWTP is collected and incinerated or sent to landfill for disposal. Waste from any scrubbers should be directed to waste water stream for further treatment. There is no further generation of solid waste.	
Conditions and measures related to external recovery of waste	
There is no envisaged external recovery of waste.	
8.2	Controlling worker exposure for ES 8
<p>ES 8: CES 2: worker exposure arising due to use in closed processes with some potential for exposure (PROC 2), CES 3: worker exposure arising due to use in batch processes with some potential for exposure (PROC 3 and PROC 4), and CES 4: worker exposure arising due transfer of formulations or preparations to small containers (PROC 9).</p> <p>During the use of sulphuric acid in the production of lead acid batteries containing sulphuric acid, controlled systems are in place to reduce the potential for worker exposure in all cases.</p> <p>Loading and unloading of tankers with sulphuric acid for use in battery manufacture is usually performed in the open air. Workers wear protective clothing (face/eye protection, helmet, anti-acid gloves boots and protective overall). Where required, respiratory protection is also provided. A safety shower is required nearby in case of accidental spillage. Gas displacement lines are also used if filling of road tankers takes place under cover. Filling of the batteries would generally be indoors with suitable LEV and worker protection measures in place.</p>	
Product characteristics	
The produced substance is a liquid with purity greater than 90%. The substance is colourless, odourless inorganic liquid which is miscible with water. Sulphuric acid is not flammable and is non-explosive.	
Amounts used	
Facilities generally use up to 2,500 tonnes per year which is considered to be a worst case assumption for a single site in Europe, operating 365 days per year.	
Frequency and duration of use exposure	
Workers perform standard shifts of 8 hours per day and have standard working years of 220 days per year. However, some tasks, such as sampling and maintenance are expected to be short duration tasks.	
Human factors not influenced by risk management	
Respiration volumes under conditions of use 10m ³ /d (default value for a worker breathing for an 8h work day in RIP 3.2).	
Other given operational conditions affecting worker exposure	
Both production and sampling are carried out at dedicated facilities with LEV and vapour recovery systems in place where required. Transfer operations are carried out in controlled systems with dedicated machinery. The handling of sulphuric acid involves special equipment and controlled systems with little or no potential for exposure.	

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Technical conditions and measures at process level (source) to prevent release
Reactors and pipes are sealed systems. Loss from reactor and pipes is monitored.
Technical conditions to control dispersion from source towards worker
Any gas displaced from containers is conducted via pipeline to be processed (removed and scrubbed and /or filtered) in the areas where sulphuric acid is used in electrolytic processes. During handling when transferring drum filling, special equipment and controlled systems with little or no potential for exposure are used to prevent losses occurring.
Organizational measures to prevent/limit release
Workers involved in sampling and transfer of materials to road tankers are trained in the procedures and protective equipment is intended to cope with the worst case scenario, in order to minimise exposure and risks. Workers are generally separated from the machinery associated with sulphuric acid, with no direct contact to the installations housing the material. During the short duration tasks where exposure is possible, suitable PPE is worn.
Conditions and measures related to personal protection, hygiene and health.
Gloves, goggles, chemical resistant overalls and work boots are worn by all operators in the facility to prevent dermal exposure. Respiratory equipment may also be worn if necessary.

8.3	Exposure estimation and reference to its source
------------	--

Environmental Exposure

For the tier 1 risk characterisation PECs derived using the ERC defaults are not assessed below as the PECs are considered unrealistically high and would lead to a failing risk assessment in any case. For the tier 2 risk characterisation the PECs calculated by the EUSES environmental model with refined inputs taking into account the emission RMMs as discussed in section 2.1 above are used to control environmental releases are used for the assessment.

Information for contributing exposure scenario 1:

List of exposure concentrations

Compartment	PEC	Justification
ERC 2 Freshwater (in mg/L)	3.69×10^{-5}	
ERC 2 Marine water (in mg/L)	5.35×10^{-6}	
ERC 2 Intermittent releases to water (in mg/L)	NA	Intermittent release not relevant
ERC 2 Freshwater sediment (in mg/kg)	2.97×10^{-5}	
ERC 2 Marine sediment (in mg/kg)	4.3×10^{-6}	
ERC 2 Agricultural soil (averaged over 30 days (in mg/kg)	2.46×10^{-4}	
ERC 2 Groundwater (in mg/L)	1.82×10^{-3}	
ERC 2 Annual average PEC in air, total (mg/m ³)	0.0476	
ERC 5 Freshwater (in mg/L)	7.38×10^{-5}	
ERC 5 Marine water (in mg/L)	1.07×10^{-5}	10-fold dilution by receiving waters.
ERC 5 Intermittent releases to water (in mg/L)	NA	Intermittent release not relevant

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

ERC 5 Freshwater sediment (in mg/kg)	5.94×10^{-5}	
ERC 5 Marine sediment (in mg/kg)	8.8×10^{-6}	
ERC 5 Agricultural soil (averaged over 30 days (in mg/kg)	4.92×10^{-3}	
ERC 5 Groundwater (in mg/L)	0.0364	
ERC 5 Annual average PEC in air, total (mg/m ³)	0.952	

The following RCRs were derived taking into account derived PNEC values

Compartments	PEC mg/L	PNEC mg/L	PEC/PNEC	Comments
ERC 2 Tier 2 Freshwater	3.69×10^{-5}	0.0025	0.0147	Safe use demonstrated in tier 2
ERC 2 Tier 2 Sediment	2.97×10^{-5}	0.002 (EPM)	0.0148	Safe use demonstrated in tier 2
ERC 2 Tier 2 Marine sediment	4.3×10^{-6}	0.002 (EPM)	0.0021	Safe use demonstrated in tier 2
ERC 2 Tier 2 Marine	5.35×10^{-6}	0.00025	0.0212	Safe use demonstrated in tier 2
ERC 5Tier 2 Freshwater	7.38×10^{-5}	0.0025	0.0295	Safe use demonstrated in tier 2
ERC 5Tier 2 Sediment	5.94×10^{-5}	0.002 (EPM)	0.029	Safe use demonstrated in tier 2
ERC 5Tier 2 Marine sediment	8.8×10^{-6}	0.002 (EPM)	0.0044	Safe use demonstrated in tier 2
ERC 5Tier 2 Marine	1.07×10^{-5}	0.00025	0.042	Safe use demonstrated in tier 2

* EPM = equilibrium partitioning method

Worker exposure

The Advanced REACH tool (ART) was used to estimate worker exposure as it was considered that the ECETOC model cannot estimate in a satisfactory manner the effects of the stringent containment and segregation practices which are in place to deal with sulphuric acid production and to limit exposure.

In the characterisation of the human health risks posed by acute/short term and long-term inhalation exposures to sulphuric acid (or formed sulphuric acid) associated with ES 8, the 90th percentile (e.g. worst case) inhalation exposure concentrations derived using the ART model for relevant PROC codes were compared with the DNEL value for acute local respiratory effects and the DNEL value for long-term local respiratory effects respectively. The results of the risk characterisation are shown in the table below.

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

The predicted acute/short-term and long-term inhalation exposure concentrations derived using the ART model were not found to exceed the DNEL value for acute local respiratory effects or the DNEL value for long-term local respiratory effects respectively for any of the processes associated with ES 8. On the basis of the assumptions made in the exposure assessment and this risk characterisation, it can be concluded that inhalation exposures to sulphuric acid that may potentially arise during processes associated with ES 8 do not pose an unacceptable health risk to workers.

Information for worker contributing scenarios 2, 3 and 4:

List of inputs used in the ART assessment

	PROC	Parameters/ assumptions
Exposure duration	All	480 mins
Product type	PROC 2,3	Liquid (medium viscosity – like oil)
	PROC 4,9	Liquid (low viscosity – like water)
Process temperature	All	Room temperature (15-25oC)
Vapour pressure	All	Substance is considered to be low volatile, exposure to mists is estimated
Liquid weight fraction	PROC 2,3	0.98
	PROC 4,9	0.25
Primary emission source proximity	All	Primary emission source located in the breathing zone of the workers (i.e. Within 1 metre)
Activity class	All	Transfer of liquid products
Containment	All	Handling reduces contact between product and adjacent air
Localised controls	All	LEV
Fugitive emission source	PROC 2	Process fully enclosed – not breached for sampling
	PROC 3,4,9	Not fully enclosed – effective housekeeping practices in place.
Dispersion	All	Indoors, any sized room, only good natural ventilation

List of derived exposure concentrations

Description of activity	PROC	Physical state of material	Short-term Concentrations		Long-term Concentration	
			Estimated Exposure (mg/m3) 50 th percentile value	90 th percentile value	Estimated Exposure (mg/m3) 50 th percentile value	90 th percentile value
Use in closed, continuous process with occasional controlled exposure (including sampling and maintenance)	2	Liquid	4.00×10^{-04}	1.60×10^{-03}	5.50×10^{-04}	1.40×10^{-03}
Use in closed batch process (synthesis or formulation)	3	Liquid	0.0041	0.016	0.0056	0.014
Use in batch and other process (synthesis) where opportunity for exposure arises	4	Liquid	0.00034	0.0014	0.00048	0.0012
Loading/transfer (small containers): Filling lead-acid	9	Liquid	0.00034	0.0014	0.00048	0.0012

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

batteries with sulphuric acid electrolyte, diluted 25%

List of derived RCRs

Exposure details	CES	PROC Code	ES 8- 90 th exposure concentrations (mg/m3)	Leading toxic end point / Critical effect	DNEL (mg/m3)	Risk characterisation ratio
Acute-local effects	CES 2	PROC 2	1.6×10^{-3}	Respiratory irritation and corrositivity	0.1	1.6×10^{-2}
	CES 3	PROC 3	1.6×10^{-2}	Respiratory irritation and corrositivity	0.1	1.6×10^{-1}
		PROC 4	1.4×10^{-3}	Respiratory irritation and corrositivity	0.1	1.4×10^{-2}
	CES 4	PROC 9	1.4×10^{-3}	Respiratory irritation and corrositivity	0.1	1.4×10^{-2}
Long-term – local effects	CES 2	PROC 2	1.4×10^{-3}	Respiratory irritation and corrositivity	0.05	2.8×10^{-2}
	CES 3	PROC 3	1.4×10^{-2}	Respiratory irritation and corrositivity	0.05	2.8×10^{-1}
		PROC 4	1.2×10^{-3}	Respiratory irritation and corrositivity	0.05	2.4×10^{-2}
	CES 4	PROC 9	1.2×10^{-3}	Respiratory irritation and corrositivity	0.05	2.4×10^{-2}

Assessment of dermal risk

During the processes that will be carried out for all the exposure scenarios associated with production and use of sulphuric acid a potential risk may arise if sulphuric acid comes into contact with human skin. This is due to the nature of sulphuric acid and its ability to cause chemical burns. As this effect is considered to be related to the corrosivity of sulphuric acid a threshold DNEL cannot be established for this risk and so measures to control this risk should be assessed in a qualitative manner. Though this risk is most pertinent when workers may come into contact with concentrated sulphuric acid in an industrial setting the operational conditions (OCs) and risk management measures (RMMs) used to control and manage the risk of dermal contact events may be equally applicable across all the exposure scenarios.

In the industrial setting an acute risk of dermal burns from exposure to sulphuric acid in its concentrated form (or its dilute form) exists due to possible splashing of the liquid acid. This risk would be highest at times of transfer to tankers, filling of barrels and filling of small vessels etc. Though these events are considered unlikely due to the high degree of system closure and control the risk is still protected against in order to eliminate any possible routes of exposure.

The risk of dermal contact is reduced due to the OC's in place. The specialised nature of the systems

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

and the degree of closure associated with them ensure the potential for dermal contact is minimised. All pipes and transfers lines are closed and sealed in order to reduce possible exposure to leaks or splashes, as are the reactors to reduce possible emissions. During times of transfer to/from road tankers gas displacement lines and special connecting systems are in place to reduce the levels of gaseous emissions that could deposit to surfaces including human skin. Specialised tanker coupling/uncoupling systems and targeted purging systems may be used in certain circumstances where large volumes and high concentrations are required. Training and certification ensures the workers understand the correct procedures for use of these specialized systems so that the measures in place to reduce emissions are conducted so proper function can be maintained.

In addition to the measures in place to reduce system emissions, workers are completely separated from the site of operation. Workers are generally housed in areas segregated from the main emission sources and time spent on tasks which require close proximity to the emission sources can be minimised effectively. Separate control rooms, screens and outdoor reactor units help to keep workers away from any potential sources of exposure. Emergency measures (and training on procedures and safe work practice) are in place in the industrial setting to ensure that any unforeseen events are safely dealt with in the case that they do arise. These measures range from procedural policies which are in place to guide workers in the proper response in the case of splashes or spills to dedicated equipment (such as emergency showers or spill clean-up kits) which can be used to minimise any effects should unforeseen exposure arise.

Personal protective equipment (PPE) should be supplied to any personnel who may be working in areas where potential emission sources (such as transfer pipes) are located. Suitable PPE that should be used to prevent dermal contact for workers would be acid resistant clothing, helmets, gloves, goggles and boots. The PPE should be properly maintained and certified and should be replaced when required. These measures combined will effectively function to ensure three aspects of safe use. These are, firstly, reduction of potential emissions with specialised systems. Secondly reduction of the potential for exposure of workers by means such as segregation and training and thirdly physical protection of the worker with the use of correct PPE. With the combination of these measures it is considered that the risk of chemical burns to workers is adequately managed.

As mentioned above when the concentration of the sulphuric acid decreases so does the potential for chemical burns to human skin. However the same measures are still in place to ensure that workers, professionals and consumers are protected from risk.

8.4

Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environmental releases:

In order to work within the boundaries of the ES the following conditions should be met:

- Emission to air after scrubbing less than 12,500 kg per day
- No emission to the municipal STP
- The industrial WWTP sludge should not be spread to soil

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

- Wastewater should be fully neutralized
- Exhaust gases from use are treated with scrubbers.
- Sufficient LEV and vapour recovery systems are in place to reduce exposure.
- Measured emissions should be confirmed to be less than the relevant PNECs in section 3.

Worker exposure:

In order to work within the boundaries of the ES the following conditions should be met:

- Reactors and pipelines should be sealed systems
- Workers should wear protective gloves, goggles, overalls and boots at all times in the production and transfer area.
- Respiratory protection should be worn when required.
- Workers should be segregated from the area of use with no direct contact with the installation housing the machinery.
- Any measured exposure should be confirmed to be less than the relevant DNELs in section 3 above.

8.5

Additional good practice advice beyond the REACH CSA.

- Do not eat, drink or smoke when working with sulphuric acid.
- Always wash hands and exposed skin thoroughly after using sulphuric acid or any surfaces/machinery that may have come into contact with sulphuric acid.
- Workers should be suitably trained in all safety procedures and in the safe handling of sulphuric acid to prevent risk of exposure.
- All PPE should be properly maintained and stored in an appropriate way so as not to damage its integrity. Workers should be correctly trained in its use.
- Procedural and safety compliance should be routinely assessed by management
- Machinery should be regularly maintained and checked for proper function
- Efficacy of all emission RMMs and waste treatment procedures should be routinely assessed and confirmed to be functioning correctly

9

Exposure Scenario 9: Use of sulphuric acid in maintenance of sulphuric acid contained batteries.

Use of sulphuric acid in maintenance of sulphuric acid contained batteries

Processes Covered:

Environmental Releases

ERC08b: Wide dispersive indoor use of reactive substances in open systems

ERC09b: Wide dispersive outdoor use of substances in closed systems

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Worker Processes

PROC19: Hand-mixing with intimate contact and only PPE available

Produce Category

PC0: Other [UNC code E10100 (Electrolytes)]

Sulphuric acid may be involved in battery maintenance. Given that batteries are sealed articles and that the sulphuric acid involved in their maintenance is not intended for direct release, exposure to and emission from sulphuric acid in these processes should be minimal. The only exposure from the maintenance of lead acid batteries will come when the electrolyte solution is topped off or replaced with fresh de-ionized water.

Because of the processes involved in battery maintenance (and the nature of sulphuric acid and the produced gases), specially trained workers and systems are employed.

Contributing Environmental Scenario: CES1 Environmental exposure arising due to the use of sulphuric acid in the maintenance of sulphuric acid contained batteries. (ERC 08b and ERC 09b).

Contributing Worker Scenarios: CES 2: worker exposure arising due to hand-mixing with intimate contact and only PPE available (PROC 19).

9.1 Controlling environmental exposure for ES 9

ES9: Contributing exposure scenario (CES) 1 Environmental exposure arising due to use of sulphuric acid in the maintenance of sulphuric acid contained batteries.

Section 2.1 describes the environmental releases that may occur during the use of sulphuric acid in the maintenance of sulphuric acid contained batteries. These releases may potentially occur due to emission to the atmosphere. Environmental emissions are limited by designated waste treatment process designed to limit environmental exposure to all relevant compartments. Waste gas emissions are scrubbed and filtered, significantly lessening the possible emission by atmospheric deposition to soil or surface waters.

Waste stream treatment may also be employed to reduce environmental exposure however for this wide dispersive use particular risk management measures are not needed to demonstrate environmental safe use.

Use of sulphuric acid in the maintenance of sulphuric acid contained batteries is generally continuous with constant production and use. Facilities generally use up to 2,500 tonnes per year which is considered to be a worst case assumption for a single site in Europe, operating 365 days per year.

Product characteristics

The produced substance is a liquid with purity greater than 90%. The substance is colourless, odourless inorganic liquid which is miscible with water. Sulphuric acid is not flammable and is non-explosive.

Amounts used

Facilities generally use up to 2,500 tonnes per year which is considered to be a worst case assumption

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

for a single site in Europe, operating 365 days per year.	
Frequency and duration of use	
Continuous production and release.	
Environmental factors influenced by risk management	
On site WWTP with the capacity for complete neutralization. Emissions to air may be as much as 34.2 kg/d but are generally much less. Exhaust gases may be treated by scrubbers and filtered.	
Other operational conditions affecting environmental exposure	
The use of sulphuric acid in the maintenance of sulphuric acid contained batteries takes place in outdoor facilities. Any gas displaced from containers is conducted via pipeline to be processed i.e. removed and scrubbed and /or filtered. Reactors and transfer pipelines are closed systems, with insulation if required.	
Technical conditions and measures at process level (source) to prevent release	
As mentioned above reactors and pipelines are fully sealed and insulated if necessary. Both production and sampling are carried out in dedicated, contained facilities.	
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Sulphuric acid used in the maintenance of sulphuric acid contained batteries on a large scale generally is only required on a rare occurrence. However, in the event that it is required, waste stream treatment may be employed to reduce environmental exposure.	
Organizational measures to prevent/limit releases from site	
Workers are fully trained in order to prevent accidental release.	
Conditions and measures related to municipal STP	
There is no release to the municipal STP due to the rare occurrence of the activity described in this exposure scenario.	
Conditions and measures related to external treatment of waste for disposal	
There is no further generation of solid waste.	
Conditions and measures related to external recovery of waste	
There is no envisaged external recovery of waste.	
9.2	Controlling worker exposure for ES 9
ES 9: CES 2: worker exposure arising due to hand-mixing with intimate contact and only PPE available (PROC 19).	
During the use of sulphuric acid in the maintenance of sulphuric acid contained batteries, controlled systems are in place to reduce the potential for worker exposure in all cases.	
Loading and unloading of vessels of sulphuric acid for use in maintenance of batteries is usually performed in the open air. Workers wear protective clothing (face/eye protection, helmet, anti-acid gloves boots and protective overall). A safety shower is required nearby in case of accidental spillage. Gas displacement lines are also used if filling of road tankers takes place under cover. Any gas displaced from containers is conducted via pipeline to be processed i.e. removed and scrubbed and /or filtered.	
Product characteristics	
The produced substance is a liquid with purity greater than 90%. The substance is colourless, odourless inorganic liquid which is miscible with water. Sulphuric acid is not flammable and is non-explosive.	
Amounts used	

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Facilities generally use up to 2,500 tonnes per year which is considered to be a worst case assumption for a single site in Europe, operating 365 days per year.
Frequency and duration of use exposure
Workers perform standard shifts of 8 hours per day and have standard working years of 220 days per year. However, the activities associated with this exposure scenario generally only occur rarely.
Human factors not influenced by risk management
Respiration volumes under conditions of use 10m ³ /d (default value for a worker breathing for an 8h work day in RIP 3.2).
Other given operational conditions affecting worker exposure
Maintenance of batteries is generally carried out by trained technicians in facilities with exposure and waste treatment procedures in place. The handling of sulphuric acid involves special equipment and controlled systems with little or no potential for exposure.
Technical conditions and measures at process level (source) to prevent release
Reactors and pipes are sealed systems.
Technical conditions to control dispersion from source towards worker
Any gas displaced from containers is conducted via pipeline to be processed (removed and scrubbed and /or filtered).
Organizational measures to prevent/limit release
Workers involved in loading and unloading of vessels of sulphuric acid for use in maintenance of batteries wear protective clothing (face/eye protection, helmet, anti-acid gloves boots and protective overall). A safety shower is required nearby in case of accidental spillage.
Conditions and measures related to personal protection, hygiene and health.
Anti-acid gloves, goggles, chemical resistant overalls and work boots are worn by all operators in the facility to prevent dermal exposure.

9.3	Exposure estimation and reference to its source
------------	--

Environmental Exposure

For the tier 1 risk characterisation PECs derived using the ERC defaults are not assessed below as the PECs are considered unrealistically high and would lead to a failing risk assessment in any case. For the tier 2 risk characterisation the PECs calculated by the EUSES environmental model with refined inputs taking into account the emission RMMs as discussed in section 2.1 above are used to control environmental releases are used for the assessment.

Information for contributing exposure scenario 1:

List of exposure concentrations

Compartment	PEC	Justification
ERC 8B Freshwater (in mg/L)	3.31 x 10 ⁻⁵	
ERC 8B Marine water (in mg/L)	2.29 x 10 ⁻⁵	
ERC 8B Intermittent releases to water (in mg/L)	NA	Intermittent release not relevant
ERC 8B Freshwater sediment (in mg/kg)	2.67 x 10 ⁻⁵	
ERC 8B Marine sediment (in mg/kg)	1.84 x 10 ⁻⁵	

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

ERC 8B Agricultural soil (averaged over 30 days (in mg/kg))	5.77×10^{-5}	
ERC 8B Groundwater (in mg/L)	9.08×10^{-5}	
ERC 8B Annual average PEC in air, total (mg/m ³)	1.9×10^{-4}	
ERC 9B Freshwater (in mg/L)	8.99×10^{-5}	
ERC 9B Marine water (in mg/L)	5.83×10^{-5}	
ERC 9B Intermittent releases to water (in mg/L)	NA	Intermittent release not relevant
ERC 9B Freshwater sediment (in mg/kg)	7.23×10^{-5}	
ERC 9B Marine sediment (in mg/kg)	4.69×10^{-5}	
ERC 9B Agricultural soil (averaged over 30 days (in mg/kg))	2.96×10^{-4}	
ERC 9B Groundwater (in mg/L)	1.35×10^{-3}	
ERC 9B Annual average PEC in air, total (mg/m ³)	9.52×10^{-3}	

The following RCRs were derived taking into account derived PNEC values

Compartments	PEC mg/L	PNEC mg/L	PEC/PNEC	Comments
ERC 8B Tier 1 Freshwater	2.26×10^{-5}	0.0025	0.009	Safe use in tier 1 for all compartments
ERC 8B Tier 1 Sediment	2.67×10^{-5}	0.002 (EPM)	0.0133	
ERC 8B Tier 1 Marine sediment	1.84×10^{-5}	0.002 (EPM)	0.009	
ERC 8B Tier 1 Marine	2.26×10^{-5}	0.00025	0.09	
ERC 9B Tier 1 Freshwater	5.64×10^{-5}	0.0025	0.02	Safe use in tier 1 for all compartments
ERC 9BTier 1 Sediment	1.84×10^{-5}	0.002 (EPM)	0.0092	
ERC 9BTier 1 Marine sediment	4.69×10^{-5}	0.002 (EPM)	0.0023	
ERC 9BTier 1 Marine	5.64×10^{-5}	0.00025	0.22	

* EPM = equilibrium partitioning method

Worker exposure

The Advanced REACH tool (ART) was used to estimate worker exposure as it was considered that the ECETOC model cannot estimate in a satisfactory manner the effects of the stringent containment and segregation practices which are in place to deal with sulphuric acid production and to limit exposure.

In the characterisation of the human health risks posed by acute/short term and long-term inhalation exposures to sulphuric acid (or formed sulphuric acid) associated with ES 9, the 90th percentile (e.g. worst case) inhalation exposure concentrations derived using the ART model for relevant PROC codes were compared with the DNEL value for acute local respiratory effects and the DNEL value for long-term local respiratory effects respectively. The results of the risk characterisation are shown in the table

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

below.

The predicted acute/short-term and long-term inhalation exposure concentrations derived using the ART model were not found to exceed the DNEL value for acute local respiratory effects or the DNEL value for long-term local respiratory effects respectively for any of the processes associated with ES 9. On the basis of the assumptions made in the exposure assessment and this risk characterisation, it can be concluded that inhalation exposures to sulphuric acid that may potentially arise during processes associated with ES 9 do not pose an unacceptable health risk to workers.

Information for worker contributing scenario 2:

List of inputs used in the ART assessment

	PROC	Parameters/ assumptions
Exposure duration	PROC 19	240 mins exposure / day; 240 mins non-exposure/day
Product type	PROC 19	Liquid (low viscosity – like water)
Process temperature	PROC 19	Room temperature (15-25oC)
Vapour pressure	PROC 19	Substance is considered to be low volatile, exposure to acid mists is estimated
Liquid weight fraction	PROC 19	0.25
Primary emission source proximity	PROC 19	Primary emission source located in the breathing zone of the workers (i.e. Within 1 metre)
Activity class	PROC 19	Handling of contaminated objects
Localised controls	PROC 19	None
Fugative emission source	PROC 19	Not fully enclosed – effective housekeeping practices in place
Dispersion	PROC 19	Indoors, any sized room, only good natural ventilation

List of derived exposure concentrations

Description of activity	PROC	Physical state of material	Estimated Exposure Concentrations (mg/m3)		Estimated Exposure Concentration (mg/m3)	
			50 th percentile value	90 th percentile value	50 th percentile value	90 th percentile value
Hand-mixing with intimate contact: only PPE available	19	Liquid	0.00058	0.0023	0.00079	0.002

List of derived RCRs

Exposure details	CES	PROC Code	ES 9- 90 th exposure concentrations (mg/m3)	Leading toxic end point / Critical effect	DNEL (mg/m3)	Risk characterisation ratio
Acute-local effects	CES 2	PROC 19	2.3×10^{-3}	Respiratory irritation and corrosivity	0.1	2.3×10^{-2}

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Long-term – local effects	CES 2	PROC 19	2×10^{-3}	Respiratory irritation and corrosivity	0.05	4×10^{-2}
---------------------------	-------	---------	--------------------	--	------	--------------------

Assessment of dermal risk

During the processes that will be carried out for all the exposure scenarios associated with production and use of sulphuric acid a potential risk may arise if sulphuric acid comes into contact with human skin. This is due to the nature of sulphuric acid and its ability to cause chemical burns. As this effect is considered to be related to the corrosivity of sulphuric acid a threshold DNEL cannot be established for this risk and so measures to control this risk should be assessed in a qualitative manner. Though this risk is most pertinent when workers may come into contact with concentrated sulphuric acid in an industrial setting the operational conditions (OCs) and risk management measures (RMMs) used to control and manage the risk of dermal contact events may be equally applicable across all the exposure scenarios.

In the industrial setting an acute risk of dermal burns from exposure to sulphuric acid in its concentrated form (or its dilute form) exists due to possible splashing of the liquid acid. This risk would be highest at times of transfer to tankers, filling of barrels and filling of small vessels etc. Though these events are considered unlikely due to the high degree of system closure and control the risk is still protected against in order to eliminate any possible routes of exposure.

The risk of dermal contact is reduced due to the OC's in place. The specialised nature of the systems and the degree of closure associated with them ensure the potential for dermal contact is minimised. All pipes and transfers lines are closed and sealed in order to reduce possible exposure to leaks or splashes, as are the reactors to reduce possible emissions. During times of transfer to/from road tankers gas displacement lines and special connecting systems are in place to reduce the levels of gaseous emissions that could deposit to surfaces including human skin. Specialised tanker coupling/uncoupling systems and targeted purging systems may be used in certain circumstances where large volumes and high concentrations are required. Training and certification ensures the workers understand the correct procedures for use of these specialized systems so that the measures in place to reduce emissions are conducted so proper function can be maintained.

In addition to the measures in place to reduce system emissions, workers are completely separated from the site of operation. Workers are generally housed in areas segregated from the main emission sources and time spent on tasks which require close proximity to the emission sources can be minimised effectively. Separate control rooms, screens and outdoor reactor units help to keep workers away from any potential sources of exposure. Emergency measures (and training on procedures and safe work practice) are in place in the industrial setting to ensure that any unforeseen events are safely dealt with in the case that they do arise. These measures range from procedural policies which are in place to guide workers in the proper response in the case of splashes or spills to dedicated equipment (such as emergency showers or spill clean-up kits) which can be used to minimise any effects should unforeseen exposure arise.

Personal protective equipment (PPE) should be supplied to any personnel who may be working in areas where potential emission sources (such as transfer pipes) are located. Suitable PPE that should be used to prevent dermal contact for workers would be acid resistant clothing, helmets, gloves, goggles and

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

boots. The PPE should be properly maintained and certified and should be replaced when required. These measures combined will effectively function to ensure three aspects of safe use. These are, firstly, reduction of potential emissions with specialised systems. Secondly reduction of the potential for exposure of workers by means such as segregation and training and thirdly physical protection of the worker with the use of correct PPE. With the combination of these measures it is considered that the risk of chemical burns to workers is adequately managed.

As mentioned above when the concentration of the sulphuric acid decreases so does the potential for chemical burns to human skin. However the same measures are still in place to ensure that workers, professionals and consumers are protected from risk.

9.4

Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environmental releases:

In order to work within the boundaries of the ES the following conditions should be met:

- Emission to air after scrubbing less than 34.2 kg per day
- No emission to the municipal STP
- Waste stream treatment may also be employed to reduce environmental exposure.
- Gas displaced from containers is conducted via pipeline to be scrubbed and /or filtered.
- Measured emissions should be confirmed to be less than the relevant PNECs in section 3.

Worker exposure:

In order to work within the boundaries of the ES the following conditions should be met:

- Reactors and pipelines should be sealed systems
- Workers should wear protective anti-acid gloves, goggles, overalls and boots at all times in the production and transfer area.
- Any measured exposure should be confirmed to be less than the relevant DNELs in section 3 above.

9.5

Additional good practice advice beyond the REACH CSA.

- Do not eat, drink or smoke when working with sulphuric acid.
- Always wash hands and exposed skin thoroughly after using sulphuric acid or any surfaces/machinery that may have come into contact with sulphuric acid.
- Workers should be suitably trained in all safety procedures and in the safe handling of sulphuric acid to prevent risk of exposure.
- All PPE should be properly maintained and stored in an appropriate way so as not to damage its integrity. Workers should be correctly trained in its use.
- Procedural and safety compliance should be routinely assessed by management
- Machinery should be regularly maintained and checked for proper function
- Efficacy of all emission RMMs and waste treatment procedures should be routinely assessed and

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

confirmed to be functioning correctly

10 Exposure Scenario 10: Recycling of lead acid batteries containing sulphuric acid

Use of sulphuric acid in maintenance of sulphuric acid contained batteries

Processes Covered:

Environmental Releases

ERC01: Manufacture of Substances

Worker Processes

PROC02: Use in closed, continuous process with occasional controlled exposure (including sampling and maintenance)

PROC04: Use in batch and other process (synthesis) where opportunity for exposure arises

PROC05: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

PROC08a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

Produce Category

PC0: Other [UNC code E10100 (Electrolytes)]

Sulphuric acid, at a concentration of 25 to 40%, may be involved in the recycling of batteries. The process of battery recycling is aimed at recovery of the lead from the battery plates and removal of the sulphuric acid electrolyte solution. The batteries are mechanically crushed using, for example, a hydraulic press, and the electrolyte is drained and collected. Recovered acid may be re-used for some applications or can be neutralized and treated to remove contaminants and disposed.

Because of the processes involved in the recycling of batteries (and the nature of sulphuric acid and the produced gases), specially trained workers and systems are employed.

Contributing Environmental Scenario: CES1 Environmental exposure arising due to the use of sulphuric acid in the recycling of batteries. (ERC 01).

Contributing Worker Scenarios: CES 2: worker exposure arising due to use in a closed process with occasional controlled exposure (PROC 02), CES 3: worker exposure arising due to use in batch and other processes where opportunity for exposure may arise (PROC 04), CES 4: worker exposure due to mixing or blending in batch processes (PROC 05) and CES 5: worker exposure due to transfer of substance or preparation from/to vessels/large containers at non-dedicated facilities (PROC 8a).

10.1 Controlling environmental exposure for ES 10

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

ES10: Contributing exposure scenario (CES) 1 Environmental exposure arising due to use of sulphuric acid in the recycling of batteries.

Section 2.1 describes the environmental releases that may occur during the use of sulphuric acid in the recycling of batteries. Environmental emissions are limited by designated waste treatment process designed to limit environmental exposure to all relevant compartments. Waste gas emissions are scrubbed and may also then be diverted to the wastewater stream. This significantly lessens the possible emission by atmospheric deposition to soil or surface waters.

Liquid wastes are treated (neutralisation to neutral pH) prior to emission to remove any sulphuric acid in the waste water and sludge from the waste water treatment plant is sent for incineration or landfill and is not used for agricultural spreading. This precludes any contamination of soil by sludge spreading. Waste water treatment is usually carried out by neutralisation followed by flocculation or decantation.

Use of sulphuric acid in the recycling of batteries is generally continuous with constant production and use. Facilities generally use up to 2,500 tonnes per year which is considered to be a worst case assumption for a single site in Europe, operating 365 days per year.

Product characteristics

The produced substance is a liquid with purity between 25 to 40%. The substance is colourless, odourless inorganic liquid which is miscible with water. Sulphuric acid is not flammable and is non-explosive.

Amounts used

Facilities generally use up to 2,500 tonnes per year which is considered to be a worst case assumption for a single site in Europe, operating 365 days per year.

Frequency and duration of use

Continuous production and release.

Environmental factors influenced by risk management

On site WWTP with the capacity for complete neutralization. Emissions to air may be as much as 34.2 kg/d but are generally much less. Exhaust gases may be treated by scrubbers and filtered.

Other operational conditions affecting environmental exposure

The use of sulphuric acid in the recycling of batteries takes place in outdoor facilities. Any gas displaced from containers is conducted via pipeline to be processed i.e. removed and scrubbed and /or filtered. Reactors and transfer pipelines are closed systems, with insulation if required.

Technical conditions and measures at process level (source) to prevent release

As mentioned above reactors and pipelines are fully sealed and insulated if necessary. Both production and sampling are carried out in dedicated, contained facilities.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Waste waters are generally treated on site by chemical and/or biological methods before release to the municipal STP or to the environment. All sludge is collected and incinerated or sent to landfill. All gas emissions are scrubbed and filtered and may also then be diverted to the wastewater stream.

Organizational measures to prevent/limit releases from site

Workers are fully trained in order to prevent accidental release.

Conditions and measures related to municipal STP

Waste waters are generally treated on site by chemical and/or biological methods before release to the municipal STP or to the environment.

Conditions and measures related to external treatment of waste for disposal

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

All sludge from the onsite WWTP is collected and incinerated or sent to landfill for disposal. Waste from any scrubbers should be directed to waste water stream for further treatment. There is no further generation of solid waste

Conditions and measures related to external recovery of waste

There is no envisaged external recovery of waste.

10.2 Controlling worker exposure for ES 10

ES 10: CES 2: worker exposure arising due to use in a closed process with occasional controlled exposure (PROC 02), CES 3: worker exposure arising due to use in batch and other processes where opportunity for exposure may arise (PROC 04), CES 4: worker exposure due to mixing or blending in batch processes (PROC 05) and CES 5: worker exposure due to transfer of substance or preparation from/to vessels/large containers at non-dedicated facilities (PROC 8a).

During the use of sulphuric acid in the recycling of sulphuric acid batteries, controlled systems are in place to reduce the potential for worker exposure in all cases.

Loading and unloading of vessels of sulphuric acid for use in the recycling of batteries containing is usually performed in the open air. Workers wear protective clothing (face/eye protection, helmet, anti acid gloves boots and protective overall). A safety shower is required nearby in case of accidental spillage.

Gas displacement lines are also used if filling of road tankers takes place under cover. Any gas displaced from containers is conducted via pipeline to be processed i.e. removed and scrubbed and /or filtered.

Product characteristics

The produced substance is a liquid with purity between 25 to 40%. The substance is colourless, odourless inorganic liquid which is miscible with water. Sulphuric acid is not flammable and is non-explosive.

Amounts used

Facilities generally use up to 2,500 tonnes per year which is considered to be a worst case assumption for a single site in Europe, operating 365 days per year.

Frequency and duration of use exposure

Workers perform standard shifts of 8 hours per day and have standard working years of 220 days per year. However, these activities are expected to be short duration tasks and 8 hours per day is a worst case assumption.

Human factors not influenced by risk management

Respiration volumes under conditions of use 10m³/d (default value for a worker breathing for an 8h work day in RIP 3.2).

Other given operational conditions affecting worker exposure

Recycling of batteries is generally carried out by trained technicians in facilities with exposure and waste treatment procedures in place. The handling of sulphuric acid involves special equipment and controlled systems with little or no potential for exposure. Workers involved in the loading and unloading of vessels of sulphuric acid for use in the recycling of batteries is usually performed in the open air. Workers wear protective clothing (face/eye protection, helmet, anti-acid gloves boots and protective overall).

Technical conditions and measures at process level (source) to prevent release

Reactors and pipes are sealed systems.

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Technical conditions to control dispersion from source towards worker

Any gas displaced from containers is conducted via pipeline to be processed (removed and scrubbed and /or filtered). During handling when transferring drum filling, special equipment and controlled systems with little or no potential for exposure are used to prevent losses occurring.

Organizational measures to prevent/limit release

Workers involved in loading and unloading of vessels of sulphuric acid for use in the recycling of batteries wear protective clothing (face/eye protection, helmet, anti-acid gloves boots and protective overall) to minimise the risk of exposure.

Conditions and measures related to personal protection, hygiene and health.

Anti-acid gloves, goggles, chemical resistant overalls and work boots are worn by all operators in the facility to prevent dermal exposure.

10.3

Exposure estimation and reference to its source

Environmental Exposure

For the tier 1 risk characterisation PECs derived using the ERC defaults are not assessed below as the PECs are considered unrealistically high and would lead to a failing risk assessment in any case. For the tier 2 risk characterisation the PECs calculated by the EUSES environmental model with refined inputs taking into account the emission RMMs as discussed in section 2.1 above are used to control environmental releases are used for the assessment.

Information for contributing exposure scenario 1:

List of exposure concentrations

Compartment	PEC	Justification
Freshwater (in mg/L)	7.38×10^{-6}	
Marine water (in mg/L)	1.07×10^{-6}	
Intermittent releases to water (in mg/L)	NA	Intermittent release not relevant
Freshwater sediment (in mg/kg)	5.94×10^{-6}	
Marine sediment (in mg/kg)	8.6×10^{-7}	
Agricultural soil (averaged over 30 days (in mg/kg)	1.6×10^{-4}	
Groundwater (in mg/L)	1.18×10^{-3}	
Annual average PEC in air, total (mg/m ³)	9.52×10^{-3}	

The following RCRs were derived taking into account derived PNEC values

Compartments	PEC mg/L	PNEC mg/L	PEC/PNEC	Comments
Tier 2 Freshwater	7.38×10^{-6}	0.0025	0.00292	Safe use demonstrated in tier 2
Tier 2 Sediment	5.94×10^{-6}	0.002 (EPM)	0.0029	Safe use demonstrated in tier 2

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Tier 2 Marine sediment	8.6×10^{-7}	0.002 (EPM)	4.3×10^{-4}	Safe use demonstrated in tier 2
Tier 2 Marine	1.07×10^{-6}	0.00025	0.0042	Safe use demonstrated in tier 2

* EPM = equilibrium partitioning method

Worker exposure

The Advanced REACH tool (ART) was used to estimate worker exposure as it was considered that the ECETOC model cannot estimate in a satisfactory manner the effects of the stringent containment and segregation practices which are in place to deal with sulphuric acid production and to limit exposure.

In the characterisation of the human health risks posed by acute/short term and long-term inhalation exposures to sulphuric acid (or formed sulphuric acid) associated with ES 10, the 90th percentile (e.g. worst case) inhalation exposure concentrations derived using the ART model for relevant PROC codes were compared with the DNEL value for acute local respiratory effects and the DNEL value for long-term local respiratory effects respectively. The results of the risk characterisation are shown in the table below.

The predicted acute/short-term and long-term inhalation exposure concentrations derived using the ART model were not found to exceed the DNEL value for acute local respiratory effects or the DNEL value for long-term local respiratory effects respectively for any of the processes associated with ES 10. On the basis of the assumptions made in the exposure assessment and this risk characterisation, it can be concluded that inhalation exposures to sulphuric acid that may potentially arise during processes associated with ES 10 do not pose an unacceptable health risk to workers.

Information for worker contributing scenario 2, 3, 4 and 5:

List of inputs used in the ART assessment

	PROC	Parameters/ assumptions
Exposure duration	All	480 mins
Product type	All	Liquid (low viscosity – like water)
Process temperature	All	Room temperature (15-25oC)
Vapour pressure	All	Substance is considered to be low volatile, exposure to mists is estimated
Liquid weight fraction	All	0.25
Primary emission source proximity	All	Primary emission source located in the breathing zone of the workers (i.e. Within 1 metre)
Activity class	PROC 2,4	Transfer of liquid products
	PROC 2,4, 8a	Transfer of liquid products – falling liquids, 1-10 L/min
	PROC 5	Activities with open surfaces
Containment	PROC 2	Handling reduces contact between product and adjacent air
	PROC 8a	Handling reduces contact between product and adjacent air – submerged loading
	PROC 4	Open process – submerged loading

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

	PROC 5	n/a
Localised controls	All	LEV
Fugitive emission source	All	Not fully enclosed – effective housekeeping practices in place.
Dispersion	All	Indoors, any sized room, only good natural ventilation

List of derived exposure concentrations

Description of activity	PROC	Physical state of material	Estimated Exposure (mg/m ³)	Short-term Concentrations		Estimated Exposure (mg/m ³)	Long-term Concentration
			50 th percentile value	90 th percentile value		50 th percentile value	90 th percentile value
Use in closed, continuous process with occasional controlled exposure (including sampling and maintenance)	2	Liquid	0.00035	0.0014		0.00047	0.0012
Use in batch and other process (synthesis) where opportunity for exposure arises	4	Liquid	0.0012	0.0046		0.0016	0.004
Mixing or blending in batch process for formulation of preparations or articles (multistage and/or significant contact)	5	Liquid	0.0038	0.015		0.0053	0.013
Transfer of 10% sulphuric acid cleaning solution to/from large vessels/containers at non-dedicated facilities	8b	Liquid	0.0017	0.0069		0.0024	0.006

List of derived RCRs

Exposure details	CES	PROC Code	ES 10- 90 th exposure concentrations (mg/m ³)	Leading toxic end point / Critical effect	DNEL (mg/m ³)	Risk characterisation ratio
Acute-local effects	CES 2	PROC 02	1.4×10^{-3}	Respiratory irritation and corrositivity	0.1	1.4×10^{-2}
	CES 3	PROC 04	4.6×10^{-3}	Respiratory irritation and corrositivity	0.1	4.6×10^{-2}
	CES 4	PROC 05	1.5×10^{-2}	Respiratory irritation and corrositivity	0.1	1.5×10^{-1}

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

	CES 5	PROC 08b	6.9×10^{-3}	Respiratory irritation and corrositivity	0.1	6.9×10^{-2}
Long-term – local effects	CES 2	PROC 02	1.2×10^{-3}	Respiratory irritation and corrositivity	0.05	2.4×10^{-2}
	CES 3	PROC 04	4×10^{-3}	Respiratory irritation and corrositivity	0.05	8×10^{-2}
	CES 4	PROC 05	1.3×10^{-2}	Respiratory irritation and corrositivity	0.05	2.6×10^{-1}
	CES 5	PROC 08b	6×10^{-3}	Respiratory irritation and corrositivity	0.05	1.2×10^{-1}

Assessment of dermal risk

During the processes that will be carried out for all the exposure scenarios associated with production and use of sulphuric acid a potential risk may arise if sulphuric acid comes into contact with human skin. This is due to the nature of sulphuric acid and its ability to cause chemical burns. As this effect is considered to be related to the corrosivity of sulphuric acid a threshold DNEL cannot be established for this risk and so measures to control this risk should be assessed in a qualitative manner. Though this risk is most pertinent when workers may come into contact with concentrated sulphuric acid in an industrial setting the operational conditions (OCs) and risk management measures (RMMs) used to control and manage the risk of dermal contact events may be equally applicable across all the exposure scenarios.

In the industrial setting an acute risk of dermal burns from exposure to sulphuric acid in its concentrated form (or its dilute form) exists due to possible splashing of the liquid acid. This risk would be highest at times of transfer to tankers, filling of barrels and filling of small vessels etc. Though these events are considered unlikely due to the high degree of system closure and control the risk is still protected against in order to eliminate any possible routes of exposure.

The risk of dermal contact is reduced due to the OC's in place. The specialised nature of the systems and the degree of closure associated with them ensure the potential for dermal contact is minimised. All pipes and transfers lines are closed and sealed in order to reduce possible exposure to leaks or splashes, as are the reactors to reduce possible emissions. During times of transfer to/from road tankers gas displacement lines and special connecting systems are in place to reduce the levels of gaseous emissions that could deposit to surfaces including human skin. Specialised tanker coupling/uncoupling systems and targeted purging systems may be used in certain circumstances where large volumes and high concentrations are required. Training and certification ensures the workers understand the correct procedures for use of these specialized systems so that the measures in place to reduce emissions are conducted so proper function can be maintained.

In addition to the measures in place to reduce system emissions, workers are completely separated from the site of operation. Workers are generally housed in areas segregated from the main emission sources and time spent on tasks which require close proximity to the emission sources can be minimised effectively. Separate control rooms, screens and outdoor reactor units help to keep workers away from any potential sources of exposure. Emergency measures (and training on procedures and safe work

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

practice) are in place in the industrial setting to ensure that any unforeseen events are safely dealt with in the case that they do arise. These measures range from procedural policies which are in place to guide workers in the proper response in the case of splashes or spills to dedicated equipment (such as emergency showers or spill clean-up kits) which can be used to minimise any effects should unforeseen exposure arise.

Personal protective equipment (PPE) should be supplied to any personnel who may be working in areas where potential emission sources (such as transfer pipes) are located. Suitable PPE that should be used to prevent dermal contact for workers would be acid resistant clothing, helmets, gloves, goggles and boots. The PPE should be properly maintained and certified and should be replaced when required. These measures combined will effectively function to ensure three aspects of safe use. These are, firstly, reduction of potential emissions with specialised systems. Secondly reduction of the potential for exposure of workers by means such as segregation and training and thirdly physical protection of the worker with the use of correct PPE. With the combination of these measures it is considered that the risk of chemical burns to workers is adequately managed.

As mentioned above when the concentration of the sulphuric acid decreases so does the potential for chemical burns to human skin. However the same measures are still in place to ensure that workers, professionals and consumers are protected from risk.

10.4

Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environmental releases:

In order to work within the boundaries of the ES the following conditions should be met:

- Emission to air after scrubbing less than 34.2 kg per day
- No emission to the municipal STP
- The industrial WWTP sludge should not be spread to soil
- Wastewater should be fully neutralized
- Waste stream treatment may also be employed to reduce environmental exposure.
- Gas displaced from containers is conducted via pipeline to be scrubbed and /or filtered.
- Measured emissions should be confirmed to be less than the relevant PNECs in section 3.

Worker exposure:

In order to work within the boundaries of the ES the following conditions should be met:

- Reactors and pipelines should be sealed systems
- Workers should wear protective anti-acid gloves, goggles, overalls and boots at all times in the production and transfer area.
- Any measured exposure should be confirmed to be less than the relevant DNELs in section 3 above.

10.5

Additional good practice advice beyond the REACH CSA.

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

- Do not eat, drink or smoke when working with sulphuric acid.
- Always wash hands and exposed skin thoroughly after using sulphuric acid or any surfaces/machinery that may have come into contact with sulphuric acid.
- Workers should be suitably trained in all safety procedures and in the safe handling of sulphuric acid to prevent risk of exposure.
- All PPE should be properly maintained and stored in an appropriate way so as not to damage its integrity. Workers should be correctly trained in its use.
- Procedural and safety compliance should be routinely assessed by management
- Machinery should be regularly maintained and checked for proper function
- Efficacy of all emission RMMs and waste treatment procedures should be routinely assessed and confirmed to be functioning correctly

11 Exposure Scenario 11: Use of lead acid batteries containing sulphuric acid

Use of lead acid batteries containing sulphuric acid.

Processes Covered:

Environmental Releases

ERC09b: Wide dispersive outdoor use of substances in closed systems

Worker Processes

PROC19: Hand-mixing with intimate contact and only PPE available

Article Category

AC3: Electrical batteries and accumulators

Sulphuric acid may be used in battery maintenance in the form of DIY battery maintenance/top-up kits, primarily by consumers. As batteries are sealed articles and that the sulphuric acid involved in their maintenance is not intended for direct release, exposure to and emission from sulphuric acid in these processes should be minimal.

Because of the processes involved in the recycling of batteries (and the nature of sulphuric acid and the produced gases), specially trained workers and systems are employed.

Contributing Environmental Scenario: CES1 Environmental exposure arising due to the use of lead acid batteries containing sulphuric acid. (ERC 01).

Contributing Worker Scenarios: CES 2: consumer exposure arising due to hand-mixing with intimate contact and only PPE available (PROC 19).

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

11.1	Controlling environmental exposure for ES 11
ES11: Contributing exposure scenario (CES) 1 Environmental exposure arising due to the use of lead acid batteries containing sulphuric acid.	
<p>Section 2.1 describes the environmental releases that may occur during the use of lead acid batteries containing sulphuric acid. Environmental emissions may be limited by waste stream treatment, however for this wide dispersive use particular risk management measures are not needed to demonstrate environmental safe use.</p> <p>Use of lead acid batteries containing sulphuric acid is generally considered to be a sporadic activity which is not continuous. Facilities generally use up to 2,500 tonnes per year which is considered to be a worst case assumption for a single site in Europe, operating 365 days per year.</p>	
Product characteristics	
The produced substance is a liquid with purity between 25 to 40%. The substance is colourless, odourless inorganic liquid which is miscible with water. Sulphuric acid is not flammable and is non-explosive.	
Amounts used	
Facilities generally use up to 2,500 tonnes per year which is considered to be a worst case assumption for a single site in Europe, operating 365 days per year.	
Frequency and duration of use	
The frequency of events associated with this use is expected to be sporadic.	
Environmental factors influenced by risk management	
Waste stream treatment may be employed to reduce environmental exposure. Emissions to air may be as much as 34.2 kg/d but are generally much less.	
Other operational conditions affecting environmental exposure	
The use of lead acid batteries containing sulphuric acid takes place in outdoor facilities.	
Technical conditions and measures at process level (source) to prevent release	
No additional technical measures in place to prevent release.	
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Waste stream treatment may be employed to reduce environmental exposure.	
Organizational measures to prevent/limit releases from site	
Workers are fully trained in order to prevent accidental release.	
Conditions and measures related to municipal STP	
Waste stream treatment may be employed to reduce environmental exposure.	
Conditions and measures related to external treatment of waste for disposal	
There is no further generation of solid waste	
Conditions and measures related to external recovery of waste	
There is no envisaged external recovery of waste.	

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

11.2	Controlling worker exposure for ES 11
ES 11: CES 2: consumer exposure arising due to hand-mixing with intimate contact and only PPE available (PROC 19).	
During the use of lead acid batteries containing sulphuric acid, controlled systems are in place to reduce the potential for consumer exposure in all cases.	
Loading and unloading of vessels of sulphuric acid for use in maintenance of batteries is usually performed in the open air. Consumers are advised to wear protective clothing, however, the worst case assumption is that no localised controls are used in the process.	
Product characteristics	
The produced substance is a liquid with purity between 25 to 40%. The substance is colourless, odourless inorganic liquid which is miscible with water. Sulphuric acid is not flammable and is non-explosive.	
Amounts used	
Facilities generally use up to 2,500 tonnes per year which is considered to be a worst case assumption for a single site in Europe, operating 365 days per year.	
Frequency and duration of use exposure	
Workers perform standard shifts of 8 hours per day and have standard working years of 220 days per year. However, these activities are expected to be short duration tasks and 8 hours per day is considered to be a worst case assumption.	
Human factors not influenced by risk management	
Respiration volumes under conditions of use 10m ³ /d (default value for a worker breathing for an 8h work day in RIP 3.2).	
Other given operational conditions affecting worker exposure	
The use of lead acid batteries containing sulphuric acid is generally carried out by the public in facilities which are not expected to have specific exposure controls and waste treatment measures in place. Individuals involved in the loading and unloading of vessels of sulphuric acid for use in the maintenance of batteries is usually performed in the open air. Consumers are advised to wear protective clothing, however, the worst case assumption is that no localised controls are used in the process.	
Technical conditions and measures at process level (source) to prevent release	
No specific localized control measures are in place.	
Technical conditions to control dispersion from source towards worker	
No specific localized control measures are expected to be in place.	
Organizational measures to prevent/limit release	
Consumers are advised to wear protective clothing, however, the worst case assumption is that no localised controls are used in the process.	
Conditions and measures related to personal protection, hygiene and health.	
It is advisable that consumers wear suitable protective clothing but no localized controls are expected to be in place.	

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

11.3

Exposure estimation and reference to its source

Environmental Exposure

For the tier 1 risk characterisation PECs derived using the ERC defaults are not assessed below as the PECs are considered unrealistically high and would lead to a failing risk assessment in any case. For the tier 2 risk characterisation the PECs calculated by the EUSES environmental model with refined inputs taking into account the emission RMMs as discussed in section 2.1 above are used to control environmental releases are used for the assessment.

Information for contributing exposure scenario 1:

List of exposure concentrations

Compartment	PEC	Justification
Freshwater (in mg/L)	8.99×10^{-5}	
Marine water (in mg/L)	5.83×10^{-5}	
Intermittent releases to water (in mg/L)	NA	Intermittent release not relevant
Freshwater sediment (in mg/kg)	7.23×10^{-5}	
Marine sediment (in mg/kg)	4.69×10^{-5}	
Agricultural soil (averaged over 30 days (in mg/kg)	2.96×10^{-4}	
Groundwater (in mg/L)	1.35×10^{-3}	
Annual average PEC in air, total (mg/m ³)	9.52×10^{-3}	

The following RCRs were derived taking into account derived PNEC values

Compartments	PEC mg/L	PNEC mg/L	PEC/PNEC	Comments
ERC 9B Tier 1 Freshwater	5.64×10^{-5}	0.0025	0.22	Safe use in tier 1 for all compartments
ERC 9BTier 1 Sediment	1.84×10^{-5}	0.002 (EPM)	0.092	
ERC 9BTier 1 Marine	5.64×10^{-5}	0.00025	0.22	
ERC 9BTier 1 Marine sediment	4.69×10^{-5}	0.002 (EPM)	0.0023	

* EPM = equilibrium partitioning method

Worker exposure

The Advanced REACH tool (ART) was used to estimate worker exposure as it was considered that the ECETOC model cannot estimate in a satisfactory manner the effects of the stringent containment and segregation practices which are in place to deal with sulphuric acid production and to limit exposure.

In the characterisation of the human health risks posed by acute/short term and long-term inhalation exposures to sulphuric acid (or formed sulphuric acid) associated with ES 11, the 90th percentile (e.g.

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

worst case) inhalation exposure concentrations derived using the ART model for relevant PROC codes were compared with the DNEL value for acute local respiratory effects and the DNEL value for long-term local respiratory effects respectively. The results of the risk characterisation are shown in the table below.

The predicted acute/short-term and long-term inhalation exposure concentrations derived using the ART model were not found to exceed the DNEL value for acute local respiratory effects or the DNEL value for long-term local respiratory effects respectively for any of the processes associated with ES 11. On the basis of the assumptions made in the exposure assessment and this risk characterisation, it can be concluded that inhalation exposures to sulphuric acid that may potentially arise during processes associated with ES 11 do not pose an unacceptable health risk to workers.

Information for worker contributing scenario 2:

List of inputs used in the ART assessment

	PROC	Parameters/ assumptions
Exposure duration	PROC 19	240 mins exposure / day; 240 mins non-exposure/day
Product type	PROC 19	Liquid (low viscosity – like water)
Process temperature	PROC 19	Room temperature (15-25oC)
Vapour pressure	PROC 19	6 Pa – Substance is considered to be low volatile, exposure to mists is estimated
Liquid weight fraction	PROC 19	0.25
Primary emission source proximity	PROC 19	Primary emission source located in the breathing zone of the workers (i.e. Within 1 metre)
Activity class	PROC 19	Handling of contaminated objects
Localised controls	PROC 19	None
Fugative emission source	PROC 19	Not fully enclosed – effective housekeeping practices in place
Dispersion	PROC 19	Indoors, any sized room, only good natural ventilation

List of derived exposure concentrations

Description of activity	PROC	Physical state of material	Short-term Concentrations		Long-term Concentration	
			Estimated Exposure (mg/m3) 50 th percentile value	90 th percentile value	Estimated Exposure (mg/m3) 50 th percentile value	90 th percentile value
Hand-mixing with intimate contact: only PPE available	19	Liquid	0.00058	0.0023	0.00079	0.002

List of derived RCRs

Exposure details	CES	PROC Code	ES 11- 90 th exposure concentrations (mg/m3)	Leading toxic end point / Critical effect	DNEL (mg/m3)	Risk characterisation ratio
------------------	-----	-----------	---	---	--------------	-----------------------------

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Acute-local effects	CES 2	PROC 19	2.3×10^{-3}	Respiratory irritation and corrositivity	0.1	2.3×10^{-2}
Long-term – local effects	CES 2	PROC 19	2×10^{-3}	Respiratory irritation and corrositivity	0.05	4×10^{-2}

Assessment of dermal risk

During the processes that will be carried out for all the exposure scenarios associated with production and use of sulphuric acid a potential risk may arise if sulphuric acid comes into contact with human skin. This is due to the nature of sulphuric acid and its ability to cause chemical burns. As this effect is considered to be related to the corrosivity of sulphuric acid a threshold DNEL cannot be established for this risk and so measures to control this risk should be assessed in a qualitative manner. Though this risk is most pertinent when workers may come into contact with concentrated sulphuric acid in an industrial setting the operational conditions (OCs) and risk management measures (RMMs) used to control and manage the risk of dermal contact events may be equally applicable across all the exposure scenarios.

In the industrial setting an acute risk of dermal burns from exposure to sulphuric acid in its concentrated form (or its dilute form) exists due to possible splashing of the liquid acid. This risk would be highest at times of transfer to tankers, filling of barrels and filling of small vessels etc. Though these events are considered unlikely due to the high degree of system closure and control the risk is still protected against in order to eliminate any possible routes of exposure.

The risk of dermal contact is reduced due to the OC's in place. The specialised nature of the systems and the degree of closure associated with them ensure the potential for dermal contact is minimised. All pipes and transfers lines are closed and sealed in order to reduce possible exposure to leaks or splashes, as are the reactors to reduce possible emissions. During times of transfer to/from road tankers gas displacement lines and special connecting systems are in place to reduce the levels of gaseous emissions that could deposit to surfaces including human skin. Specialised tanker coupling/uncoupling systems and targeted purging systems may be used in certain circumstances where large volumes and high concentrations are required. Training and certification ensures the workers understand the correct procedures for use of these specialized systems so that the measures in place to reduce emissions are conducted so proper function can be maintained.

In addition to the measures in place to reduce system emissions, workers are completely separated from the site of operation. Workers are generally housed in areas segregated from the main emission sources and time spent on tasks which require close proximity to the emission sources can be minimised effectively. Separate control rooms, screens and outdoor reactor units help to keep workers away from any potential sources of exposure. Emergency measures (and training on procedures and safe work practice) are in place in the industrial setting to ensure that any unforeseen events are safely dealt with in the case that they do arise. These measures range from procedural policies which are in place to guide workers in the proper response in the case of splashes or spills to dedicated equipment (such as emergency showers or spill clean-up kits) which can be used to minimise any effects should unforeseen exposure arise.

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Personal protective equipment (PPE) should be supplied to any personnel who may be working in areas where potential emission sources (such as transfer pipes) are located. Suitable PPE that should be used to prevent dermal contact for workers would be acid resistant clothing, helmets, gloves, goggles and boots. The PPE should be properly maintained and certified and should be replaced when required. These measures combined will effectively function to ensure three aspects of safe use. These are, firstly, reduction of potential emissions with specialised systems. Secondly reduction of the potential for exposure of workers by means such as segregation and training and thirdly physical protection of the worker with the use of correct PPE. With the combination of these measures it is considered that the risk of chemical burns to workers is adequately managed.

As mentioned above when the concentration of the sulphuric acid decreases so does the potential for chemical burns to human skin. However the same measures are still in place to ensure that workers, professionals and consumers are protected from risk.

11.4

Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environmental releases:

In order to work within the boundaries of the ES the following conditions should be met:

- Emission to air after scrubbing less than 34.2 kg per day
- Waste stream treatment may be employed to reduce environmental exposure.
- Measured emissions should be confirmed to be less than the relevant PNECs in section 3.

Worker exposure:

In order to work within the boundaries of the ES the following conditions should be met:

- Consumers are advised to wear appropriate protective clothing in the use and handling of sulphuric acid.
- Any measured exposure should be confirmed to be less than the relevant DNELs in section 3 above.

11.5

Additional good practice advice beyond the REACH CSA.

- Do not eat, drink or smoke when working with sulphuric acid.
- Always wash hands and exposed skin thoroughly after using sulphuric acid or any surfaces/machinery that may have come into contact with sulphuric acid.
- Workers should be suitably trained in all safety procedures and in the safe handling of sulphuric acid to prevent risk of exposure.
- All PPE should be properly maintained and stored in an appropriate way so as not to damage its integrity. Workers should be correctly trained in its use.

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

- Procedural and safety compliance should be routinely assessed by management
- Machinery should be regularly maintained and checked for proper function
- Efficacy of all emission RMMs and waste treatment procedures should be routinely assessed and confirmed to be functioning correctly

12 Exposure Scenario 12: Use of sulphuric acid as a laboratory chemical

Use of sulphuric acid as a laboratory chemical

Processes Covered:

Environmental Releases

ERC08a: Wide dispersive indoor use of processing aids in open systems

ERC08b: Wide dispersive indoor use of reactive substances in open systems

Worker Processes

PROC15: Use as laboratory reagent

Produce Category

PC21: Laboratory chemicals

Sulphuric acid may be used as laboratory agent in buffers, in protein reagents and as acidification reagents. Uses would generally be on a smaller scale and would not be intensive. Sulphuric acid may be used in laboratories in a diluted form as the uses of acid in laboratory science are so diverse.

Because of the processes involved in the use of sulphuric acid as a laboratory agent, (and the nature of sulphuric acid and the produced gases), specially trained workers and systems are employed.

Contributing Environmental Scenario: CES1 Environmental exposure arising due to the use of sulphuric acid as a laboratory reagent. (ERC 08a and ERC 08b).

Contributing Worker Scenarios: CES 2: worker exposure arising due to use as a laboratory reagent (PROC 15).

12.1 Controlling environmental exposure for ES 12

ES12: Contributing exposure scenario (CES) 1 Environmental exposure arising due to use of sulphuric acid as a laboratory reagent.

Section 2.1 describes the environmental releases that may occur during the use of sulphuric acid as a laboratory reagent. Environmental emissions are limited by waste capture strategies including the use of flow hoods with gaseous removal and dedicated effluent capture treatment facilities are generally

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

employed. This significantly lessens the possible emission by atmospheric deposition to soil or surface waters.

Use of sulphuric acid as a laboratory reagent is generally continuous with constant production and use. Facilities generally use up to 5,000 tonnes per year which is considered to be a worst case assumption for a single site in Europe, operating 365 days per year.

Product characteristics

The produced substance is a liquid with purity greater than 90%. The substance is colourless, odourless inorganic liquid which is miscible with water. Sulphuric acid is not flammable and is non-explosive.

Amounts used

Facilities generally use up to 5,000 tonnes per year which is considered to be a worst case assumption for a single site in Europe, operating 365 days per year.

Frequency and duration of use

Continuous production and release.

Environmental factors influenced by risk management

Dedicated effluent capture treatment facilities are used. Emissions to air may be as much as 1,370 kg/d but are generally much less. Exhaust gases may be treated by the use of flow hoods with gaseous removal capabilities.

Other operational conditions affecting environmental exposure

The use of sulphuric acid as a laboratory reagent takes place indoors. Any gas displaced from containers is conducted via pipeline to be processed i.e. removed and scrubbed and /or filtered.

Technical conditions and measures at process level (source) to prevent release

Laboratory use and handling of sulphuric acid occurs indoors and involves special equipment with little or no potential for exposure.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Waste stream treatment may be used to reduce environmental exposure however for this wide dispersive use particular risk management measures are not needed to demonstrate environmental safe use for laboratories. All gas emissions are scrubbed and filtered through the use of flow hoods to capture any gaseous emissions.

Organizational measures to prevent/limit releases from site

Workers using sulphuric acid in a laboratory are fully trained in order to prevent accidental release.

Conditions and measures related to municipal STP

Waste waters are generally treated on site.

Conditions and measures related to external treatment of waste for disposal

Waste stream treatment and gaseous capture through the use of flow hoods may be used to reduce environmental exposure however for this wide dispersive use particular risk management measures are not needed to demonstrate environmental safe use for laboratories. There is no further generation of solid waste

Conditions and measures related to external recovery of waste

There is no envisaged external recovery of waste.

12.2

Controlling worker exposure for ES 12

ES 12: CES 2: worker exposure arising due to use as a laboratory reagent (PROC 15).

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

During the use of sulphuric acid as a laboratory reagent, controlled systems are in place to reduce the potential for worker exposure in all cases.

Workers involved in the handling and transfer of materials are trained in the procedures and protective equipment is intended to cope with the worst case scenario, in order to minimise exposure and risks. LEV is generally used to ensure adequate control of gaseous emissions.

Product characteristics

The produced substance is a liquid with purity greater than 90%. The substance is colourless, odourless inorganic liquid which is miscible with water. Sulphuric acid is not flammable and is non-explosive.

Amounts used

Facilities generally use up to 5,000 tonnes per year which is considered to be a worst case assumption for a single site in Europe, operating 365 days per year.

Frequency and duration of use exposure

Workers perform standard shifts of 8 hours per day and have standard working years of 220 days per year. However, the activities associated with the use of sulphuric acid as a laboratory reagent are expected to be short duration tasks and 8 hours per day is a worst case assumption.

Human factors not influenced by risk management

Respiration volumes under conditions of use $10\text{m}^3/\text{d}$ (default value for a worker breathing for an 8h work day in RIP 3.2).

Other given operational conditions affecting worker exposure

Sulphuric acid is used as a laboratory reagent by trained personnel. LEV and the use of flow hoods to capture gaseous emissions reduce the potential for exposure. Controlled systems are also employed with little or no potential for exposure. Workers involved in the handling and transfer of materials are trained in the procedures and protective equipment is intended to cope with the worst case scenario, in order to minimise exposure and risks.

Technical conditions and measures at process level (source) to prevent release

LEV and the use of flow hoods to capture gaseous emissions reduce the potential for exposure.

Technical conditions to control dispersion from source towards worker

Any gas displaced during the use of sulphuric acid as a laboratory reagent is captured in flow hoods to be scrubbed and /or filtered. During the use of sulphuric acid as a laboratory reagent, special equipment and controlled systems with little or no potential for exposure are used to prevent losses occurring.

Organizational measures to prevent/limit release

Workers involved in the handling and transfer of materials are trained in the procedures and protective equipment is intended to cope with the worst case scenario, in order to minimise exposure and risks.

Conditions and measures related to personal protection, hygiene and health.

Anti-acid gloves, goggles, chemical resistant overalls and work boots are worn by all operators in the facility to prevent dermal exposure.

12.3

Exposure estimation and reference to its source

Environmental Exposure

For the tier 1 risk characterisation PECs derived using the ERC defaults are not assessed below as the PECs are considered unrealistically high and would lead to a failing risk assessment in any case. For the tier 2 risk characterisation the PECs calculated by the EUSES environmental model with refined inputs taking into account the emission RMMs as discussed in section 2.1 above are used to control

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

environmental releases are used for the assessment.

Information for contributing exposure scenario 1:

List of exposure concentrations

Compartment	PEC	Justification
ERC 8a Freshwater (in mg/L)	1.34×10^{-4}	Wide dispersive dilution.
ERC 8a Marine water (in mg/L)	6.04×10^{-6}	
ERC 8a Intermittent releases to water (in mg/L)	NA	Intermittent release not relevant
ERC 8a Freshwater sediment (in mg/kg)	1.08×10^{-4}	
ERC 8a Marine sediment (in mg/kg)	6.04×10^{-6}	
ERC 8a Agricultural soil (averaged over 30 days (in mg/kg)	6.42×10^{-3}	
ERC 8a Groundwater (in mg/L)	0.0213	
ERC 8a Annual average PEC in air, total (mg/m ³)	0.381	
ERC 8b Freshwater (in mg/L)	2.12×10^{-6}	Wide dispersive dilution.
ERC 8b Marine water (in mg/L)	5.54×10^{-8}	
ERC 8b Intermittent releases to water (in mg/L)	NA	Intermittent release not relevant
ERC 8b Freshwater sediment (in mg/kg)	1.7×10^{-6}	
ERC 8b Marine sediment (in mg/kg)	5.54×10^{-8}	
ERC 8b Agricultural soil (averaged over 30 days (in mg/kg)	1.1×10^{-4}	
ERC 8b Groundwater (in mg/L)	1.49×10^{-4}	
ERC 8b Annual average PEC in air, total (mg/m ³)	3.81×10^{-4}	

The following RCRs were derived taking into account derived PNEC values

Compartments	PEC mg/L	PNEC mg/L	PEC/PNEC	Comments
ERC 8A Tier 1 Freshwater	1.34×10^{-4}	0.0025	0.0536	Safe use in tier 1 for all compartments
ERC 8A Tier 1 Sediment	2.67×10^{-5}	0.002 (EPM)	0.013	
ERC 8A Tier 1 Marine sediment	6.04×10^{-6}	0.002 (EPM)	0.003	
ERC 8A Tier 1 Marine	1.08×10^{-4}	0.00025	0.43	
ERC 8B Tier 1 Freshwater	2.21×10^{-6}	0.0025	8.8×10^{-4}	Safe use in tier 1 for all compartments
ERC 8BTier 1 Sediment	1.7×10^{-6}	0.002 (EPM)	8.5×10^{-4}	
ERC 8BTier 1 Marine sediment	5.54×10^{-8}	0.002 (EPM)	2.7×10^{-5}	

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

ERC 8BTier 1 Marine	5.54 x 10 ⁻⁸	0.00025	2.1 x 10 ⁻⁴	
---------------------	-------------------------	---------	------------------------	--

* EPM = equilibrium partitioning method

Worker exposure

The Advanced REACH tool (ART) was used to estimate worker exposure as it was considered that the ECETOC model cannot estimate in a satisfactory manner the effects of the stringent containment and segregation practices which are in place to deal with sulphuric acid production and to limit exposure.

In the characterisation of the human health risks posed by acute/short term and long-term inhalation exposures to sulphuric acid (or formed sulphuric acid) associated with ES 12, the 90th percentile (e.g. worst case) inhalation exposure concentrations derived using the ART model for relevant PROC codes were compared with the DNEL value for acute local respiratory effects and the DNEL value for long-term local respiratory effects respectively. The results of the risk characterisation are shown in the table below.

The predicted acute/short-term and long-term inhalation exposure concentrations derived using the ART model were not found to exceed the DNEL value for acute local respiratory effects or the DNEL value for long-term local respiratory effects respectively for any of the processes associated with ES 12. On the basis of the assumptions made in the exposure assessment and this risk characterisation, it can be concluded that inhalation exposures to sulphuric acid that may potentially arise during processes associated with ES 12 do not pose an unacceptable health risk to workers.

Information for worker contributing scenario 2:

List of inputs used in the ART assessment

	PROC	Parameters/ assumptions
Exposure duration	PROC 15	240 mins exposure / day; 240 mins non-exposure/day
Product type	PROC 15	Liquid (medium viscosity – like oil)
Process temperature	PROC 15	Room temperature (15-25oC)
Vapour pressure	PROC 15	Substance is considered to be low volatile, exposure to mists is estimated
Liquid weight fraction	PROC 15	0.98
Primary emission source proximity	PROC 15	Primary emission source located in the breathing zone of the workers (i.e. Within 1 metre)
Activity class	PROC 15	Transfer of liquids
Localised controls	PROC 15	LEV
Fugative emission source	PROC 15	Not fully enclosed – effective housekeeping practices in place
Dispersion	PROC 15	Indoors, any sized room, only good natural ventilation

List of derived exposure concentrations

Description of activity	PROC	Physical state of material	Estimated Exposure (mg/m3)	Short-term Concentrations	Estimated Exposure (mg/m3)	Long-term Concentration

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

			50 th percentile value	90 th percentile value	50 th percentile value	90 th percentile value
Handling sulphuric acid in a laboratory	15	Liquid	6.8 x 10 ⁻⁵	2.7 x 10 ⁻⁴	9.3 x 10 ⁻⁵	2.3 x 10 ⁻⁴

List of derived RCRs

Exposure details	CES	PROC Code	ES 12- 90 th exposure concentrations (mg/m3)	Leading toxic end point / Critical effect	DNEL (mg/m3)	Risk characterisation ratio
Acute-local effects	CES 2	PROC 15	2.7 x 10 ⁻⁴	Respiratory irritation and corrositivity	0.1	2.7 x 10 ⁻³
Long-term – local effects	CES 2	PROC 15	2.3 x 10 ⁻⁴	Respiratory irritation and corrositivity	0.05	4.6 x 10 ⁻³

Assessment of dermal risk

During the processes that will be carried out for all the exposure scenarios associated with production and use of sulphuric acid a potential risk may arise if sulphuric acid comes into contact with human skin. This is due to the nature of sulphuric acid and its ability to cause chemical burns. As this effect is considered to be related to the corrosivity of sulphuric acid a threshold DNEL cannot be established for this risk and so measures to control this risk should be assessed in a qualitative manner. Though this risk is most pertinent when workers may come into contact with concentrated sulphuric acid in an industrial setting the operational conditions (OCs) and risk management measures (RMMs) used to control and manage the risk of dermal contact events may be equally applicable across all the exposure scenarios.

In the industrial setting an acute risk of dermal burns from exposure to sulphuric acid in its concentrated form (or its dilute form) exists due to possible splashing of the liquid acid. This risk would be highest at times of transfer to tankers, filling of barrels and filling of small vessels etc. Though these events are considered unlikely due to the high degree of system closure and control the risk is still protected against in order to eliminate any possible routes of exposure.

The risk of dermal contact is reduced due to the OC's in place. The specialised nature of the systems and the degree of closure associated with them ensure the potential for dermal contact is minimised. All pipes and transfers lines are closed and sealed in order to reduce possible exposure to leaks or splashes, as are the reactors to reduce possible emissions. During times of transfer to/from road tankers gas displacement lines and special connecting systems are in place to reduce the levels of gaseous emissions that could deposit to surfaces including human skin. Specialised tanker coupling/uncoupling systems and targeted purging systems may be used in certain circumstances where large volumes and high concentrations are required. Training and certification ensures the workers understand the correct procedures for use of these specialized systems so that the measures in place to reduce emissions are conducted so proper function can be maintained.

In addition to the measures in place to reduce system emissions, workers are completely separated from

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

the site of operation. Workers are generally housed in areas segregated from the main emission sources and time spent on tasks which require close proximity to the emission sources can be minimised effectively. Separate control rooms, screens and outdoor reactor units help to keep workers away from any potential sources of exposure. Emergency measures (and training on procedures and safe work practice) are in place in the industrial setting to ensure that any unforeseen events are safely dealt with in the case that they do arise. These measures range from procedural policies which are in place to guide workers in the proper response in the case of splashes or spills to dedicated equipment (such as emergency showers or spill clean-up kits) which can be used to minimise any effects should unforeseen exposure arise.

Personal protective equipment (PPE) should be supplied to any personnel who may be working in areas where potential emission sources (such as transfer pipes) are located. Suitable PPE that should be used to prevent dermal contact for workers would be acid resistant clothing, helmets, gloves, goggles and boots. The PPE should be properly maintained and certified and should be replaced when required. These measures combined will effectively function to ensure three aspects of safe use. These are, firstly, reduction of potential emissions with specialised systems. Secondly reduction of the potential for exposure of workers by means such as segregation and training and thirdly physical protection of the worker with the use of correct PPE. With the combination of these measures it is considered that the risk of chemical burns to workers is adequately managed.

As mentioned above when the concentration of the sulphuric acid decreases so does the potential for chemical burns to human skin. However the same measures are still in place to ensure that workers, professionals and consumers are protected from risk.

12.4

Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environmental releases:

In order to work within the boundaries of the ES the following conditions should be met:

- Emission to air after scrubbing less than 1,370 kg per day
- Waste stream treatment may be used to reduce environmental exposure.
- Gas displaced following use of sulphuric acid as a laboratory reagent is captured in flow hoods and is scrubbed and /or filtered.
- Sufficient LEV and vapour recovery systems are in place to reduce exposure.
- Measured emissions should be confirmed to be less than the relevant PNECs in section 3.

Worker exposure:

In order to work within the boundaries of the ES the following conditions should be met:

- LEV and the use of flow hoods to capture gaseous emissions reduce the potential for exposure.
- Workers should wear protective anti-acid gloves, goggles, overalls and boots at all times in the production and transfer area.
- Any measured exposure should be confirmed to be less than the relevant DNELs in section 3 above.

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

12.5	Additional good practice advice beyond the REACH CSA.
<ul style="list-style-type: none"> • Do not eat, drink or smoke when working with sulphuric acid. • Always wash hands and exposed skin thoroughly after using sulphuric acid or any surfaces/machinery that may have come into contact with sulphuric acid. • Workers should be suitably trained in all safety procedures and in the safe handling of sulphuric acid to prevent risk of exposure. • All PPE should be properly maintained and stored in an appropriate way so as not to damage its integrity. Workers should be correctly trained in its use. • Procedural and safety compliance should be routinely assessed by management • Machinery should be regularly maintained and checked for proper function • Efficacy of all emission RMMs and waste treatment procedures should be routinely assessed and confirmed to be functioning correctly 	

13	Exposure Scenario 13: Use of sulphuric acid in industrial cleaning
<p>Use of sulphuric acid in industrial cleaning</p> <p>Processes Covered:</p> <p>Environmental Releases</p> <p>ERC08a: Wide dispersive indoor use of processing aids in open systems ERC08b: Wide dispersive indoor use of reactive substances in open systems</p> <p>Worker Processes</p> <p>PROC02: Use in closed, continuous process with occasional controlled exposure (including sampling and maintenance) PROC05: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant con-tact) PROC08a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC08b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC09: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC10: Roller application or brushing PROC13: Treatment of articles by dipping and pouring</p> <p>Produce Category PC35: Washing and cleaning products (including solvent based products)</p>	

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Sulphuric acid as a component or feedstock in heavy duty industrial cleaners. This use would not be very regular and would generally be used in cases of heavy industrial contamination.

Because of the processes involved in the use of sulphuric acid as a laboratory agent, (and the nature of sulphuric acid and the produced gases), specially trained workers and systems are employed.

Contributing Environmental Scenario: CES1 Environmental exposure arising due to the use of sulphuric acid in industrial cleaning. (ERC 08a and ERC 08b).

Contributing Worker Scenarios: CES 2: worker exposure due to day to day use in closed continuous processes with occasional exposure (such as sampling) (PROC 2), CES 3: worker exposure due to mixing or blending in batch processes for formulation of preparations and articles in an industrial setting (PROC 5), CES 4: worker exposure due to transfer of substance to and from vessels and containers at non-dedicated and dedicated facilities (PROC 8a and PROC 8b), CES 5: worker exposure due to transfer of formulations or preparations to small containers (PROC 9), CES 6: worker exposure due to roller and brushing application (PROC 10) and CES 7: worker exposure due to treatment of articles by dipping and pouring (PROC 13).

13.1 Controlling environmental exposure for ES 13

ES13 Contributing exposure scenario (CES) 1 Environmental exposure arising due to use of sulphuric acid industrial cleaning.

Section 2.1 describes the environmental releases that may occur during the use of sulphuric acid in industrial cleaning. Environmental emissions are limited by emission to the STP. Waste stream treatment may also be employed to reduce environmental exposure however for this wide dispersive use particular risk management measures are not needed to demonstrate environmental safe use.

In addition to this, as the amounts used are low and pre-diluted, dilution in the waste stream is expected to be significant, thus reducing the exposure to the environment.

Use of sulphuric acid as a laboratory reagent is generally continuous with constant production and use. Facilities generally use up to 5,000 tonnes per year which is considered to be a worst case assumption for a single site in Europe, operating 365 days per year.

Product characteristics

The produced substance is a liquid with purity of 10%. The substance is colourless, odourless inorganic liquid which is miscible with water. Sulphuric acid is not flammable and is non-explosive.

Amounts used

Facilities generally use up to 5,000 tonnes per year which is considered to be a worst case assumption for a single site in Europe, operating 365 days per year.

Frequency and duration of use

Use is expected to be infrequent in varying amounts.

Environmental factors influenced by risk management

Environmental emissions are directed to the STP. Emissions to air may be as much as 1,370 kg/d but are generally much less. Exhaust gases are removed by LEV.

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Other operational conditions affecting environmental exposure	
The use of sulphuric acid in industrial cleaning takes place indoors in controlled environments. Any gas displaced from containers is removed by LEV.	
Technical conditions and measures at process level (source) to prevent release	
Sulphuric acid used in industrial cleaning is used by trained personnel under controlled conditions. LEV is in place to capture any gaseous emissions. All emissions are directed to the STP for treatment before emission to the environment.	
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Environmental emissions are limited by emission to the STP. Waste stream treatment may also be employed to reduce environmental exposure. All gas emissions are captured by LEV to prevent any gaseous emissions.	
Organizational measures to prevent/limit releases from site	
Workers using sulphuric acid in industrial cleaning are fully trained in order to prevent accidental release.	
Conditions and measures related to municipal STP	
Waste emissions are treated in the onsite STP.	
Conditions and measures related to external treatment of waste for disposal	
Environmental emissions are limited by emission to the STP. Waste stream treatment may also be employed to reduce environmental exposure. There is no further generation of solid waste	
Conditions and measures related to external recovery of waste	
There is no envisaged external recovery of waste.	
13.2	Controlling worker exposure for ES 13
ES 13: CES 2: worker exposure due to day to day use in closed continuous processes with occasional exposure (such as sampling) (PROC 2), CES 3: worker exposure due to mixing or blending in batch processes for formulation of preparations and articles in an industrial setting (PROC 5), CES 4: worker exposure due to transfer of substance to and from vessels and containers at non-dedicated and dedicated facilities (PROC 8a and PROC 8b), CES 5: worker exposure due to transfer of formulations or preparations to small containers (PROC 9), CES 6: worker exposure due to roller and brushing application (PROC 10) and CES 7: worker exposure due to treatment of articles by dipping and pouring (PROC 13).	
During the use of sulphuric acid in industrial cleaning, controlled systems are in place to reduce the potential for worker exposure in all cases.	
Loading and unloading of vessels of sulphuric acid for use in maintenance of batteries is usually performed in the open air. Workers wear protective clothing (face/eye protection, helmet, anti-acid gloves boots and protective overall). A safety shower is required nearby in case of accidental spillage. LEV is generally used to ensure adequate control of gaseous emissions.	
Product characteristics	
The produced substance is a liquid with purity of 10%. The substance is colourless, odourless inorganic liquid which is miscible with water. Sulphuric acid is not flammable and is non-explosive.	
Amounts used	
Facilities generally use up to 5,000 tonnes per year which is considered to be a worst case assumption	

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

for a single site in Europe, operating 365 days per year.
Frequency and duration of use exposure
Workers perform standard shifts of 8 hours per day and have standard working years of 220 days per year. However, the activities associated with the use of sulphuric acid in industrial cleaning are expected to be short duration tasks and 8 hours per day is a worst case assumption.
Human factors not influenced by risk management
Respiration volumes under conditions of use 10m ³ /d (default value for a worker breathing for an 8h work day in RIP 3.2).
Other given operational conditions affecting worker exposure
Industrial cleaning using sulphuric acid is conducted by trained personnel. LEV is in place to capture gaseous emissions, reducing the potential for exposure. Workers involved in the loading/unloading of sulphuric acid or the handling of sulphuric acid wear protective clothing (face/eye protection, helmet, anti-acid gloves boots and protective overall). Workers are also trained in the procedures and protective equipment is intended to cope with the worst case scenario, in order to minimise exposure and risks.
Technical conditions and measures at process level (source) to prevent release
LEV used to capture gaseous emissions reduces the potential for exposure.
Technical conditions to control dispersion from source towards worker
Any gas displaced from containers is removed by LEV. During the use of sulphuric acid as a laboratory reagent, special equipment and controlled systems with little or no potential for exposure are used to prevent losses occurring.
Organizational measures to prevent/limit release
Workers involved in the handling and transfer of materials are trained in the procedures and protective equipment is intended to cope with the worst case scenario, in order to minimise exposure and risks.
Conditions and measures related to personal protection, hygiene and health.
Anti-acid gloves, goggles, chemical resistant overalls and work boots are worn by all operators in the facility to prevent dermal exposure.

13.3

Exposure estimation and reference to its source

Environmental Exposure

For the tier 1 risk characterisation PECs derived using the ERC defaults are not assessed below as the PECs are considered unrealistically high and would lead to a failing risk assessment in any case. For the tier 2 risk characterisation the PECs calculated by the EUSES environmental model with refined inputs taking into account the emission RMMs as discussed in section 2.1 above are used to control environmental releases are used for the assessment.

Information for contributing exposure scenario 1:

List of exposure concentrations

Compartment	PEC	Justification
ERC 8a Freshwater (in mg/L)	1.34 x 10 ⁻⁴	Wide dispersive dilution.
ERC 8a Marine water (in mg/L)	6.04 x 10 ⁻⁶	

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

ERC 8a Intermittent releases to water (in mg/L)	NA	Intermittent release not relevant
ERC 8a Freshwater sediment (in mg/kg)	1.08×10^{-4}	
ERC 8a Marine sediment (in mg/kg)	6.04×10^{-6}	
ERC 8a Agricultural soil (averaged over 30 days (in mg/kg)	6.42×10^{-3}	
ERC 8a Groundwater (in mg/L)	0.0213	
ERC 8a Annual average PEC in air, total (mg/m ³)	0.381	
ERC 8b Freshwater (in mg/L)	2.12×10^{-6}	Wide dispersive dilution.
ERC 8b Marine water (in mg/L)	5.54×10^{-8}	
ERC 8b Intermittent releases to water (in mg/L)	NA	Intermittent release not relevant
ERC 8b Freshwater sediment (in mg/kg)	1.7×10^{-6}	
ERC 8b Marine sediment (in mg/kg)	5.54×10^{-8}	
ERC 8b Agricultural soil (averaged over 30 days (in mg/kg)	1.1×10^{-4}	
ERC 8b Groundwater (in mg/L)	1.49×10^{-4}	
ERC 8b Annual average PEC in air, total (mg/m ³)	3.81×10^{-4}	

The following RCRs were derived taking into account derived PNEC values

Compartments	PEC mg/L	PNEC mg/L	PEC/PNEC	Comments
ERC 8A Tier 1 Freshwater	1.34×10^{-4}	0.0025	0.0536	Safe use in tier 1 for all compartments
ERC 8A Tier 1 Sediment	2.67×10^{-5}	0.002 (EPM)	0.013	
ERC 8A Tier 1 Marine sediment	6.04×10^{-6}	0.002 (EPM)	0.003	
ERC 8A Tier 1 Marine	1.08×10^{-4}	0.00025	0.43	
ERC 8B Tier 1 Freshwater	2.21×10^{-6}	0.0025	8.8×10^{-4}	Safe use in tier 1 for all compartments
ERC 8BTier 1 Sediment	1.7×10^{-6}	0.002 (EPM)	8.5×10^{-4}	
ERC 8BTier 1 Marine sediment	5.54×10^{-8}	0.002 (EPM)	2.7×10^{-5}	
ERC 8BTier 1 Marine	5.54×10^{-8}	0.00025	2.1×10^{-4}	

* EPM = equilibrium partitioning method

Worker exposure

The Advanced REACH tool (ART) was used to estimate worker exposure as it was considered that the ECETOC model cannot estimate in a satisfactory manner the effects of the stringent containment and segregation practices which are in place to deal with sulphuric acid production and to limit exposure.

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

In the characterisation of the human health risks posed by acute/short term and long-term inhalation exposures to sulphuric acid (or formed sulphuric acid) associated with ES 13, the 90th percentile (e.g. worst case) inhalation exposure concentrations derived using the ART model for relevant PROC codes were compared with the DNEL value for acute local respiratory effects and the DNEL value for long-term local respiratory effects respectively. The results of the risk characterisation are shown in the table below.

The predicted acute/short-term and long-term inhalation exposure concentrations derived using the ART model were not found to exceed the DNEL value for acute local respiratory effects or the DNEL value for long-term local respiratory effects respectively for any of the processes associated with ES 13. On the basis of the assumptions made in the exposure assessment and this risk characterisation, it can be concluded that inhalation exposures to sulphuric acid that may potentially arise during processes associated with ES 13 do not pose an unacceptable health risk to workers.

Information for worker contributing scenario 2, 3, 4, 5, 6 and 7:

List of inputs used in the ART assessment

	PROC	Parameters/ assumptions
Exposure duration	All	480 mins
Product type	All	Liquid (low viscosity – like water)
Process temperature	All	Room temperature (15-25°C)
Vapour pressure	All	Substance is considered to be low volatile, exposure to mists is estimated
Liquid weight fraction	All	0.1
Primary emission source proximity	All	Primary emission source located in the breathing zone of the workers (i.e. Within 1 metre)
Activity class	PROC 2,8a,8b,9	Transfer of liquid products
	PROC 5,13	Activities with open liquid surface or reservoirs
	PROC 10	Spreading of liquid products
Containment	PROC 2,8a,9	Handling reduces contact between product and adjacent air
	PROC 5,8b,10,13	n/a
Localised controls	PROC 2,5	LEV
	PROC,8a,8b,9,10,13	none
Fugative emission source	All	Not fully enclosed – effective housekeeping practices in place
Dispersion	All	Indoors, any sized room, only good natural ventilation

List of derived exposure concentrations

Description of activity	PROC	Physical state of material	Estimated Short-term Exposure Concentrations (mg/m ³)		Estimated Long-term Exposure Concentration (mg/m ³)	
			50 th percentile value	90 th percentile value	50 th percentile value	90 th percentile value
Use in closed, continuous process with occasional controlled exposure (including sampling and maintenance)	2	Liquid	1.40E-04	0.00055	1.90E-04	4.80E-04
Mixing or blending in batch process for formulation of	5	Liquid	0.015	0.061	0.021	0.053

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

preparations or articles (multistage and/or significant contact)						
Transfer of 10% sulphuric acid cleaning solution to/from large vessels/containers at dedicated facilities	8a	Liquid	0.0014	0.0055	0.0019	0.0048
Transfer of 10% sulphuric acid cleaning solution to/from large vessels/containers at non-dedicated facilities	8b	Liquid	0.0014	0.0055	0.0019	0.0048
Filling small containers with 10% sulphuric acid cleaning solution	9	Liquid	0.0014	0.0055	0.0019	0.0048
Applying 10% sulphuric acid cleaning solutions using brush or roller.	10	Liquid	0.15	0.61	0.21	0.53
Cleaning articles by dipping/immersing in 10% sulphuric acid solution	13	Liquid	1.50E-03	0.0061	2.10E-03	0.0053

List of derived RCRs

Exposure details	CES	PROC Code	ES 13- 90 th exposure concentrations (mg/m3)	Leading toxic end point / Critical effect	DNEL (mg/m3)	Risk characterisation ratio
Acute-local effects	CES 2	PROC 2	5.5×10^{-4}	Respiratory irritation and corrositivity	0.1	5.5×10^{-3}
	CES 3	PROC 5	6.1×10^{-2}	Respiratory irritation and corrositivity	0.1	6.1×10^{-1}
	CES 4	PROC 8a	5.5×10^{-3}	Respiratory irritation and corrositivity	0.1	5.5×10^{-2}
		PROC 8b	5.5×10^{-3}	Respiratory irritation and corrositivity	0.1	5.5×10^{-2}
	CES 5	PROC 9	5.5×10^{-3}	Respiratory irritation and corrositivity	0.1	5.5×10^{-2}
	CES 6	PROC 10	6.1×10^{-1} (3×10^{-2})*	Respiratory irritation and corrositivity	0.1	6.1×10^0 (3×10^{-1})*
	CES 7	PROC 13	6.1×10^{-3}	Respiratory irritation and corrositivity	0.1	6.1×10^{-2}
Long-term – local effects	CES 2	PROC 2	4.8×10^{-4}	Respiratory irritation and corrositivity	0.05	9.6×10^{-3}
	CES 3	PROC 5	5.3×10^{-2} (2.7×10^{-3})*	Respiratory irritation and corrositivity	0.05	1.1×10^0 (5.3×10^{-2})*

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

	CES 4	PROC 8a	4.8×10^{-3}	Respiratory irritation and corrositivity	0.05	9.6×10^{-2}
		PROC 8b	4.8×10^{-3}	Respiratory irritation and corrositivity	0.05	9.6×10^{-2}
	CES 5	PROC 9	4.8×10^{-3}	Respiratory irritation and corrositivity	0.05	9.6×10^{-2}
	CES 6	PROC 10	5.3×10^{-1} (2.7×10^{-2})*	Respiratory irritation and corrositivity	0.05	1.1×10^1 (0.54)*
	CES 7	PROC 13	5.3×10^{-3}	Respiratory irritation and corrositivity	0.05	1.1×10^{-1}

*Assumes Respiratory Protective Equipment (95% reduction) is worn

Assessment of dermal risk

During the processes that will be carried out for all the exposure scenarios associated with production and use of sulphuric acid a potential risk may arise if sulphuric acid comes into contact with human skin. This is due to the nature of sulphuric acid and its ability to cause chemical burns. As this effect is considered to be related to the corrosivity of sulphuric acid a threshold DNEL cannot be established for this risk and so measures to control this risk should be assessed in a qualitative manner. Though this risk is most pertinent when workers may come into contact with concentrated sulphuric acid in an industrial setting the operational conditions (OCs) and risk management measures (RMMs) used to control and manage the risk of dermal contact events may be equally applicable across all the exposure scenarios.

In the industrial setting an acute risk of dermal burns from exposure to sulphuric acid in its concentrated form (or its dilute form) exists due to possible splashing of the liquid acid. This risk would be highest at times of transfer to tankers, filling of barrels and filling of small vessels etc. Though these events are considered unlikely due to the high degree of system closure and control the risk is still protected against in order to eliminate any possible routes of exposure.

The risk of dermal contact is reduced due to the OC's in place. The specialised nature of the systems and the degree of closure associated with them ensure the potential for dermal contact is minimised. All pipes and transfers lines are closed and sealed in order to reduce possible exposure to leaks or splashes, as are the reactors to reduce possible emissions. During times of transfer to/from road tankers gas displacement lines and special connecting systems are in place to reduce the levels of gaseous emissions that could deposit to surfaces including human skin. Specialised tanker coupling/uncoupling systems and targeted purging systems may be used in certain circumstances where large volumes and high concentrations are required. Training and certification ensures the workers understand the correct procedures for use of these specialized systems so that the measures in place to reduce emissions are conducted so proper function can be maintained.

In addition to the measures in place to reduce system emissions, workers are completely separated from the site of operation. Workers are generally housed in areas segregated from the main emission sources and time spent on tasks which require close proximity to the emission sources can be minimised effectively. Separate control rooms, screens and outdoor reactor units help to keep workers away from

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

any potential sources of exposure. Emergency measures (and training on procedures and safe work practice) are in place in the industrial setting to ensure that any unforeseen events are safely dealt with in the case that they do arise. These measures range from procedural policies which are in place to guide workers in the proper response in the case of splashes or spills to dedicated equipment (such as emergency showers or spill clean-up kits) which can be used to minimise any effects should unforeseen exposure arise.

Personal protective equipment (PPE) should be supplied to any personnel who may be working in areas where potential emission sources (such as transfer pipes) are located. Suitable PPE that should be used to prevent dermal contact for workers would be acid resistant clothing, helmets, gloves, goggles and boots. The PPE should be properly maintained and certified and should be replaced when required. These measures combined will effectively function to ensure three aspects of safe use. These are, firstly, reduction of potential emissions with specialised systems. Secondly reduction of the potential for exposure of workers by means such as segregation and training and thirdly physical protection of the worker with the use of correct PPE. With the combination of these measures it is considered that the risk of chemical burns to workers is adequately managed.

As mentioned above when the concentration of the sulphuric acid decreases so does the potential for chemical burns to human skin. However the same measures are still in place to ensure that workers, professionals and consumers are protected from risk.

13.4

Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environmental releases:

In order to work within the boundaries of the ES the following conditions should be met:

- Emission to air after scrubbing less than 1,370 kg per day
- Environmental emissions are limited by emission to the STP.
- Waste stream treatment may be used to reduce environmental exposure.
- Gas displaced following use of sulphuric acid in industrial cleaning is processes with the use of LEV.
- Measured emissions should be confirmed to be less than the relevant PNECs in section 3.

Worker exposure:

In order to work within the boundaries of the ES the following conditions should be met:

- LEV is in place to capture gaseous emissions and reduce the potential for exposure.
- Workers should wear protective anti-acid gloves, goggles, overalls and boots at all times in the production and transfer area.
- Workers should be suitably trained in the correct use of all machinery and PPE used in industrial cleaning.
- Any measured exposure should be confirmed to be less than the relevant DNELs in section 3 above.

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

13.5

Additional good practice advice beyond the REACH CSA.

- Do not eat, drink or smoke when working with sulphuric acid.
- Always wash hands and exposed skin thoroughly after using sulphuric acid or any surfaces/machinery that may have come into contact with sulphuric acid.
- Workers should be suitably trained in all safety procedures and in the safe handling of sulphuric acid to prevent risk of exposure.
- All PPE should be properly maintained and stored in an appropriate way so as not to damage its integrity. Workers should be correctly trained in its use.
- Procedural and safety compliance should be routinely assessed by management
- Machinery should be regularly maintained and checked for proper function
- Efficacy of all emission RMMs and waste treatment procedures should be routinely assessed and confirmed to be functioning correctly

14

Exposure Scenario 14: Use of sulphuric acid in the mixing, preparation and repackaging of sulphuric acid.

Use of sulphuric acid in the mixing, preparation and repackaging of sulphuric acid.

Processes Covered:

Environmental Releases

ERC02: Formulation of preparations

Worker Processes

PROC01: Use in closed process, no likelihood of exposure

PROC03: Use in closed batch process (synthesis or formulation)

PROC05: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

PROC08a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC08b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC09: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

Sulphuric acid may be used during mixing, repackaging, preparation and in the production of oleum. Oleum is produced using sulphur trioxide which is dissolved in concentrated sulphuric acid. Sulphuric acid is used in this manner is generally recycled by dilution of the produced oleum.

Because of the processes involved in the use of sulphuric acid, (and the nature of sulphuric acid and the produced gases), specially trained workers and systems are employed.

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Contributing Environmental Scenario: CES1 Environmental exposure arising due to the use of sulphuric acid in the mixing, preparation and repackaging of sulphuric acid. (ERC 02).

Contributing Worker Scenarios: CES 2: worker exposure due to day to day use in closed processes, no likelihood of exposure (PROC 1), CES 3: worker exposure arising due to day to day use in closed batch process (PROC 3), CES 4: worker exposure due to mixing or blending in batch processes for formulation of preparations and articles in an industrial setting (PROC 5), CES 5: worker exposure due to transfer of substance to and from vessels and containers at non-dedicated and dedicated facilities (PROC 8a and PROC 8b), CES 6: worker exposure due to transfer of formulations or preparations to small containers (PROC 9).

14.1 Controlling environmental exposure for ES 14

ES14 Contributing exposure scenario (CES) 1 Environmental exposure arising due to use of sulphuric acid in the mixing, preparation and repackaging of sulphuric acid.

Section 2.1 describes the environmental releases that may occur during the use of sulphuric acid in the mixing, preparation and repackaging of sulphuric acid. These releases may potentially occur due to emission to wastewater or through emission to the atmosphere. Environmental emissions are limited by designated waste treatment process designed to limit environmental exposure to all relevant compartments. Waste gas emissions are scrubbed and may also then be diverted to the wastewater stream. This significantly lessens the possible emission by atmospheric deposition to soil or surface waters.

Liquid wastes are treated (neutralization to neutral pH) prior to emission to remove any sulphuric acid in the waste water and sludge from the waste water treatment plant is sent for incineration or landfill and is not used for agricultural spreading. This precludes any contamination of soil by sludge spreading. Waste water treatment is usually carried out by neutralisation followed by flocculation or decantation.

Use of sulphuric acid in mixing, preparation and repackaging is generally continuous with constant production and use. Facilities may generally produce between 100 and 500 tonnes per day in a large facility, with up to 300,000 tonnes produced per year at the largest European manufacturing plant in a working year of 365 days. This value has been considered as a worst case assumption for this environmental exposure scenario.

Product characteristics

The produced substance is a liquid with purity of greater than 90 %. The substance is colourless, odourless inorganic liquid which is miscible with water. Sulphuric acid is not flammable and is non-explosive.

Amounts used

Facilities may generally produce between 100 and 500 tonnes per day in a large facility, with up to 300,000 tonnes produced per year at the largest European manufacturing plant operating 365 days a year. This value has been considered as a worst case assumption for this environmental exposure scenario.

Frequency and duration of use

Continuous production and release.

Environmental factors influenced by risk management

On site WWTP with the capacity for complete neutralization. Emissions to air may be as much as 205

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

kg/d but are generally much less.	
Other operational conditions affecting environmental exposure	
Use of sulphuric acid in mixing, preparation and repackaging takes place in a highly specialized indoor facility with emissions to water being fully neutralized before release. Reactors and transfer pipelines are closed systems. Waste gas emissions are scrubbed and may also be diverted to the wastewater stream.	
Technical conditions and measures at process level (source) to prevent release	
As mentioned above reactors and pipelines are fully sealed. Both production and sampling are carried out in dedicated facilities. Transfer operations are carried out under controlled conditions in sealed systems to reduce potential losses.	
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Sulphuric acid is used in mixing, preparation and repackaging on a large scale, generally on major chemical sites, which will have dedicated effluent treatment facilities, involving both chemical and biological treatment, coping with many chemical substances. As such any emission to wastewater will be almost instantly hydrolysed before even reaching the STP.	
Neutralisation procedures are in place to ensure that the pH of any downstream biological treatment or final receiving waters is not affected. All waste waters should be treated in this manner. Measured pH values can be used to confirm the efficacy of the neutralization procedure.	
Organizational measures to prevent/limit releases from site	
Workers are fully trained in order to prevent accidental release. The gaseous outflow is continually analysed for waste gases associated with sulphuric acid use.	
Conditions and measures related to municipal STP	
Emissions to the municipal STP should not be made. All waste water should be treated in the on-site waste water treatment plant. Precipitated sludge should be sent for specialized waste treatment and should not be spread to soil.	
Conditions and measures related to external treatment of waste for disposal	
Sludge from the on-site WWTP would normally be sent to specialized landfill or for incineration at a dedicated waste facility. Waste from any scrubbers should be directed to waste water. There is no further generation of solid waste.	
Conditions and measures related to external recovery of waste	
There is no envisaged external recovery of waste.	
14.2	Controlling worker exposure for ES 14
ES 14: CES 2: worker exposure due to day to day use in closed processes, no likelihood of exposure (PROC 1), CES 3: worker exposure arising due to day to day use in closed batch process (PROC 3), CES 4: worker exposure due to mixing or blending in batch processes for formulation of preparations and articles in an industrial setting (PROC 5), CES 5: worker exposure due to transfer of substance to and from vessels and containers at non-dedicated and dedicated facilities (PROC 8a and PROC 8b), CES 6: worker exposure due to transfer of formulations or preparations to small containers (PROC 9).	
During the use of sulphuric acid mixing, preparation and repackaging, controlled systems are in place to reduce the potential for worker exposure in all cases.	
Loading and unloading of tankers with sulphuric acid or oleum is usually performed in the open air.	

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Workers wear protective clothing (face/eye protection, respiratory protection, helmet, anti-acid gloves boots and protective overall). A safety shower is required nearby in case of accidental spillage. Gas displacement lines are also used if filling of road tankers takes place under cover.	
Product characteristics	
The produced substance is a liquid with purity greater than 90%. The substance is colourless, odourless inorganic liquid which is miscible with water. Sulphuric acid is not flammable and is non-explosive.	
Amounts used	
Facilities may generally produce between 100 and 500 tonnes per day in a large facility, with up to 300,000 tonnes produced per year at the largest European manufacturing plant operating 365 days a year.	
Frequency and duration of use exposure	
Workers perform standard shifts of 8 hours per day and have standard working years of 220 days per year. However, the activities associated with this exposure scenario are not expected to take 8 hours to complete and so, are considered to be a worst case assumption.	
Human factors not influenced by risk management	
Respiration volumes under conditions of use 10m ³ /d (default value for a worker breathing for an 8h work day in RIP 3.2).	
Other given operational conditions affecting worker exposure	
Mixing, preparing and repackaging sulphuric acid is conducted by trained personnel. LEV is in place to capture gaseous emissions, reducing the potential for exposure. Workers involved in the loading/unloading of sulphuric acid or the handling of sulphuric acid wear protective clothing (face/eye protection, helmet, anti-acid gloves boots and protective overalls). Workers are also trained in the correct and appropriate handling procedures and protective equipment is intended to cope with the worst case scenario, in order to minimise exposure and risks.	
Technical conditions and measures at process level (source) to prevent release	
LEV used to capture gaseous emissions reduces the potential for exposure.	
Technical conditions to control dispersion from source towards worker	
Any gas displaced from containers is removed by LEV. During the use of sulphuric acid as a laboratory reagent, special equipment and controlled systems with little or no potential for exposure are used to prevent losses occurring. Workers are generally separated from the machinery and installations housing the machinery to minimize the potential for exposure.	
Organizational measures to prevent/limit release	
Workers involved in the handling and transfer of materials are trained in the procedures and protective equipment is intended to cope with the worst case scenario, in order to minimise exposure and risks.	
Conditions and measures related to personal protection, hygiene and health.	
Anti-acid gloves, goggles, chemical resistant overalls and work boots are worn by all operators in the facility to prevent dermal exposure.	
14.3	Exposure estimation and reference to its source

Environmental Exposure

For the tier 1 risk characterisation PECs derived using the ERC defaults are not assessed below as the PECs are considered unrealistically high and would lead to a failing risk assessment in any case. For the tier 2 risk characterisation the PECs calculated by the EUSES environmental model with refined inputs taking into account the emission RMMs as discussed in section 2.1 above are used to control

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

environmental releases are used for the assessment.

Information for contributing exposure scenario 1:

List of exposure concentrations

Compartment	PEC	Justification
Freshwater (in mg/L)	4.43×10^{-5}	Wide dispersive dilution.
Marine water (in mg/L)	6.42×10^{-6}	
Intermittent releases to water (in mg/L)	NA	Intermittent release not relevant
Freshwater sediment (in mg/kg)	3.56×10^{-5}	
Marine sediment (in mg/kg)	5.16×10^{-6}	
Agricultural soil (averaged over 30 days (in mg/kg)	9.42×10^{-4}	
Groundwater (in mg/L)	0.007	
Annual average PEC in air, total (mg/m ³)	0.0571	

The following RCRs were derived taking into account derived PNEC values

Compartments	PEC mg/L	PNEC mg/L	PEC/PNEC	Comments
Tier 2 Freshwater	4.43×10^{-5}	0.0025	0.01	Safe use demonstrated in tier 2
Tier 2 Sediment	3.56×10^{-5}	0.002 (EPM)	0.0178	Safe use demonstrated in tier 2
Tier 2 Marine sediment	5.16×10^{-6}	0.002 (EPM)	0.0025	Safe use demonstrated in tier 2
Tier 2 Marine	6.42×10^{-6}	0.00025	0.0256	Safe use demonstrated in tier 2

* EPM = equilibrium partitioning method

Worker exposure

The Advanced REACH tool (ART) was used to estimate worker exposure as it was considered that the ECETOC model cannot estimate in a satisfactory manner the effects of the stringent containment and segregation practices which are in place to deal with sulphuric acid production and to limit exposure.

In the characterisation of the human health risks posed by acute/short term and long-term inhalation exposures to sulphuric acid (or formed sulphuric acid) associated with ES 14, the 90th percentile (e.g. worst case) inhalation exposure concentrations derived using the ART model for relevant PROC codes were compared with the DNEL value for acute local respiratory effects and the DNEL value for long-term local respiratory effects respectively. The results of the risk characterisation are shown in the table below.

The predicted acute/short-term and long-term inhalation exposure concentrations derived using the ART model were not found to exceed the DNEL value for acute local respiratory effects or the DNEL value

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

for long-term local respiratory effects respectively for any of the processes associated with ES 14. On the basis of the assumptions made in the exposure assessment and this risk characterisation, it can be concluded that inhalation exposures to sulphuric acid that may potentially arise during processes associated with ES 14 do not pose an unacceptable health risk to workers.

Information for worker contributing scenario 2, 3, 4, 5 and 6:

List of inputs used in the ART assessment

	PROC	Parameters/ assumptions
Exposure duration	All	480 mins
Product type	All	Liquid (medium viscosity – like oil)
Process temperature	PROC 1,3	Hot processes (50-150oC)
	PROC 5,8a,8b, 9	Room temperature (15-25oC)
Vapour pressure	All	Substance is considered to be low volatile, exposure to mists is estimated
Liquid weight fraction	All	0.98
Primary emission source proximity	PROC 1,	Primary emission source is not located in the breathing zone of the worker - the assessment for this activity involves a primary far-field emission source only (workers are in a control room)
	PROC 3,5,8a,8b,9	Primary emission source located in the breathing zone of the workers (i.e. Within 1 metre)
Activity class	PROC 1,3,8a,8b,9	Transfer of liquid products
	PROC 5	Activities with open liquid surfaces
Containment	PROC 1,3,9	Handling reduces contact between product and adjacent air
	PROC 5,8a8b	n/a
Localised controls	PROC 1,3,8b,	Vapour recovery systems; LEV
	PROC 2,9	Vapour recovery
	PROC 5	LEV
Segregation	PROC 1	Complete segregation of workers in separate control room
Fugitive emission source	PROC 1,3,8b,9	Process fully enclosed – not breached for sampling
	PROC 5,8a	Not fully enclosed – effective housekeeping practices in place.
Dispersion	PROC 1, 8a, 8b	Outdoors not close to buildings
	PROC 3	Outdoors near to buildings
	PROC 5,9	Indoors, any sized room, only good natural ventilation

List of derived exposure concentrations

Description of activity	PROC	Physical state of material	Estimated Short-term Exposure Concentrations (mg/m ³)		Estimated Long-term Exposure Concentration (mg/m ³)	
			50 th percentile value	90 th percentile value	50 th percentile value	90 th percentile value
Use in closed process, no likelihood of exposure	1	Liquid	8.20 x 10 ⁻¹⁰	9.30 x 10 ⁻⁰⁹	3.60 x 10 ⁻⁰⁹	9.40 x 10 ⁻⁰⁹

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

Use in closed batch process (synthesis or formulation)	3	Liquid	3.70×10^{-05}	4.20×10^{-04}	1.60×10^{-04}	4.20×10^{-04}
Mixing or blending in batch process for formulation of preparations or articles (multistage and/or significant contact)	5	Liquid	0.0045	0.018	0.0063	0.016
Transfer of substances from/to vessels/large containers at non-dedicated facilities (exposure can occur)	8a	Liquid	0.002	0.023	0.0088	0.023
Transfer of substances from/to vessels/large containers at dedicated facilities	8b	Liquid	1.10×10^{-05}	1.20×10^{-04}	4.80×10^{-05}	4.80×10^{-06}
Transfer of substance into small containers (dedicated filling line - vapour/aerosol control)	9	Liquid	0.00081	0.0032	0.0011	0.0028

List of derived RCRs

Exposure details	CES	PROC Code	ES 13- 90 th exposure concentrations (mg/m3)	Leading toxic end point / Critical effect	DNEL (mg/m3)	Risk characterisation ratio
Acute-local effects	CES 2	PROC 1	9.3×10^{-9}	Respiratory irritation and corrositivity	0.1	9.3×10^{-8}
	CES 3	PROC 3	4.2×10^{-4}	Respiratory irritation and corrositivity	0.1	4.2×10^{-3}
	CES 4	PROC 5	1.8×10^{-2}	Respiratory irritation and corrositivity	0.1	1.8×10^{-1}
	CES 5	PROC 8a	2.3×10^{-2}	Respiratory irritation and corrositivity	0.1	2.3×10^{-1}
		PROC 8b	1.2×10^{-4}	Respiratory irritation and corrositivity	0.1	1.2×10^{-3}
	CES 6	PROC 9	3.2×10^{-3}	Respiratory irritation and corrositivity	0.1	3.2×10^{-2}
Long-term – local effects	CES 2	PROC 1	9.4×10^{-9}	Respiratory irritation and corrositivity	0.05	1.9×10^{-7}
	CES 3	PROC 3	4.2×10^{-4}	Respiratory irritation and corrositivity	0.05	8.4×10^{-3}
	CES 4	PROC 5	1.6×10^{-2}	Respiratory irritation and corrositivity	0.05	3.2×10^{-1}

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

	CES 5	PROC 8a	2.3×10^{-2}	Respiratory irritation and corrositivity	0.05	4.6×10^{-1}
		PROC 8b	4.8×10^{-6}	Respiratory irritation and corrositivity	0.05	9.6×10^{-5}
	CES 6	PROC 9	2.8×10^{-3}	Respiratory irritation and corrositivity	0.05	5.6×10^{-2}

*Assumes Respiratory Protective Equipment (95% reduction) is worn

Assessment of dermal risk

During the processes that will be carried out for all the exposure scenarios associated with production and use of sulphuric acid a potential risk may arise if sulphuric acid comes into contact with human skin. This is due to the nature of sulphuric acid and its ability to cause chemical burns. As this effect is considered to be related to the corrosivity of sulphuric acid a threshold DNEL cannot be established for this risk and so measures to control this risk should be assessed in a qualitative manner. Though this risk is most pertinent when workers may come into contact with concentrated sulphuric acid in an industrial setting the operational conditions (OCs) and risk management measures (RMMs) used to control and manage the risk of dermal contact events may be equally applicable across all the exposure scenarios.

In the industrial setting an acute risk of dermal burns from exposure to sulphuric acid in its concentrated form (or its dilute form) exists due to possible splashing of the liquid acid. This risk would be highest at times of transfer to tankers, filling of barrels and filling of small vessels etc. Though these events are considered unlikely due to the high degree of system closure and control the risk is still protected against in order to eliminate any possible routes of exposure.

The risk of dermal contact is reduced due to the OC's in place. The specialised nature of the systems and the degree of closure associated with them ensure the potential for dermal contact is minimised. All pipes and transfers lines are closed and sealed in order to reduce possible exposure to leaks or splashes, as are the reactors to reduce possible emissions. During times of transfer to/from road tankers gas displacement lines and special connecting systems are in place to reduce the levels of gaseous emissions that could deposit to surfaces including human skin. Specialised tanker coupling/uncoupling systems and targeted purging systems may be used in certain circumstances where large volumes and high concentrations are required. Training and certification ensures the workers understand the correct procedures for use of these specialized systems so that the measures in place to reduce emissions are conducted so proper function can be maintained.

In addition to the measures in place to reduce system emissions, workers are completely separated from the site of operation. Workers are generally housed in areas segregated from the main emission sources and time spent on tasks which require close proximity to the emission sources can be minimised effectively. Separate control rooms, screens and outdoor reactor units help to keep workers away from any potential sources of exposure. Emergency measures (and training on procedures and safe work practice) are in place in the industrial setting to ensure that any unforeseen events are safely dealt with in the case that they do arise. These measures range from procedural policies which are in place to guide workers in the proper response in the case of splashes or spills to dedicated equipment (such as

Annex to the extended Safety Data Sheet (eSDS)

Sulphuric acid

emergency showers or spill clean-up kits) which can be used to minimise any effects should unforeseen exposure arise.

Personal protective equipment (PPE) should be supplied to any personnel who may be working in areas where potential emission sources (such as transfer pipes) are located. Suitable PPE that should be used to prevent dermal contact for workers would be acid resistant clothing, helmets, gloves, goggles and boots. The PPE should be properly maintained and certified and should be replaced when required. These measures combined will effectively function to ensure three aspects of safe use. These are, firstly, reduction of potential emissions with specialised systems. Secondly reduction of the potential for exposure of workers by means such as segregation and training and thirdly physical protection of the worker with the use of correct PPE. With the combination of these measures it is considered that the risk of chemical burns to workers is adequately managed.

As mentioned above when the concentration of the sulphuric acid decreases so does the potential for chemical burns to human skin. However the same measures are still in place to ensure that workers, professionals and consumers are protected from risk.

14.4

Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environmental releases:

In order to work within the boundaries of the ES the following conditions should be met:

- Emission to air after scrubbing less than 205 kg per day
- No emission to the municipal STP
- The industrial WWTP sludge should not be spread to soil
- Wastewater should be fully neutralized
- Measured emissions should be confirmed to be less than the relevant PNECs in section 3.

Worker exposure:

In order to work within the boundaries of the ES the following conditions should be met:

- LEV is in place to capture gaseous emissions and reduce the potential for exposure.
- Workers should wear protective anti-acid gloves, goggles, overalls and boots at all times in the production and transfer area.
- Respiratory equipment should be worn if required.
- Workers should be suitably trained in the correct use of all machinery and PPE used in industrial cleaning.
- Any measured exposure should be confirmed to be less than the relevant DNELs in section 3 above.

Annex to the extended Safety Data Sheet (eSDS) Sulphuric acid

14.5

Additional good practice advice beyond the REACH CSA.

- Do not eat, drink or smoke when working with sulphuric acid.
- Always wash hands and exposed skin thoroughly after using sulphuric acid or any surfaces/machinery that may have come into contact with sulphuric acid.
- Workers should be suitably trained in all safety procedures and in the safe handling of sulphuric acid to prevent risk of exposure.
- All PPE should be properly maintained and stored in an appropriate way so as not to damage its integrity. Workers should be correctly trained in its use.
- Procedural and safety compliance should be routinely assessed by management
- Machinery should be regularly maintained and checked for proper function
- Efficacy of all emission RMMs and waste treatment procedures should be routinely assessed and confirmed to be functioning correctly